


High Density Foam



RoHS
Compliant



Specifications:

Construction	: Polyurethane open cell, carbon/acrylic impregnated
Corrosion Resistance	: per MIL-STD 883C, Method 1004.2
Density (approx.)	: 2.5/ft. 3±10%
Tensile Strength	: 20 psi, min.
Tear Strength	: 2.0/l in.
Elongation	: 150% min.
Recommended Operating Temp. Range (within 24 hr exposure period)	: -20°F to +250°F

Electrical Properties:

Surface Resistivity	: 10E3 - 10E5 Ω per ASTM-D257
Volume Resistivity	: 10E3 - 10E5 Ω per ASTM-D257
Charge Decay	: Less than 0.05 seconds from 5KV per FTMS 101C, Method 4046.1

Packaging:

Product to be packaged with Duratool label

Part Number Table

Description	Part Number
High Density Foam, 1/4" × 24" × 36"	MC23781
High Density Foam, 3/8" × 24" × 36"	MC23782

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. DURATOOL is the registered trademark of the Group. © Premier Farnell plc 2012.

