Microsoft* Microsoft* Comfort Mouse 4500 for Business 4500 Microsoft® BlueTrack™ Technology







Technical Data Sheet

Version Information	
Product Name	Microsoft Comfort Mouse 4500 for Business
Product Version	Microsoft Comfort Mouse 4500 v1.0
Mouse Version	Microsoft Comfort Mouse 4500 v1.0
Product Dimensions	
Mouse Length	4.57 inches (116 millimeters)
Mouse Width	2.67 inches (67.9 millimeters)
Mouse Depth/Height	1.66 inches (42.3 millimeters)
Mouse Weight	4.62 ounces (131 grams)
Mouse Cable Length	76 inches (1930 millimeters +/- 85 millimeters)
Compatibility and Localization	
Interface	USB compatible Microsoft Windows[®] 7, Windows Vista[®], and Windows XP with Service Pack 2 (excluding Windows XP 64-bit)
Operating Systems	Macintosh Mac OS X v10.4x-10.6x
Top-line System Requirements	For Windows-based PC: Requires a PC that meets the requirements for and has installed one of these operating systems: • Windows 7, Windows Vista, or Windows XP with Service Pack 2 (excluding Windows XP 64-bit) • 100 MB of available hard disk space • IntelliPoint software version 7.1 For Macintosh: • Mac OSX v10.4x-10.6x
	30 MB of available hard disk space
O and a the life is a second	IntelliPoint for Mac software version 7.1
Compatibility Logos	Compatible with Microsoft Windows 7 Mac logo Universal Mac logo Certified USB logo
Software Localization	For a Microsoft Windows-based PC: Microsoft IntelliPoint software may be installed in Simplified Chinese, Traditional Chinese, English, French, German, Italian, Japanese, Korean, Brazilian Portuguese, Iberian Portuguese, or Spanish. If available, standard setup will install the software in the default OS language. Otherwise, the English language version will be installed.
	For a Macintosh PC: Microsoft IntelliPoint for Mac will install in English, French, German, Italian, Japanese, Brazilian Portuguese, and Spanish. User settings for OS language preference determine which localized version of the software is displayed. In the event that OS language preferences are not supported, the English language version will be displayed.
Tracking Technology	
Mouse Tracking System	Microsoft-proprietary BlueTrack™ Technology
Imaging Rate	Dynamically adaptable to 8000 frames per second 1000 points per inch (39.4 points per millimeter)
X-Y Resolution	
Tracking Speed	Up to 72 inches (1829 millimeters) per second
Tracking Speed Product Feature Performance	Up to 72 inches (1829 millimeters) per second
Tracking Speed Product Feature Performance Mouse Button Features	Up to 72 inches (1829 millimeters) per second 5 buttons including scroll wheel button
Tracking Speed Product Feature Performance Mouse Button Features Right & Left Button Life	Up to 72 inches (1829 millimeters) per second 5 buttons including scroll wheel button 3,000,000 actuations at no more than 4 actuations per second
Tracking Speed Product Feature Performance Mouse Button Features Right & Left Button Life Side Button Life	Up to 72 inches (1829 millimeters) per second 5 buttons including scroll wheel button 3,000,000 actuations at no more than 4 actuations per second 1,000,000 actuations at no more than 4 actuations per second
Tracking Speed Product Feature Performance Mouse Button Features Right & Left Button Life Side Button Life Wheel Button Life	Up to 72 inches (1829 millimeters) per second 5 buttons including scroll wheel button 3,000,000 actuations at no more than 4 actuations per second 1,000,000 actuations at no more than 4 actuations per second 350,000 actuations at no more than 4 actuations per second
Tracking Speed Product Feature Performance Mouse Button Features Right & Left Button Life Side Button Life Wheel Button Life Mouse Scrolling Features	Up to 72 inches (1829 millimeters) per second 5 buttons including scroll wheel button 3,000,000 actuations at no more than 4 actuations per second 1,000,000 actuations at no more than 4 actuations per second 350,000 actuations at no more than 4 actuations per second Tilt wheel enables vertical and horizontal scrolling
Tracking Speed Product Feature Performance Mouse Button Features Right & Left Button Life Side Button Life Wheel Button Life	Up to 72 inches (1829 millimeters) per second 5 buttons including scroll wheel button 3,000,000 actuations at no more than 4 actuations per second 1,000,000 actuations at no more than 4 actuations per second 350,000 actuations at no more than 4 actuations per second Tilt wheel enables vertical and horizontal scrolling • 100,000 revolutions (away from user) at no more than 60 rotations per minute
Tracking Speed	Up to 72 inches (1829 millimeters) per second 5 buttons including scroll wheel button 3,000,000 actuations at no more than 4 actuations per second 1,000,000 actuations at no more than 4 actuations per second 350,000 actuations at no more than 4 actuations per second Tilt wheel enables vertical and horizontal scrolling • 100,000 revolutions (away from user) at no more than 60 rotations per minute • 300,000 revolutions (toward user) at no more than 60 rotations per minute
Tracking Speed Product Feature Performance Mouse Button Features Right & Left Button Life Side Button Life Wheel Button Life Mouse Scrolling Features	Up to 72 inches (1829 millimeters) per second 5 buttons including scroll wheel button 3,000,000 actuations at no more than 4 actuations per second 1,000,000 actuations at no more than 4 actuations per second 350,000 actuations at no more than 4 actuations per second Tilt wheel enables vertical and horizontal scrolling • 100,000 revolutions (away from user) at no more than 60 rotations per minute • 300,000 revolutions (toward user) at no more than 60 rotations per minute -40 °F (-40 °C) to 140 °F (60 °C) at < 5% to 65% relative humidity (non-condensing)
Tracking Speed Product Feature Performance Mouse Button Features Right & Left Button Life Side Button Life Wheel Button Life Mouse Scrolling Features Wheel Vertical Scrolling Life Storage Temperature & Humidity	Up to 72 inches (1829 millimeters) per second 5 buttons including scroll wheel button 3,000,000 actuations at no more than 4 actuations per second 1,000,000 actuations at no more than 4 actuations per second 350,000 actuations at no more than 4 actuations per second Tilt wheel enables vertical and horizontal scrolling • 100,000 revolutions (away from user) at no more than 60 rotations per minute • 300,000 revolutions (toward user) at no more than 60 rotations per minute
Tracking Speed	Up to 72 inches (1829 millimeters) per second 5 buttons including scroll wheel button 3,000,000 actuations at no more than 4 actuations per second 1,000,000 actuations at no more than 4 actuations per second 350,000 actuations at no more than 4 actuations per second Tilt wheel enables vertical and horizontal scrolling • 100,000 revolutions (away from user) at no more than 60 rotations per minute • 300,000 revolutions (toward user) at no more than 60 rotations per minute -40 °F (-40 °C) to 140 °F (60 °C) at < 5% to 65% relative humidity (non-condensing)
Tracking Speed	Up to 72 inches (1829 millimeters) per second 5 buttons including scroll wheel button 3,000,000 actuations at no more than 4 actuations per second 1,000,000 actuations at no more than 4 actuations per second 350,000 actuations at no more than 4 actuations per second Tilt wheel enables vertical and horizontal scrolling • 100,000 revolutions (away from user) at no more than 60 rotations per minute • 300,000 revolutions (toward user) at no more than 60 rotations per minute • 40° F (-40°C) to 140° F (60°C) at < 5% to 65% relative humidity (non-condensing) 32° F (0°C) to 104° F (40°C) at <5% to 80% relative humidity (non-condensing)
Tracking Speed	Up to 72 inches (1829 millimeters) per second 5 buttons including scroll wheel button 3,000,000 actuations at no more than 4 actuations per second 1,000,000 actuations at no more than 4 actuations per second 350,000 actuations at no more than 4 actuations per second Tilt wheel enables vertical and horizontal scrolling • 100,000 revolutions (away from user) at no more than 60 rotations per minute • 300,000 revolutions (toward user) at no more than 60 rotations per minute • 40 °F (-40 °C) to 140 °F (60 °C) at <5% to 65% relative humidity (non-condensing)
Tracking Speed	Up to 72 inches (1829 millimeters) per second 5 buttons including scroll wheel button 3,000,000 actuations at no more than 4 actuations per second 1,000,000 actuations at no more than 4 actuations per second 350,000 actuations at no more than 4 actuations per second 350,000 actuations at no more than 4 actuations per second 350,000 actuations at no more than 4 actuations per second 1100,000 revolutions (away from user) at no more than 60 rotations per minute • 300,000 revolutions (toward user) at no more than 60 rotations per minute • 300,000 revolutions (toward user) at no more than 60 rotations per minute • 40 °F (-40 °C) to 140 °F (60 °C) at <5% to 65% relative humidity (non-condensing)
Tracking Speed	Up to 72 inches (1829 millimeters) per second 5 buttons including scroll wheel button 3,000,000 actuations at no more than 4 actuations per second 1,000,000 actuations at no more than 4 actuations per second 350,000 actuations at no more than 4 actuations per second 3100,000 revolutions (away from user) at no more than 60 rotations per minute • 300,000 revolutions (toward user) at no more than 60 rotations per minute • 40 °F (-40 °C) to 140 °F (60 °C) at <5% to 65% relative humidity (non-condensing)
Tracking Speed Product Feature Performance Mouse Button Features Right & Left Button Life Side Button Life Wheel Button Life Wheel Vertical Scrolling Features Wheel Vertical Scrolling Life Storage Temperature & Humidity Operating Temperature & Humidity Certification Information Country of Manufacturer ISO 14001 Qualified Manufacturer Restriction on Hazardous Substances	Up to 72 inches (1829 millimeters) per second 5 buttons including scroll wheel button 3,000,000 actuations at no more than 4 actuations per second 1,000,000 actuations at no more than 4 actuations per second 350,000 actuations at no more than 4 actuations per second 350,000 actuations at no more than 4 actuations per second 350,000 actuations at no more than 4 actuations per second 1100,000 revolutions (away from user) at no more than 60 rotations per minute • 300,000 revolutions (toward user) at no more than 60 rotations per minute • 300,000 revolutions (toward user) at no more than 60 rotations per minute • 40 °F (-40 °C) to 140 °F (60 °C) at <5% to 65% relative humidity (non-condensing)

Results stated herein are based on internal Microsoft testing. Individual results and performance may vary. Any device images shown are not actual size. This document is provided for informational purposes only and is subject to change without notice. Microsoft makes no warranty, express or implied, with this document or the information contained herein. Review any public use or publications of any data herein with your local legal counsel.

©2011 Microsoft Corporation. The names of actual companies and products mentioned herein may be trademarks of their respective owners.