

**Ordering number CP12817_LXP3-RS2**

Family	Leila	FWHM	10 degrees
Type	Assembly	Efficiency	93 %
LED	XT-E	cd/Im	15.600
Color	White	Gerber File	Available
Diameter	21.6 mm		
Height	14.6 mm		
Style	Round		
Optic Material	PMMA		
Holder Material	PC		
Fastening	Glue		
Status	On production		

**Ordering number CP11632_LXP3-D**

Family	Leila	FWHM	11 degrees
Type	Assembly	Efficiency	-
LED	XT-E	cd/Im	8.950
Color	White	Gerber File	Available
Diameter	21.6 mm		
Height	14.6 mm		
Style	Round		
Optic Material	PMMA		
Holder Material	PC		
Fastening	Glue		
Status	On production		

Suitable for Star PCB

**Ordering number CP11634_LXP3-O-90**

Family	Leila	FWHM	13+41 degrees
Type	Assembly	Efficiency	91 %
LED	XT-E	cd/Im	4.050
Color	White	Gerber File	Available
Diameter	21.6 mm		
Height	14.6 mm		
Style	Round		
Optic Material	PMMA		
Holder Material	PC		
Fastening	Glue		
Status	On production		

**Ordering number CP12395_LXP3-W**

Family	Leila	FWHM	41 degrees
Type	Assembly	Efficiency	89 %
LED	XT-E	cd/Im	1.580
Color	White	Gerber File	Available
Diameter	21.6 mm		
Height	14.6 mm		
Style	Round		
Optic Material	PMMA		
Holder Material	PC		
Fastening	Glue		
Status	On production		

Star PCB compatible.



PRODUCT DATASHEET

Leila series

last update 5/2/2013

NOTE: The typical divergence will be changed by different color, chip size and chip position tolerance. The typical total divergence is the full angle measured where the luminous intensity is half of the peak value.



PRODUCT DATASHEET

Leila series

last update 5/2/2013

GENERAL INFORMATION

- Product series especially designed & optimized for XT-E series of LEDs.
- Special care taken to make light distribution as uniform as possible.
- Lens material optical grade PMMA with high UV and temperature resistance. Allows use of high current and temperature conditions.

Please find more information about used material from below:

http://ledil.fi/sites/default/files/Documents/Technical/Material/PMMA%20N%20UL94_Yellow%20Card.pdf

<http://ledil.fi/sites/default/files/Documents/Technical/Material/PMMA%20N%20PLEXIGLAS-Datasheet.pdf>

- Optic holder molded by high quality PC material (120 degrees of Celcius / 248 degrees of Fahrenheit).


- Fastening to PCB with appropriate adhesive. By clicking link below you can find Ledil recommended glue options.

http://www.ledil.com/datasheets/DataSheet_GLUES.pdf

NOTE 1: We advise customer to ensure the suitability and sufficiency of the bond in the end product. For example, mechanical stress, vibration and holes on the surface of the circuit board weaken the strength of the glue.

NOTE 2: All surfaces where glue is applied must be clean, dry and free from grease and dirt. If cleaning of PCB surfaces is needed, please follow strictly the cleaning instructions of your LED manufacturer -this is important as cleaning shall under no circumstances damage LEDs or other electronics components on the PCB.




Further note that optical components shall not be cleaned with any chemicals - only micro fiber cloth may be used to remove fingerprints or other traces from handling.



Isometric view
Scale: 1:1

Solder pocket

Glue groove



Materials:
Holder: PC white
Lens: PMMA

This drawing is our property.
It can't be reproduced
or communicated without
our written agreement.

LEDIL

L
T
F
F

e
e
l
i
n
N

d
h

DRAWING TITLE

DATASHEET LXP3

DRAWN BY

m

DATE

25.11.2010

CHECKED BY

s n

DATE

25.11.2010

SIZE

A4

DRAWING NUMBER

REV

2

DESIGNED BY

HH

DATE

30.04.2010

SCALE

2:1

WEIGHT (g)


SHEET

1/1


D

A


Luminaire: Ledil Oy CP11632_LXP3-D-WHT (Cree XT-E (AWT) 113lm @ 250mA)
Lamps: 1 x Cree XT-E 113lm @ 250mA




Luminaire: LEDiL Oy CP11634_LXP3-O-90_(XT-E) Eff. 91%
Lamps: 1 x XT-E (106,1lm@250mA) CCT=Cool white P=0.8W I=250mA




Luminaire: Ledil Oy CP12817_LXP3-RS2_(XT-E) Efficiency=92%
Lamps: 1 x Cree XT-E (AWT) 250mA 113lm



Luminaire: Ledil Oy CP11632_LXP3-D-WHT (Cree XT-E (AWT) 113lm @ 250mA)
Lamps: 1 x Cree XT-E 113lm @ 250mA



Luminaire: LEDiL Oy CP11634_LXP3-O-90_(XT-E) Eff. 91%
Lamps: 1 x XT-E (106,1lm@250mA) CCT=Cool white P=0.8W I=250mA



Luminaire: Ledil Oy CP12395_LXP3-W-XT-E (XT-E (AWT) 113lm @ 250mA)
Lamps: 1 x XT-E 113lm @ 250mA

