

Safety Data Sheet according to (EC) No 1907/2006

Page 1 of 10

Loctite 431

sds no. : 169788 V003.5 Revision: 04.04.2013 printing date: 31.10.2013

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Loctite 431 **1.2. Relevant identified uses of the substance or mixture and uses advised against** Intended use: Cyanoacrylate

1.3. Details of the supplier of the safety data sheet

Henkel Limited 2 Bishop Square Business Park AL109EY Herfordshire Hatfield

Great Britain

Phone: +44 1606 593933 Fax-no.: +44 1606 863762

ua-productsafety.uk@uk.henkel.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (DPD):

Xi - Irritant R36/37/38 Irritating to eyes, respiratory system and skin.

2.2. Label elements

Label elements (DPD):

Xi - Irritant



Risk phrases:

R36/37/38 Irritating to eyes, respiratory system and skin.

Safety phrases:

S23 Do not breathe vapour.S24/25 Avoid contact with skin and eyes.S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Additional labeling:

Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.

2.3. Other hazards

None if used properly.

SECTION 3: Composition/information on ingredients

General chemical description:

Cyanoacrylate Adhesive

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Ethyl 2-cyanoacrylate 7085-85-0	230-391-5 01-2119527766-29	> 80- < 100 %	Serious eye irritation 2 H319 Specific target organ toxicity - single exposure 3 H335 Skin irritation 2 H315

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

Declaration of ingredients according to DPD (EC) No 1999/45:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Ethyl 2-cyanoacrylate 7085-85-0	230-391-5 01-2119527766-29	> 80 - < 100 %	Xi - Irritant; R36/37/38

For full text of the R-Phrases indicated by codes see section 16 'Other Information'.

Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Do not pull bonded skin apart. It may be gently peeled apart using a blunt object such as a spoon, preferably after soaking in warm soapy water.

Cyanoacrylates give off heat on solidification. In rare cases a large drop will generate enough heat to cause a burn. Burns should be treated normally after the adhesive has been removed from the skin.

If lips are accidentally stuck together apply warm water to the lips and encourage maximum wetting and pressure from saliva inside the mouth.

Peel or roll lips apart. Do not try to pull the lips apart with direct opposing action.

Eye contact:

If the eye is bonded closed, release eyelashes with warm water by covering with wet pad.

Cyanoacrylate will bond to eye protein and will cause periods of weeping which will help to debond the adhesive.

Keep eye covered until debonding is complete, usually within 1-3 days.

Do not force eye open. Medical advice should be sought in case solid particles of cyanoacrylate trapped behind the eyelid cause any abrasive damage.

Ingestion:

Ensure that breathing passages are not obstructed. The product will polymerise immediately in the mouth making it almost impossible to swallow. Saliva will slowly separate the solidified product from the mouth (several hours).

4.2. Most important symptoms and effects, both acute and delayed

EYE: Irritation, conjunctivitis.

SKIN: Redness, inflammation.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Foam, extinguishing powder, carbon dioxide. Fine water spray

Extinguishing media which must not be used for safety reasons: High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.

5.3. Advice for firefighters

Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Avoid skin and eye contact.

6.2. Environmental precautions

Do not let product enter drains.

6.3. Methods and material for containment and cleaning up

Do not use cloths for mopping up. Flood with water to complete polymerization and scrape off the floor. Cured material can be disposed of as non-hazardous waste.

Dispose of contaminated material as waste according to Chapter 13.

6.4. Reference to other sections

See advice in chapter 8

7.1. Precautions for safe handling

Ventilation (low level) is recommended when using large volumes Use of dispensing equipment is recommended to minimise the risk of skin or eye contact Avoid skin and eye contact. See advice in chapter 8

Hygiene measures:

Wash hands before work breaks and after finishing work. Do not eat, drink or smoke while working. Good industrial hygiene practices should be observed.

7.2. Conditions for safe storage, including any incompatibilities

For optimum shelf life store in original containers under refrigerated conditions at 2 - 8°C (35.6 - 46.4 °F)

7.3. Specific end use(s)

Cyanoacrylate

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for

Great Britain

Ingredient	ppm	mg/m ³	Туре	Category	Remarks
ETHYL CYANOACRYLATE	0,3	1,5	Short Term Exposure		EH40 WEL
7085-85-0			Limit (STEL):		

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Ethyl 2-cyanoacrylate 7085-85-0	worker	inhalation	Long term exposure - local effects		9,25 mg/m3	
Ethyl 2-cyanoacrylate 7085-85-0	worker	inhalation	Long term exposure - systemic effects		9,25 mg/m3	
Ethyl 2-cyanoacrylate 7085-85-0	general population	inhalation	Long term exposure - local effects		9,25 mg/m3	
Ethyl 2-cyanoacrylate 7085-85-0	general population	inhalation	Long term exposure - systemic effects		9,25 mg/m3	

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area Filter type: A

Hand protection:

The use of chemical resistant gloves such as Nitrile is recommended.

Polyethylene or polypropylene gloves are recommended when using large volumes.

Do not use PVC, rubber or nylon gloves.

Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Wear protective glasses.

Skin protection:

Wear suitable protective clothing.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	liquid
- F F	Liquid
	Colorless
Odor	Irritating
Odour threshold	No data available / Not applicable
ъЦ	No data available / Not applicable
pH Initial boiling point	$> 149 \ ^{\circ}C \ (> 300.2 \ ^{\circ}F)$
Flash point	80 - 93,4 °C (176 - 200.12 °F)
Decomposition temperature	No data available / Not applicable
Vapour pressure	0,6600000 mbar
(25,0 °C (77 °F))	0,000000 110ai
Density	1,1000 g/cm3
(20,0 °C (68 °F))	1,1000 g/ellis
Bulk density	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Solubility (qualitative)	Polymerises in presence of water.
(Solvent: Water)	Torymenses in presence of water.
Solubility (qualitative)	Miscible
(Solvent: Acetone)	Wilselble
Solidification temperature	No data available / Not applicable
Melting point	No data available / Not applicable
Flammability	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Explosive limits	No data available / Not applicable
Partition coefficient: n-octanol/water	No data available / Not applicable
Evaporation rate	No data available / Not applicable
Vapor density	No data available / Not applicable
Oxidising properties	No data available / Not applicable
Caldishing properties	The data available / The applicable

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

Rapid exothermic polymerization will occur in the presence of water, amines, alkalis and alcohols.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

No decomposition if used according to specifications.

10.5. Incompatible materials

None if used properly.

10.6. Hazardous decomposition products

None known

SECTION 11: Toxicological information

11.1. Information on toxicological effects

General toxicological information:

The preparation is classified based on the conventional method outlined in Article 6(1)(a) of Directive 1999/45/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Oral toxicity:

Cyanoacrylates are considered to have relatively low toxicity. Acute oral LD50 is >5000mg/kg (rat). It is almost impossible to swallow as it rapidly polymerises in the mouth.

Inhalative toxicity:

Irritating to respiratory system

Prolonged exposure to high concentrations of vapours may lead to chronic effects in sensitive individuals In dry atmosphere with < 50% humidity, vapours may irritate the eyes and respiratory system

Skin irritation:

Irritating to the skin.

Bonds skin in seconds. Considered to be of low toxicity: acute dermal LD50 (rabbit)>2000mg/kg Due to polymerisation at the skin surface allergic reaction is unlikely to occur

Eye irritation:

Irritating to eyes.

Liquid product will bond eyelids. In a dry atmosphere (RH<50%) vapours may cause irritation and lachrymatory effect

Acute oral toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Ethyl 2-cyanoacrylate 7085-85-0	LD50	> 5.000 mg/kg	oral		rat	OECD Guideline 401 (Acute Oral Toxicity)

Acute dermal toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Ethyl 2-cyanoacrylate 7085-85-0	LD50	> 2.000 mg/kg	dermal		rabbit	OECD Guideline 402 (Acute Dermal Toxicity)

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Ethyl 2-cyanoacrylate 7085-85-0	slightly irritating	24 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Ethyl 2-cyanoacrylate 7085-85-0	irritating	72 h	rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
Ethyl 2-cyanoacrylate 7085-85-0	not sensitising		guinea pig	

Germ cell mutagenicity:

Hazardous components	Result	Type of study /	Metabolic	Species	Method
CAS-No.		Route of	activation /		
		administration	Exposure time		
Ethyl 2-cyanoacrylate	negative	mammalian cell	with and without		OECD Guideline 476 (In vitro
7085-85-0	-	gene mutation assay			Mammalian Cell Gene
					Mutation Test)
	negative	bacterial reverse			OECD Guideline 471
	-	mutation assay (e.g			(Bacterial Reverse Mutation
		Ames test)			Assay)
	negative	in vitro mammalian	with and without		OECD Guideline 473 (In vitro
	-	chromosome			Mammalian Chromosome
		aberration test			Aberration Test)

SECTION 12: Ecological information

General ecological information:

Biological and Chemical Oxygen Demands (BOD and COD) are insignificant.

The preparation is classified based on the conventional method outlined in Article 6(1)(a) of Directive 1999/45/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

12.1. Toxicity

Ecotoxicity:

Do not empty into drains / surface water / ground water.

12.2. Persistence and degradability

Persistence and Biodegradability:

No data available.

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
Ethyl 2-cyanoacrylate		aerobic	57 %	OECD Guideline 301 D (Ready
7085-85-0			- / / /	Biodegradability: Closed Bottle
				Test)

12.3. Bioaccumulative potential / 12.4. Mobility in soil

Mobility:

Cured adhesives are immobile.

Bioaccumulative potential:

No data available.

Hazardous components CAS-No.	LogKow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
Ethyl 2-cyanoacrylate 7085-85-0	0,776				22 °C	EU Method A.8 (Partition Coefficient)

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Cured adhesive: Dispose of as water insoluble non-toxic solid chemical in authorised landfill or incinerate under controlled conditions.

Dispose of in accordance with local and national regulations.

Contribution of this product to waste is very insignificant in comparison to article in which it is used

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

14.1.	UN number					
	ADR	Not dangerous goods				
	RID	Not dangerous goods				
	ADNR	Not dangerous goods				
	IMDG	Not dangerous goods				
	IATA	3334				
14.2.	UN proper shipping name					
	ADR	Not dangerous goods				
	RID	Not dangerous goods				
	ADNR	Not dangerous goods				
	IMDG	Not dangerous goods				
	IATA	Aviation regulated liquid, n.o.s. (Cyanoacrylate ester)				
14.3.	Transport haz	Transport hazard class(es)				
	ADR	Not dangerous goods				
	RID	Not dangerous goods				
	ADNR	Not dangerous goods				
	IMDG	Not dangerous goods				
	IATA	9				
		9				
14.4.	Packaging group					
	ADR	Not dangerous goods				
	RID	Not dangerous goods				
	ADNR	Not dangerous goods				
	IMDG	Not dangerous goods				
	IATA	III				
14.5.	Environmenta	l hazards				
	ADR	not applicable				
	RID	not applicable not applicable				
	ADNR					
	IMDG	not applicable not applicable				
	IATA	not applicable				
14.6.	Special precau	itions for user				
	ADR	not applicable				
	RID	not applicable				
	ADNR	not applicable				
	IMDG	not applicable				
	IATA	Primary packs containing less than 500ml are unregulated by this mode of transport				
		and may be shipped unrestricted.				
14.7.	Transport in b	oulk according to Annex II of MARPOL 73/78 and the IBC Code				
	not applicable					

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content (1999/13/EC)

< 3,00 %

15.2. Chemical safety assessment

A chemical safety assessment has been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

R36/37/38 Irritating to eyes, respiratory system and skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Annex - Exposure Scenarios:

Exposure Scenarios for ethyl 2-cyanoacrylate can be downloaded under the following link: http://mymsds.henkel.com/mymsds/.470833..en.ANNEX_DE.15743123.0.DE.pdf Alternatively they can be accessed on the internet site www.mymsds.henkel.com by entering number 470833.