Srew Pitch Gauges





Accurately milled gauges for checking internal and external thread forms.

Accurately	inilied gauges for checking internal	and external timeau for	489394
Description	No of Size blades	Order Code	Price Each
Unified	30 4, 4½, 5, 5½, 6, 7, 8, 9, 10, 11, 11½, 12, 13, 14, 15, 16, 18, 20, 22, 24, 26, 27, 28, 30,	407 0040	
American National	32, 34, 36, 38, 40, 42 30 4, 46, 5, 5½, 6, 7, 8, 9, 10, 11, 11½, 2, 13, 14, 15, 16, 18, 20, 22, 24, 28, 27, 28, 30, 32, 34,	137-6812	
Whit	36, 38, 40, 42 28 4, 4½, 5, 6, 7, 8, 10, 11, 12, 13, 14, 16, 18, 19, 20, 22, 24, 25, 26, 28, 30, 32, 36, 40, 48,	137-6813	
SI Metric	60 blades and 55° screw cotting gauge 30 0.25, 0.3, 0.35, 0.4, 0.45, 0.5, 0.55, 0.6, 0.65, 0.7, 0.75, 0.8	137-6814	
Combination		137-6815	
set Metric/Whit ISO/Metric	3.5, 3.0, 25, 2.0, 1.75, 1.5, 1.25 1.0, 0.7, 0.8, 0.75, 0.7, 0.5, 0.4 blades plus Whit as No. 800 auge 6.0, 5.5, 5.0, 4.5, 4.0, 3.5, 3.0, 2.5, 2.0, 1.75, 1.5, 1.25, 1.0	137-6816	
	0.8, 0.75, 0.7, 0.6, 0.5, 0.45, 0.4 0.35 blades	, 137-6817	