

SAFETY DATA SHEET FLUXCLENE CLEANING SOLVENT (Combi)

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name FLUXCLENE CLEANING SOLVENT (Combi)

Product No. FLU-db, EFLU400DB, ZE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Manufacture of electrical equipment

Uses advised against At this moment in time we do not have information on use restrictions. They will be included

in this safety data sheet when available

1.3. Details of the supplier of the safety data sheet

Supplier ELECTROLUBE. A division of HK

WENTWORTH LTD

ASHBY PARK, COALFIELD WAY,

ASHBY DE LA ZOUCH, LEICESTERSHIRE

LE65 1JR

UNITED KINGDOM +44 (0)1530 419600 +44 (0)1530 416640 info@hkw.co.uk

1.4. Emergency telephone number

+44 (0)1530 419600 between 8.30am - 5.00pm GMT Mon - Fri

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and Chemical Flam. Aerosol 1 - H222

Hazards

Human health Skin Irrit. 2 - H315;Eye Irrit. 2 - H319;Skin Sens. 1 - H317;STOT SE

3 - H336

Environment Aquatic Acute 1 - H400; Aquatic Chronic 1 - H410

Classification (1999/45/EEC) Xi;R36/38. R43. F+;R12. N;R50/53. R67.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Environment

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Use appropriate containment to avoid environmental contamination. Avoid release to the environment. Refer to special instructions/safety data sheets. Dispose of waste and residues in accordance with local authority requirements.

Physical and Chemical Hazards

Aerosol containers can explode when heated, due to excessive pressure build-up. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited.

2.2. Label elements

Contains Orange Terpenes

Label In Accordance With (EC) No. 1272/2008







Signal Word	Danger	
Hazard Statements		
	H222	Extremely flammable aerosol.
	H315	Causes skin irritation.
	H317	May cause an allergic skin reaction.
	H319	Causes serious eye irritation.
	H336	May cause drowsiness or dizziness.
	H410	Very toxic to aquatic life with long lasting effects.
Precautionary Statements		
	P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
	P211	Do not spray on an open flame or other ignition source.
	P251	Pressurized container: Do not pierce or burn, even after use.
	P280	Wear protective gloves, eye and face protection.
Supplementary Precautionary State	ements	

P261 Avoid breathing vapour/spray.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P313 Get medical advice/attention.

P410+412 Protect from sunlight. Do not expose to temperatures exceeding 50 $^{\circ}$

C/122°F.

2.3. Other hazards

Not Classified as PBT/vPvB by current EU criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

CYCLOHEXANE			30-60%
CAS-No.: 110-82-7	EC No.: 203-806-2		
Classification (EC 1272/2008)		Classification (67/548/EEC)	
Flam. Liq. 2 - H225		F;R11	
Skin Irrit. 2 - H315		Xn;R65	
STOT SE 3 - H336		Xi;R38	
Asp. Tox. 1 - H304		R67	
Aquatic Acute 1 - H400		N;R50/53	
Aquatic Chronic 1 - H410			

PROPAN-2-OL			10-30%
CAS-No.: 67-63-0	EC No.: 200-661-7		
Classification (EC 1272/2008)		Classification (67/548/EEC)	
Flam. Liq. 2 - H225		F;R11	
Eye Irrit. 2 - H319		Xi;R36	
STOT SE 3 - H336		R67	

1-METHOXY-2-PROPANOL			10-30%
CAS-No.: 107-98-2	EC No.: 203-539-1		
Classification (EC 1272/2008)		Classification (67/548/EEC)	
Flam. Liq. 3 - H226		R10	
STOT SE 3 - H336		R67	

HEXANE MIXTURE OF ISOMERS (MAX 5% n-HEXANE (203-777-6))			5-10%
CAS-No.: -	EC No.: -		
Classification (EC 1272/2008)		Classification (67/548/EEC)	
Flam. Liq. 2 - H225		F;R11	
Skin Irrit. 2 - H315		Xn;R65	
STOT SE 3 - H336		Xi;R38	
Asp. Tox. 1 - H304		R67	
Aquatic Chronic 2 - H411		N;R51/53	

CAS-No.: 8028-48-6	EC No.: 232-433-8		
Classification (EC 1272/2008)		Classification (67/548/EEC)	
Flam. Liq. 3 - H226		Xn;R65.	
Skin Irrit. 2 - H315		Xi;R38.	
Skin Sens. 1 - H317		N;R50/53.	
Asp. Tox. 1 - H304		R10,R43.	
Aquatic Acute 1 - H400			
Aquatic Chronic 1 - H410			

1-5%

1-5%

CAS-No.: 142-82-5	EC No.: 205-563-8		
Classification (EC 1272/2008)		Classification (67/548/EEC)	
Flam. Liq. 2 - H225		F;R11	
Skin Irrit. 2 - H315		Xn;R65	
STOT SE 3 - H336		Xi;R38	
Asp. Tox. 1 - H304		R67	
Aquatic Acute 1 - H400		N;R50/53	
Aquatic Chronic 1 - H410			

HEXANE-norm			< 1%
CAS-No.: 110-54-3	EC No.: 203-777-6		
Classification (EC 1272/2008)		Classification (67/548/EEC)	
Flam. Liq. 2 - H225		F;R11	
Skin Irrit. 2 - H315		Repr. Cat. 3;R62	
Repr. 2 - H361f		Xn;R48/20,R65	
STOT SE 3 - H336		Xi;R38	
STOT RE 2 - H373		R67	
Asp. Tox. 1 - H304		N;R51/53	
Aquatic Chronic 2 - H411			

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Orange Terpenes

HEPTANE

Composition Comments

Ingredients not listed are classified as non-hazardous or at a concentration below reportable levels.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Inhalation

Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention. Get medical attention.

Ingestion

Not relevant

Skin contact

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

Eye contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

Treat Symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media

Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

Unusual Fire & Explosion Hazards

Extremely flammable. Aerosol cans may explode in a fire.

Specific hazards

Aerosol containers can explode when heated, due to excessive pressure build-up. Vapours may be ignited by a spark, a hot surface or an ember. The product is flammable, and heating may generate vapours which may form explosive vapour/air mixtures.

5.3. Advice for firefighters

Special Fire Fighting Procedures

Move container from fire area if it can be done without risk. Water spray should be used to cool containers.

Protective equipment for fire-fighters

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Do not discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb in vermiculite, dry sand or earth and place into containers.

6.4. Reference to other sections

Wear protective clothing as described in Section 8 of this safety data sheet. See section 11 for additional information on health hazards. The product contains a substance which is hazardous to aquatic organisms and which may cause long term adverse effects in the aquatic environment. See section 12 as well. For waste disposal, see section 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid spilling, skin and eye contact. Provide good ventilation.

7.2. Conditions for safe storage, including any incompatibilities

Store at moderate temperatures in dry, well ventilated area.

7.3. Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Name	STD	TWA	- 8 Hrs	STEL	- 15 Min	Notes
1-METHOXY-2-PROPANOL	WEL	100 ppm	375 mg/m3	150 ppm	560 mg/m3	Sk
CYCLOHEXANE	WEL	100 ppm	350 mg/m3	300 ppm	1050 mg/m3	
HEPTANE	WEL	500 ppm				
PROPAN-2-OL	WEL	400 ppm	999 mg/m3	500 ppm	1250 mg/m3	

WEL = Workplace Exposure Limit.

Sk = Can be absorbed through skin.

PROPAN-2-OL (CAS: 67-63-0)

DNEL			
Industry	Dermal	888	mg/kg/day
Industry	Inhalation.	500	mg/m3
Consumer	Dermal	319	mg/kg/day
Consumer	Inhalation.	89	mg/m3
Consumer	Oral	26	mg/kg/day
PNEC			
Freshwater	140.9	mg/l	
Marinewater	140.9	mg/l	
Sediment	552	mg/kg	
Soil	28	mg/kg	

8.2. Exposure controls

Protective equipment



Process conditions

Use engineering controls to reduce air contamination to permissible exposure level. Provide eyewash station.

Engineering measures

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Respiratory equipment

In case of inadequate ventilation and work of brief duration, use suitable respiratory equipment. No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit. Use respiratory equipment with combination filter, type A2/P3. EN14387

Hand protection

Protective gloves should be used if there is a risk of direct contact or splash. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material. Butyl rubber gloves are recommended. Gloves should conform to EN374

Eye protection

Wear approved, tight fitting safety glasses where splashing is probable. EN166

Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures

Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke. DO NOT SMOKE IN WORK AREA!

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance Aerosol. Liquid Colour Colourless.

OdourCharacteristic. Lemon.SolubilityInsoluble in waterInitial boiling point and boiling range>80 (176 F)

(°C)

 Melting point (°C)
 <-29 (-20.2 F)</td>

 Relative density
 0.780 @ 20 °C (68 F)

 Vapour pressure
 11.52 kPa @ 20 °C (68 F)

 Flash point (°C)
 0 (32 F) CC (Closed cup).

Auto Ignition Temperature (°C) > 200 (392 F)

Flammability Limit - Lower(%) 0.6
Flammability Limit - Upper(%) 8.3

9.2. Other information

None.

Volatile Volatile

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stable under normal temperature conditions.

10.3. Possibility of hazardous reactions

Not determined.

Hazardous Polymerisation

Will not polymerise.

10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid contact with acids and alkalis.

10.5. Incompatible materials

Materials To Avoid

Strong oxidising substances.

10.6. Hazardous decomposition products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Other Health Effects

This substance has no evidence of carcinogenic properties.

Inhalation

Vapours may cause headache, fatigue, dizziness and nausea. High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting.

Skin contact

May cause sensitisation by skin contact. Prolonged or repeated exposure may cause severe irritation. Product has a defatting effect on skin. Prolonged contact may cause dryness of the skin.

Eye contact

Irritating to eyes.

Route of entry

Skin and/or eye contact. Inhalation.

Toxicological information on ingredients.

HEPTANE (CAS: 142-82-5)

Toxic Dose 1 - LD 50 222 mg/kg (ivn-mouse) Toxic Conc. - LC 50 103 ppm/4h (inh-rat)

HEXANE-norm (CAS: 110-54-3)

Toxic Dose 1 - LD 50 28700 mg/kg (oral rat) Toxic Conc. - LC 50 48000 ppm/4h (inh-rat)

PROPAN-2-OL (CAS: 67-63-0)

Acute toxicity:

Acute Toxicity (Oral LD50)

5280 mg/kg Rat

Acute Toxicity (Dermal LD50)

12800 mg/kg Rabbit

Acute Toxicity (Inhalation LC50)

72.6 mg/l (vapours) Rat 4 hours

1-METHOXY-2-PROPANOL (CAS: 107-98-2)

Toxic Dose 1 - LD 50 5200 mg/kg (oral rat) Toxic Dose 2 - LD 50

11700 mg/kg (oral-mouse)

Orange Terpenes (CAS: 8028-48-6)

Acute toxicity:

Acute Toxicity (Oral LD50)

5300 mg/kg Rat

Acute Toxicity (Dermal LD50)

> 5000 mg/kg Rabbit

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Dangerous for the environment if discharged into watercourses.

12.1. Toxicity

Ecological information on ingredients.

HEPTANE (CAS: 142-82-5)

LC 50, 96 Hrs, Fish mg/l

4.924

PROPAN-2-OL (CAS: 67-63-0)

Acute Toxicity - Fish

LC50 96 hours 9640 mg/l Pimephales promelas (Fat-head Minnow)

Acute Toxicity - Aquatic Invertebrates

EC50 48 hours 13299 mg/l Daphnia magna

Acute Toxicity - Aquatic Plants

EC50 72 hours > 1.000 mg/l Scenedesmus subspicatus

Acute Toxicity - Microorganisms

EC50 > 1.000 mg/l Activated sludge

1-METHOXY-2-PROPANOL (CAS: 107-98-2)

LC 50, 96 Hrs, Fish mg/l

20800

EC 50, 48 Hrs, Daphnia, mg/l

23300

Orange Terpenes (CAS: 8028-48-6)

Acute Toxicity - Fish

LC50 96 hours 0.71 mg/l Pimephales promelas (Fat-head Minnow)

Acute Toxicity - Aquatic Invertebrates

EC50 0.4 mg/l Daphnia magna

Acute Toxicity - Aquatic Plants

IC50 4 mg/l Selenastrum capricornutum

12.2. Persistence and degradability

Degradability

There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential

No data available on bioaccumulation.

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

This product does not contain any PBT or vPvB substances.

12.6. Other adverse effects

SECTION 13: DISPOSAL CONSIDERATIONS

General information

Waste is classified as hazardous waste. Disposal to licensed waste disposal site in accordance with the local Waste Disposal Authority.

13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements. Empty containers must not be burned because of explosion hazard.

SECTION 14: TRANSPORT INFORMATION

General This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2,

ADR and IMDG. These provisions allow transport of aerosols of less than 1 litre packed in cartons of less than 30kg gross to be exempt from control providing that they are labelled in accordance with the requirements of these regulations to show that they are being

transported as Limited Quantities. Aerosols not so packed must show the following

14.1. UN number

UN No. (ADR/RID/ADN) 1950 **UN No. (IMDG)** 1950

UN No. (ICAO) 1950

14.2. UN proper shipping name

Proper Shipping Name AEROSOLS (CYCLOHEXANE)

14.3. Transport hazard class(es)

ADR/RID/ADN Class 2.1

ADR/RID/ADN Class Class 2: Gases

ADR Label No. 2.1

IMDG Class 2.1

ICAO Class/Division 2.1

Transport Labels



14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant



14.6. Special precautions for user

EMS F-D, S-U

Tunnel Restriction Code (D)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Statutory Instruments

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716). Control of Substances Hazardous to Health.

Guidance Notes

Workplace Exposure Limits EH40.

Authorisations (Title VII Regulation 1907/2006)

No specific authorisations are noted for this product.

Restrictions (Title VIII Regulation 1907/2006)

No specific restrictions of use are noted for this product.

15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out.

SECTION 16: OTHER INFORMATION

Issued ByHelen O'ReillyRevision DateAPRIL 2013

 Revision
 7

 SDS No.
 10372

Risk Phrases In Full

R12 Extremely flammable.

R10 Flammable.

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R65 Harmful: may cause lung damage if swallowed.

R11 Highly flammable

R36/38 Irritating to eyes and skin.

R36 Irritating to eyes.
R38 Irritating to skin.

R43 May cause sensitisation by skin contact.

R62 Possible risk of impaired fertility.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67 Vapours may cause drowsiness and dizziness.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

Hazard Statements In Full

H222 Extremely flammable aerosol.
 H225 Highly flammable liquid and vapour.
 H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.
H361f Suspected of damaging fertility.

H373 May cause damage to organs << Organs>> through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.H411 Toxic to aquatic life with long lasting effects.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.



SAFETY DATA SHEET FLUXCLENE Aerosol

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name FLUXCLENE Aerosol

Product No. FLU-a, EFLU200D, EFLU400D, ZE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Manufacture of electrical equipment

Uses advised against At this moment in time we do not have information on use restrictions. They will be included

in this safety data sheet when available

1.3. Details of the supplier of the safety data sheet

Supplier ELECTROLUBE. A division of HK

WENTWORTH LTD

ASHBY PARK, COALFIELD WAY,

ASHBY DE LA ZOUCH, LEICESTERSHIRE

LE65 1JR

UNITED KINGDOM +44 (0)1530 419600 +44 (0)1530 416640 info@hkw.co.uk

1.4. Emergency telephone number

+44 (0)1530 419600 between 8.30am - 5.00pm GMT Mon - Fri

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and Chemical Flam. Aerosol 1 - H222

Hazards

Human health Skin Irrit. 2 - H315;Eye Irrit. 2 - H319;Skin Sens. 1 - H317;STOT SE

3 - H336

Environment Aquatic Acute 1 - H400; Aquatic Chronic 1 - H410

Classification (1999/45/EEC) Xi;R36/38. R43. F+;R12. N;R50/53. R67.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Environment

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Use appropriate containment to avoid environmental contamination. Avoid release to the environment. Refer to special instructions/safety data sheets. Dispose of waste and residues in accordance with local authority requirements.

Physical and Chemical Hazards

Aerosol containers can explode when heated, due to excessive pressure build-up. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited.

2.2. Label elements

Contains Orange Terpenes

Label In Accordance With (EC) No. 1272/2008







Dispose of contents/container to ...

Signal Word	Danger	
Hazard Statements	_	
	H222	Extremely flammable aerosol.
	H315	Causes skin irritation.
	H317	May cause an allergic skin reaction.
	H319	Causes serious eye irritation.
	H336	May cause drowsiness or dizziness.
	H410	Very toxic to aquatic life with long lasting effects.
Precautionary Statements		
	P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
	P211	Do not spray on an open flame or other ignition source.
	P251	Pressurized container: Do not pierce or burn, even after use.
	P280	Wear protective gloves, eye and face protection.
	P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P313	Get medical advice/attention.
Supplementary Precautionary Stat	ements	
	P261	Avoid breathing vapour/spray.
	P410+412	Protect from sunlight. Do not expose to temperatures exceeding 50 ° C/122°F.

2.3. Other hazards

Not Classified as PBT/vPvB by current EU criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

P501

3.2. Mixtures

CYCLOHEXANE			30-60%
CAS-No.: 110-82-7	EC No.: 203-806-2		
Classification (EC 1272/2008)		Classification (67/548/EEC)	
Flam. Liq. 2 - H225		F;R11	
Skin Irrit. 2 - H315		Xn;R65	
STOT SE 3 - H336		Xi;R38	
Asp. Tox. 1 - H304		R67	
Aquatic Acute 1 - H400		N;R50/53	
Aquatic Chronic 1 - H410			

PROPAN-2-OL			10-30%
CAS-No.: 67-63-0	EC No.: 200-661-7		
Classification (EC 1272/2008)		Classification (67/548/EEC)	
Flam. Liq. 2 - H225		F;R11	
Eye Irrit. 2 - H319		Xi;R36	
STOT SE 3 - H336		R67	

1-METHOXY-2-PROPANOL			10-30%
CAS-No.: 107-98-2	EC No.: 203-539-1		
Classification (EC 1272/2008)		Classification (67/548/EEC)	
Flam. Liq. 3 - H226		R10	
STOT SE 3 - H336		R67	

HEXANE MIXTURE OF ISOMERS (MAX 5% n-HEXANE (203-777-6))			5-10%
CAS-No.: -	EC No.: -		
Classification (EC 1272/2008)		Classification (67/548/EEC)	
Flam. Liq. 2 - H225		F;R11	
Skin Irrit. 2 - H315		Xn;R65	
STOT SE 3 - H336		Xi;R38	
Asp. Tox. 1 - H304		R67	
Aquatic Chronic 2 - H411		N;R51/53	

CAS-No.: 8028-48-6	EC No.: 232-433-8		
Classification (EC 1272/2008)		Classification (67/548/EEC)	
Flam. Liq. 3 - H226		Xn;R65.	
Skin Irrit. 2 - H315		Xi;R38.	
Skin Sens. 1 - H317		N;R50/53.	
Asp. Tox. 1 - H304		R10,R43.	
Aquatic Acute 1 - H400			
Aquatic Chronic 1 - H410			

1-5%

1-5%

CAS-No.: 142-82-5	EC No.: 205-563-8		
Classification (EC 1272/2008)		Classification (67/548/EEC)	
Flam. Liq. 2 - H225		F;R11	
Skin Irrit. 2 - H315		Xn;R65	
STOT SE 3 - H336		Xi;R38	
Asp. Tox. 1 - H304		R67	
Aquatic Acute 1 - H400		N;R50/53	
Aquatic Chronic 1 - H410			

HEXANE-norm			< 1%
CAS-No.: 110-54-3	EC No.: 203-777-6		
Classification (EC 1272/2008)		Classification (67/548/EEC)	
Flam. Liq. 2 - H225		F;R11	
Skin Irrit. 2 - H315		Repr. Cat. 3;R62	
Repr. 2 - H361f		Xn;R48/20,R65	
STOT SE 3 - H336		Xi;R38	
STOT RE 2 - H373		R67	
Asp. Tox. 1 - H304		N;R51/53	
Aquatic Chronic 2 - H411			

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Orange Terpenes

HEPTANE

Composition Comments

Ingredients not listed are classified as non-hazardous or at a concentration below reportable levels.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Inhalation

Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention. Get medical attention.

Ingestion

Not relevant

Skin contact

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

Eye contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

Treat Symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media

Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

Unusual Fire & Explosion Hazards

Extremely flammable. Aerosol cans may explode in a fire.

Specific hazards

Aerosol containers can explode when heated, due to excessive pressure build-up. Vapours may be ignited by a spark, a hot surface or an ember. The product is flammable, and heating may generate vapours which may form explosive vapour/air mixtures.

5.3. Advice for firefighters

Special Fire Fighting Procedures

Move container from fire area if it can be done without risk. Water spray should be used to cool containers.

Protective equipment for fire-fighters

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Do not discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb in vermiculite, dry sand or earth and place into containers.

6.4. Reference to other sections

Wear protective clothing as described in Section 8 of this safety data sheet. See section 11 for additional information on health hazards. The product contains a substance which is hazardous to aquatic organisms and which may cause long term adverse effects in the aquatic environment. See section 12 as well. For waste disposal, see section 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid spilling, skin and eye contact. Provide good ventilation.

7.2. Conditions for safe storage, including any incompatibilities

Store at moderate temperatures in dry, well ventilated area.

7.3. Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Name	STD	TWA	- 8 Hrs	STEL	- 15 Min	Notes
1-METHOXY-2-PROPANOL	WEL	100 ppm	375 mg/m3	150 ppm	560 mg/m3	Sk
CYCLOHEXANE	WEL	100 ppm	350 mg/m3	300 ppm	1050 mg/m3	
HEPTANE	WEL	500 ppm				
PROPAN-2-OL	WEL	400 ppm	999 mg/m3	500 ppm	1250 mg/m3	

WEL = Workplace Exposure Limit.

PROPAN-2-OL (CAS: 67-63-0)

DNEL			
Industry	Dermal	888	mg/kg/day
Industry	Inhalation.	500	mg/m3
Consumer	Dermal	319	mg/kg/day
Consumer	Inhalation.	89	mg/m3
Consumer	Oral	26	mg/kg/day
PNEC			
Freshwater	140.9	mg/l	
Marinewater	140.9	mg/l	
Sediment	552	mg/kg	
Soil	28	mg/kg	

8.2. Exposure controls

Protective equipment



Process conditions

Use engineering controls to reduce air contamination to permissible exposure level. Provide eyewash station.

Engineering measures

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Respiratory equipment

In case of inadequate ventilation and work of brief duration, use suitable respiratory equipment. Use respiratory equipment with combination filter, type A2/P3. EN14387

Hand protection

Protective gloves must be used if there is a risk of direct contact or splash. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material. Nitrile gloves are recommended. Gloves should conform to EN374

Eye protection

Wear approved, tight fitting safety glasses where splashing is probable. EN166

Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures

Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke. DO NOT SMOKE IN WORK AREA!

Sk = Can be absorbed through skin.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance Aerosol. Liquid
Colour Colourless.
Odour Lemon.

Solubility Insoluble in water Initial boiling point and boiling range >80 (176 F)

(°C)

Melting point (°C) <-29 (-20.2 F)

 Relative density
 0.780 @ 20 °C (68 F)

 Vapour pressure
 11.52 kPa @ 20 °C (68 F)

 Flash point (°C)
 0 (32 F) CC (Closed cup).

Auto Ignition Temperature (°C) > 200 (392 F)

Flammability Limit - Lower(%) 0.6 Flammability Limit - Upper(%) 8.3

9.2. Other information

None.

Volatile Volatile

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stable under normal temperature conditions.

10.3. Possibility of hazardous reactions

Not determined.

Hazardous Polymerisation

Will not polymerise.

10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid contact with acids and alkalis.

10.5. Incompatible materials

Materials To Avoid

Strong oxidising substances.

10.6. Hazardous decomposition products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Other Health Effects

This substance has no evidence of carcinogenic properties.

Inhalation

Vapours may cause headache, fatigue, dizziness and nausea. High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting.

Skin contact

May cause sensitisation by skin contact. Prolonged or repeated exposure may cause severe irritation. Product has a defatting effect on skin. Prolonged contact may cause dryness of the skin.

Eye contact

Irritating to eyes.

Route of entry

Skin and/or eye contact. Inhalation.

Toxicological information on ingredients.

HEPTANE (CAS: 142-82-5)

Toxic Dose 1 - LD 50

222 mg/kg (ivn-mouse)

Toxic Conc. - LC 50

103 ppm/4h (inh-rat)

CYCLOHEXANE (CAS: 110-82-7)

Toxic Dose 1 - LD 50

12705 mg/kg (oral rat)

Toxic Dose 2 - LD 50

813 mg/kg (oral-mouse)

HEXANE-norm (CAS: 110-54-3)

Toxic Dose 1 - LD 50

28700 mg/kg (oral rat)

Toxic Conc. - LC 50

48000 ppm/4h (inh-rat)

PROPAN-2-OL (CAS: 67-63-0)

Acute toxicity:

Acute Toxicity (Oral LD50)

5280 mg/kg Rat

Acute Toxicity (Dermal LD50)

12800 mg/kg Rabbit

Acute Toxicity (Inhalation LC50)

72.6 mg/l (vapours) Rat 4 hours

1-METHOXY-2-PROPANOL (CAS: 107-98-2)

Toxic Dose 1 - LD 50

5200 mg/kg (oral rat)

Toxic Dose 2 - LD 50

11700 mg/kg (oral-mouse)

Orange Terpenes (CAS: 8028-48-6)

Acute toxicity:

Acute Toxicity (Oral LD50)

5300 mg/kg Rat

Acute Toxicity (Dermal LD50)

> 5000 mg/kg Rabbit

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Dangerous for the environment if discharged into watercourses.

12.1. Toxicity

Ecological information on ingredients.

HEPTANE (CAS: 142-82-5)

LC 50, 96 Hrs, Fish mg/l

4.924

CYCLOHEXANE (CAS: 110-82-7)

LC 50, 96 Hrs, Fish mg/l

42.3

PROPAN-2-OL (CAS: 67-63-0)

Acute Toxicity - Fish

LC50 96 hours 9640 mg/l Pimephales promelas (Fat-head Minnow)

Acute Toxicity - Aquatic Invertebrates

EC50 48 hours 13299 mg/l Daphnia magna

Acute Toxicity - Aquatic Plants

EC50 72 hours > 1.000 mg/l Scenedesmus subspicatus

Acute Toxicity - Microorganisms

EC50 > 1.000 mg/l Activated sludge

1-METHOXY-2-PROPANOL (CAS: 107-98-2)

LC 50, 96 Hrs, Fish mg/l

20800

EC 50, 48 Hrs, Daphnia, mg/l

23300

Orange Terpenes (CAS: 8028-48-6)

Acute Toxicity - Fish

LC50 96 hours 0.71 mg/l Pimephales promelas (Fat-head Minnow)

Acute Toxicity - Aquatic Invertebrates

EC50 0.4 mg/l Daphnia magna

Acute Toxicity - Aquatic Plants

IC50 4 mg/l Selenastrum capricornutum

12.2. Persistence and degradability

Degradability

There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential

No data available on bioaccumulation.

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

This product does not contain any PBT or vPvB substances.

12.6. Other adverse effects

SECTION 13: DISPOSAL CONSIDERATIONS

General information

Waste is classified as hazardous waste. Disposal to licensed waste disposal site in accordance with the local Waste Disposal Authority.

13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements. Empty containers must not be burned because of explosion hazard.

SECTION 14: TRANSPORT INFORMATION

General

This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR and IMDG. These provisions allow transport of aerosols of less than 1litre packed in cartons of less than 30kg gross to be exempt from control providing that they are labelled in accordance with the requirements of these regulations to show that they are being transported as Limited Quantities. Aerosols not so packed must show the following

14.1. UN number

UN No. (ADR/RID/ADN) 1950 UN No. (IMDG) 1950 UN No. (ICAO) 1950

14.2. UN proper shipping name

Proper Shipping Name AEROSOLS (CYCLOHEXANE)

14.3. Transport hazard class(es)

ADR/RID/ADN Class 2.1

ADR/RID/ADN Class Class 2: Gases

ADR Label No. 2.1

IMDG Class 2.1

ICAO Class/Division 2.1

Transport Labels



14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant



14.6. Special precautions for user

EMS F-D, S-U

Tunnel Restriction Code (D)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Statutory Instruments

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716). Control of Substances Hazardous to Health.

Guidance Notes

Workplace Exposure Limits EH40.

EU Legislation

Commission Directive 2000/39/EC of 8 June 2000 establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

Authorisations (Title VII Regulation 1907/2006)

No specific authorisations are noted for this product.

Restrictions (Title VIII Regulation 1907/2006)

No specific restrictions of use are noted for this product.

15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out.

SECTION 16: OTHER INFORMATION

Issued ByHelen O'ReillyRevision DateAPRIL 2013Revision6

SDS No. 10371

Risk Phrases In Full

R12 Extremely flammable.

R10 Flammable.

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R65 Harmful: may cause lung damage if swallowed.

R11 Highly flammable

R36/38 Irritating to eyes and skin.

R36 Irritating to eyes.
R38 Irritating to skin.

R43 May cause sensitisation by skin contact.

R62 Possible risk of impaired fertility.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67 Vapours may cause drowsiness and dizziness.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

Hazard Statements In Full

H222 Extremely flammable aerosol.
 H225 Highly flammable liquid and vapour.
 H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H361f Suspected of damaging fertility.

H373 May cause damage to organs << Organs>> through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.H411 Toxic to aquatic life with long lasting effects.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.



SAFETY DATA SHEET FLUXCLENE

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name FLUXCLENE

Product No. FLU-b, EFLU01L, EFLU05L, EFLU25L, ZE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Cleaning Product

Uses advised against At this moment in time we do not have information on use restrictions. They will be included

in this safety data sheet when available

1.3. Details of the supplier of the safety data sheet

Supplier ELECTROLUBE. A division of HK

WENTWORTH LTD

ASHBY PARK, COALFIELD WAY,

ASHBY DE LA ZOUCH, LEICESTERSHIRE

LE65 1JR

UNITED KINGDOM +44 (0)1530 419600 +44 (0)1530 416640 info@hkw.co.uk

1.4. Emergency telephone number

+44 (0)1530 419600 between 8.30am - 5.00pm GMT Mon - Fri

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and Chemical Flam. Liq. 2 - H225

Hazards

Human health Skin Irrit. 2 - H315;Eye Irrit. 2 - H319;Skin Sens. 1 - H317;STOT SE

3 - H336; Asp. Tox. 1 - H304

Environment Aquatic Acute 1 - H400; Aquatic Chronic 1 - H410

Classification (1999/45/EEC) Xn;R65. Xi;R36/38. R43. F;R11. N;R50/53. R67.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Environment

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Use appropriate containment to avoid environmental contamination. Avoid release to the environment. Refer to special instructions/safety data sheets. Dispose of waste and residues in accordance with local authority requirements.

2.2. Label elements

Contains CYCLOHEXANE

Orange Terpenes

Label In Accordance With (EC) No. 1272/2008









Signal Word	Danger	
Hazard Statements		
	H225	Highly flammable liquid and vapour.
	H304	May be fatal if swallowed and enters airways.
	H315	Causes skin irritation.
	H317	May cause an allergic skin reaction.
	H319	Causes serious eye irritation.
	H336	May cause drowsiness or dizziness.
	H410	Very toxic to aquatic life with long lasting effects.
Precautionary Statements		
	P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
	P280	Wear protective gloves/protective clothing/eye protection/face protection.
	P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P313	Get medical advice/attention.
Supplementary Precautionary State	ements	
	P261	Avoid breathing vapour/spray.
	P301+310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
	P331	Do NOT induce vomiting.

2.3. Other hazards

Not Classified as PBT/vPvB by current EU criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

CYCLOHEXANE			30-60%
CAS-No.: 110-82-7	EC No.: 203-806-2		
Classification (EC 1272/2008)		Classification (67/548/EEC)	
Flam. Liq. 2 - H225		F;R11	
Skin Irrit. 2 - H315		Xn;R65	
STOT SE 3 - H336		Xi;R38	
Asp. Tox. 1 - H304		R67	
Aquatic Acute 1 - H400		N;R50/53	
Aquatic Chronic 1 - H410			

PROPAN-2-OL			10-30%
CAS-No.: 67-63-0	EC No.: 200-661-7		
Classification (EC 1272/2008)		Classification (67/548/EEC)	
Flam. Liq. 2 - H225		F;R11	
Eye Irrit. 2 - H319		Xi;R36	
STOT SE 3 - H336		R67	

1-METHOXY-2-PROPANOL			10-30%
CAS-No.: 107-98-2	EC No.: 203-539-1		
Classification (EC 1272/2008)		Classification (67/548/EEC)	
Flam. Liq. 3 - H226		R10	
STOT SE 3 - H336		R67	
HEXANE MIXTURE OF ISOMERS	S (MAX 5% n_HEXANE (2	203-777-6))	5-10%

			0.07
CAS-No.: -	EC No.: -		
Classification (EC 1272/2008)		Classification (67/548/EEC)	
Flam. Liq. 2 - H225		F;R11	
Skin Irrit. 2 - H315		Xn;R65	
STOT SE 3 - H336		Xi;R38	
Asp. Tox. 1 - H304		R67	
Aquatic Chronic 2 - H411		N;R51/53	

CAS-No.: 8028-48-6	EC No.: 232-433-8		
Classification (EC 1272/2008)		Classification (67/548/EEC)	
Flam. Liq. 3 - H226		Xn;R65.	
Skin Irrit. 2 - H315		Xi;R38.	
Skin Sens. 1 - H317		N;R50/53.	
Asp. Tox. 1 - H304		R10,R43.	
Aquatic Acute 1 - H400			
Aquatic Chronic 1 - H410			

1-5%

1-5%

CAS-No.: 142-82-5	EC No.: 205-563-8		
Classification (EC 1272/2008)		Classification (67/548/EEC)	
Flam. Liq. 2 - H225		F;R11	
Skin Irrit. 2 - H315		Xn;R65	
STOT SE 3 - H336		Xi;R38	
Asp. Tox. 1 - H304		R67	
Aquatic Acute 1 - H400		N;R50/53	
Aquatic Chronic 1 - H410			

HEXANE-norm			< 1%
CAS-No.: 110-54-3	EC No.: 203-777-6		
Classification (EC 1272/2008)		Classification (67/548/EEC)	
Flam. Liq. 2 - H225		F;R11	
Skin Irrit. 2 - H315		Repr. Cat. 3;R62	
Repr. 2 - H361f		Xn;R48/20,R65	
STOT SE 3 - H336		Xi;R38	
STOT RE 2 - H373		R67	
Asp. Tox. 1 - H304		N;R51/53	
Aquatic Chronic 2 - H411			

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Orange Terpenes

HEPTANE

Composition Comments

Ingredients not listed are classified as non-hazardous or at a concentration below reportable levels.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Inhalation

Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention. **Ingestion**

DO NOT INDUCE VOMITING! Rinse mouth thoroughly. Provide rest, warmth and fresh air. Get medical attention immediately!

Skin contact

Remove affected person from source of contamination. Wash the skin immediately with soap and water. Get medical attention if irritation persists after washing.

Eye contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Contact physician if irritation persists.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

Treat Symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media

Fire can be extinguished using: Foam. Dry chemicals, sand, dolomite etc.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

Unusual Fire & Explosion Hazards

No unusual fire or explosion hazards noted.

Specific hazards

The product is flammable, and heating may generate vapours which may form explosive vapour/air mixtures.

5.3. Advice for firefighters

Special Fire Fighting Procedures

Avoid breathing fire vapours. Cool containers exposed to flames with water until well after the fire is out. Keep run-off water out of sewers and water sources. Dike for water control.

Protective equipment for fire-fighters

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Do not discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Clean-up personnel should use respiratory and/or liquid contact protection. Absorb in vermiculite, dry sand or earth and place into containers.

6.4. Reference to other sections

Wear protective clothing as described in Section 8 of this safety data sheet. See section 11 for additional information on health hazards. Collect and dispose of spillage as indicated in section 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid spilling, skin and eye contact. Keep away from heat, sparks and open flame. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Use explosion proof electric equipment.

7.2. Conditions for safe storage, including any incompatibilities

Flammable/combustible - Keep away from oxidisers, heat and flames. Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

7.3. Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Name	STD	TWA	- 8 Hrs	STEL	- 15 Min	Notes
1-METHOXY-2-PROPANOL	WEL	100 ppm	375 mg/m3	150 ppm	560 mg/m3	Sk
CYCLOHEXANE	WEL	100 ppm	350 mg/m3	300 ppm	1050 mg/m3	
HEPTANE	WEL	500 ppm				
PROPAN-2-OL	WEL	400 ppm	999 mg/m3	500 ppm	1250 mg/m3	

WEL = Workplace Exposure Limit.

Sk = Can be absorbed through skin.

Ingredient Comments

WEL = Workplace Exposure Limits

PROPAN-2-OL (CAS: 67-63-0)

DNEL			•
Industry	Dermal	888	mg/kg/day
Industry	Inhalation.	500	mg/m3
Consumer	Dermal	319	mg/kg/day
Consumer	Inhalation.	89	mg/m3
Consumer	Oral	26	mg/kg/day
PNEC			
Freshwater	140.9	mg/l	
Marinewater	140.9	mg/l	
Sediment	552	mg/kg	
Soil	28	mg/kg	

8.2. Exposure controls

Protective equipment





Engineering measures

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. Observe occupational exposure limits and minimize the risk of inhalation of vapours.

Respiratory equipment

In case of inadequate ventilation and work of brief duration, use suitable respiratory equipment. Use respiratory equipment with combination filter, type A2/P3. EN14387

Hand protection

Use suitable protective gloves if risk of skin contact. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material. Gloves of nitrile rubber, PVA or Viton are recommended. Gloves should conform to EN374

Eye protection

Wear approved chemical safety goggles where eye exposure is reasonably probable. EN166

Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap & water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance Liquid Clear

Colour Colourless.

Odour Organic solvents.

Solubility Insoluble in water Soluble in: Acetone Miscible with: Alcohol Chloroform Ether.

Initial boiling point and boiling range

>80 (>176 F)

(°C)

Relative density 0.78 @ 20 °C (68 F)Flash point (°C) 0 (32 F) CC (Closed cup).

Auto Ignition Temperature (°C) >200 (>392 F)

Flammability Limit - Lower(%) 0.7
Flammability Limit - Upper(%) 8.3

9.2. Other information

None.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stable under normal temperature conditions.

10.3. Possibility of hazardous reactions

Not available.

Hazardous Polymerisation

Will not polymerise.

10.4. Conditions to avoid

Avoid heat. Avoid contact with oxidisers or reducing agents.

10.5. Incompatible materials

Materials To Avoid

Strong acids. Strong alkalis. Strong oxidising substances.

10.6. Hazardous decomposition products

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Inhalation

Vapours may cause headache, fatigue, dizziness and nausea. High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting.

Ingestior

Harmful: may cause lung damage if swallowed.

Skin contact

Irritating to skin. May cause sensitisation by skin contact. Product has a defatting effect on skin. Prolonged contact may cause dryness of the skin.

Eye contact

Irritating to eyes.

Route of entry

Inhalation. Skin absorption.

Toxicological information on ingredients.

HEPTANE (CAS: 142-82-5)

Toxic Dose 1 - LD 50

222 mg/kg (ivn-mouse)

Toxic Conc. - LC 50

103 ppm/4h (inh-rat)

CYCLOHEXANE (CAS: 110-82-7)

Toxic Dose 1 - LD 50

12705 mg/kg (oral rat)

Toxic Dose 2 - LD 50

813 mg/kg (oral-mouse)

PROPAN-2-OL (CAS: 67-63-0)

Acute toxicity:

Acute Toxicity (Oral LD50)

5280 mg/kg Rat

Acute Toxicity (Dermal LD50)

12800 mg/kg Rabbit

Acute Toxicity (Inhalation LC50)

72.6 mg/l (vapours) Rat 4 hours

1-METHOXY-2-PROPANOL (CAS: 107-98-2)

Toxic Dose 1 - LD 50

5200 mg/kg (oral rat)

Toxic Dose 2 - LD 50

11700 mg/kg (oral-mouse)

Orange Terpenes (CAS: 8028-48-6)

Acute toxicity:

Acute Toxicity (Oral LD50)

5300 mg/kg Rat

Acute Toxicity (Dermal LD50)

> 5000 mg/kg Rabbit

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Dangerous for the environment if discharged into watercourses.

12.1. Toxicity

Ecological information on ingredients.

HEPTANE (CAS: 142-82-5)

LC 50, 96 Hrs, Fish mg/l

4.924

CYCLOHEXANE (CAS: 110-82-7)

LC 50, 96 Hrs, Fish mg/l

42.3

PROPAN-2-OL (CAS: 67-63-0)

Acute Toxicity - Fish

LC50 96 hours 9640 mg/l Pimephales promelas (Fat-head Minnow)

Acute Toxicity - Aquatic Invertebrates

EC50 48 hours 13299 mg/l Daphnia magna

Acute Toxicity - Aquatic Plants

EC50 72 hours > 1.000 mg/l Scenedesmus subspicatus

Acute Toxicity - Microorganisms

EC50 > 1.000 mg/l Activated sludge

1-METHOXY-2-PROPANOL (CAS: 107-98-2)

LC 50, 96 Hrs, Fish mg/l

20800

EC 50, 48 Hrs, Daphnia, mg/l

23300

Orange Terpenes (CAS: 8028-48-6)

Acute Toxicity - Fish

LC50 96 hours 0.71 mg/l Pimephales promelas (Fat-head Minnow)

Acute Toxicity - Aquatic Invertebrates

EC50 0.4 mg/l Daphnia magna

Acute Toxicity - Aquatic Plants

IC50 4 mg/l Selenastrum capricornutum

12.2. Persistence and degradability

Degradability

There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential

No data available on bioaccumulation.

12.4. Mobility in soil

Mobility:

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces.

12.5. Results of PBT and vPvB assessment

This product does not contain any PBT or vPvB substances.

12.6. Other adverse effects

Not available.

SECTION 13: DISPOSAL CONSIDERATIONS

General information

Waste is classified as hazardous waste. Disposal to licensed waste disposal site in accordance with the local Waste Disposal Authority.

13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements.

SECTION 14: TRANSPORT INFORMATION

14.1. UN number

UN No. (ADR/RID/ADN) 1993 **UN No. (IMDG)** 1993

UN No. (ICAO) 1993

14.2. UN proper shipping name

Proper Shipping Name FLAMMABLE LIQUID, N.O.S. (CYCLOHEXANE, Orange Terpenes)

14.3. Transport hazard class(es)

ADR/RID/ADN Class 3

ADR/RID/ADN Class Class 3: Flammable liquids.

ADR Label No. 3
IMDG Class 3
ICAO Class/Division 3

Transport Labels



14.4. Packing group

ADR/RID/ADN Packing group || IMDG Packing group || ICAO Packing group || II

14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant



14.6. Special precautions for user

EMS F-E, S-E
Emergency Action Code •3YE
Hazard No. (ADR) 33
Tunnel Restriction Code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Statutory Instruments

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716). Control of Substances Hazardous to Health.

Guidance Notes

Workplace Exposure Limits EH40.

EU Legislation

Commission Directive 2000/39/EC of 8 June 2000 establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

Authorisations (Title VII Regulation 1907/2006)

No specific authorisations are noted for this product.

Restrictions (Title VIII Regulation 1907/2006)

No specific restrictions of use are noted for this product.

15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out.

SECTION 16: OTHER INFORMATION

Issued ByHelen O'ReillyRevision DateAPRIL 2013

Revision 6 **SDS No.** 10368

Risk Phrases In Full

R10 Flammable.

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R65 Harmful: may cause lung damage if swallowed.

R11 Highly flammable

R36/38 Irritating to eyes and skin.

R36 Irritating to eyes. R38 Irritating to skin.

R43 May cause sensitisation by skin contact.

R62 Possible risk of impaired fertility.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67 Vapours may cause drowsiness and dizziness.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

Hazard Statements In Full

H225 Highly flammable liquid and vapour.H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

H361f Suspected of damaging fertility.

H373 May cause damage to organs << Organs>> through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.H411 Toxic to aquatic life with long lasting effects.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.