

## Quick Mating panel and cable connectors

### Description

The versatile and easy to use “SMS” Quick Mating panel and cable connectors are a highly cost-effective system approach to solving the constant demand for more interconnection solutions and techniques.


A full plastic solution offered in either Wire attachment or PCB mounting options to provide rapid assembly/installation without requiring additional mounting hardware. Panel receptacle connectors simply snap and lock into panel cut-outs and cable plugs quickly connect and disconnect with positive retention locks. Just push to mate then press and release to un-mate.

In addition, cable plug connectors also feature pin-protection skirts, positive polarization and are offered with or without integrated strain relief hoods. Cable receptacle connectors (with integrated strain relief hoods) are available to mate with the cable plug connectors for cable-to-cable solutions when needed.

These multi-way connectors accept the Size 16 TRIM TRIO .0625” (1.6mm) diameter contacts and are available with 10 contact arrangements from 2 to 36 positions.

### Features and benefits

- Available in 10 contact arrangements.
- Self mountable panel receptacle with positive housing retention.
- Cable plugs with retaining latches for positive locking.
- Cable plug has pin protection skirt to prevent damage of male contacts
- Positive polarization keys prevent mismatching.
- Cable plug and receptacle have integrated strain relief hood which can accept a wide range of cables.
- Cable plug and receptacle have discrimination cavities in between contact cavities, thus offering discrimination without contact loss.



- UL recognized File Nr.: E238675
- CSA certified File Nr.: LR44961-21

### Environmental

- Operating temperature: -55°C to +105°C
- Insulation resistance: 5000 MΩ min.
- Test potential: 2000 VAC
- Durability: 500 matings and unmatings
- Sealing performances: IP40
- Electrical performances:  
UL: 250V - 10A  
CSA: 250V - 15A

### Wire insulation acceptance

- SMS PDH1, RDH1, PD3, PDH3, RD3, RDH3 max: 3.2mm
- SMS R1, P1, R3 max: 4.19mm

### Material

- Connector: Polyamide 6.6
- Flammability rating: UL94 V2 (Black) or UL94 V0 (White).

The white version is also I3F2/I2F3 according to the NFF 16101 /16102 (Fire & fume standard for French rail market)

- Fire resistance, toxicity & smoke opacity: R23/HL3 following CEN/TS 45-545

### Contact


- “SMS” Quick Mating connectors accept TRIM TRIO size 16 removable snap-lock contacts (see contact section)
- Contacts to be ordered separately.

## Ordering information


|   |     |    |      |
|---|-----|----|------|
| <b>Connector family</b>   | SMS | 12 | PDH3 |
| <b>Layout:</b> see next page  |     |    |      |
| <b>Body variation:</b>  |     |    |      |
| R1: (UL94 V2) Panel mount receptacle - Black                                  |     |    |      |
| R3: (UL94 V0) Panel mount receptacle - White                                  |     |    |      |
| P1: (UL94 V2) Cable plug without strain relief hood - Black                   |     |    |      |
| PD3: (UL94 V0) Cable plug without strain relief hood - White                  |     |    |      |
| PDH1: (UL94 V2) Cable plug with integrated strain relief hood - Black         |     |    |      |
| PDH3: (UL94 V0) Cable plug with integrated strain relief hood - White         |     |    |      |
| RD3: (UL94 V0) Cable receptacle without integrated strain relief hood - White |     |    |      |
| RDH1: (UL94 V2) Cable receptacle with integrated strain relief hood - Black   |     |    |      |
| RDH3: (UL94 V0) Cable receptacle with integrated strain relief hood - White   |     |    |      |

## Contacts layout


SMS 2




SMS 3




SMS 4




SMS 6




SMS 9




SMS 12




SMS 15




SMS 18



SMS 24



SMS 36



Contact identifications shown are for mating face. Contact identifications of wiring face are identical as shown on the receptacle arrangements


Range overview

**SMS...PDH1/SMS...PDH3**  
Cable plug with strain relief hood



**SMS...P1/SMS...PD3**  
Cable plug without strain relief hood

**SMS...RDH1/SMS...RDH3**  
Cable receptacle with strain relief hood



**SMS...GE3-GE4/SMS...SE3-SE4**  
Straight board mount



**SMS...GE5-SE5/SMS...GE6-SE6**  
Right angle board mount



**SMS...R1**  
Panel mount receptacle





**SMS...RD3**  
Cable receptacle without strain relief hood



## Connectors


### Panel mount receptacle without discrimination cavities (wire acceptance: 4.19mm)



| Part number   |               | Nbr. of contact* | A      | B      | C max. | J      | K      |
|---------------|---------------|------------------|--------|--------|--------|--------|--------|
| Black UL94 V2 | White UL94 V0 |                  |        |        |        |        |        |
| SMS2R1        | SMS2R3        | 2                | 0.433" | 0.228" | 0.598" | 0.448" | 0.456" |
| SMS3R1        | SMS3R3        | 3                | 0.637" |        |        |        |        |
| SMS4R1        | SMS4R3        | 4                | 0.834" |        |        |        |        |
| SMS6R1        | SMS6R3        | 6                | 0.637" | 0.429" | 0.799" | 0.649" | 0.657" |
| SMS9R1        | SMS9R3        | 9                |        | 0.629" |        | 0.999" | 0.850" |
| SMS12R1       | SMS12R3       | 12               |        | 0.830" | 1.200" | 1.200" | 1.051" |
| SMS15R1       | SMS15R3       | 15               | 1.031" | 1.401" | 1.251" |        |        |
| SMS18R1       | SMS18R3       | 18               | 0.834" | 1.228" | 1.598" | 0.854" | 1.452" |
| SMS24R1       | SMS24R3       | 24               |        |        |        |        |        |
| SMS36R1       | SMS36R3       | 36               | 1.834" | 0.830" | 1.200" | 1.854" | 1.051" |

\*Contacts supplied separately

### Cable plug without strain relief hood & without discrimination cavities (wire acceptance: 4.19mm)






| Part number   | Nbr. of contact* | A      | C max. |
|---------------|------------------|--------|--------|
| Black UL94 V2 |                  |        |        |
| SMS2P1        | 2                | 0.590" | 0.700" |
| SMS3P1        | 3                | 0.732" |        |
| SMS4P1        | 4                | 0.933" |        |
| SMS6P1        | 6                | 0.732" | 0.901" |
| SMS9P1        | 9                |        | 1.098" |
| SMS12P1       | 12               |        | 1.299" |
| SMS15P1       | 15               | 0.933" | 1.499" |
| SMS18P1       | 18               |        | 1.700" |
| SMS24P1       | 24               | 1.933" | 1.299" |
| SMS36P1       | 36               |        |        |

\*Contacts supplied separately

Note: all dimensions are in inches




**Cable receptacle without strain relief hood & with discrimination cavities**



| Part number   | Nbr. of contact* | Nbr. of discrimination cavities | B max  | C      | D      | E      |        |        |
|---------------|------------------|---------------------------------|--------|--------|--------|--------|--------|--------|
| White UL94 V0 |                  |                                 |        |        |        |        |        |        |
| SMS2RD3       | 2                | 0                               | 0.389" | 0.330" | 0.436" | 0.555" |        |        |
| SMS3RD3       | 3                | 0                               |        |        | 0.637" | 0.732" |        |        |
| SMS4RD3       | 4                | 0                               |        |        | 0.834" | 0.933" |        |        |
| SMS6RD3       | 6                | 2                               | 0.590" | 0.527" | 0.637" | 0.732" |        |        |
| SMS9RD3       | 9                | 4                               | 0.787" | 0.728" |        |        |        |        |
| SMS12RD3      | 12               | 6                               | 0.988" | 0.929" |        |        |        |        |
| SMS15RD3      | 15               | 8                               | 1.188" | 1.129" |        |        |        |        |
| SMS18RD3      | 18               | 10                              | 1.389" | 1.330" |        |        | 0.834" | 0.933" |
| SMS24RD3      | 24               | 15                              |        |        |        |        |        |        |
| SMS36RD3      | 36               | 24                              | 0.988" | 0.929" | 1.834" | 1.933" |        |        |

\*Contacts supplied separately

**Cable plug without strain relief hood & with discrimination cavities**





| Part number   | Nbr. of contact* | Nbr. of discrimination cavities | B max. | C      | D      |        |
|---------------|------------------|---------------------------------|--------|--------|--------|--------|
| White UL94 V0 |                  |                                 |        |        |        |        |
| SMS2PD3       | 2                | 0                               | 0.645" | 0.330" | 0.555" |        |
| SMS3PD3       | 3                | 0                               |        |        | 0.732" |        |
| SMS4PD3       | 4                | 0                               |        |        | 0.933" |        |
| SMS6PD3       | 6                | 2                               | 0.846" | 0.527" | 0.732" |        |
| SMS9PD3       | 9                | 4                               | 1.051" | 0.728" |        |        |
| SMS12PD3      | 12               | 6                               | 1.248" | 0.929" |        |        |
| SMS15PD3      | 15               | 8                               | 1.444" | 1.129" |        |        |
| SMS18PD3      | 18               | 10                              | 1.645" | 1.330" |        | 0.933" |
| SMS24PD3      | 24               | 15                              |        |        |        |        |
| SMS36PD3      | 36               | 24                              | 1.248" | 0.929" | 1.933" |        |

\*Contacts supplied separately

Note: all dimensions are in inches

Connectors (Continued)



Cable receptacle with integrated strain relief hood



| Part number   |               | Nbr. of contact* | Nbr. of discrimination cavities | A      | B      | C      | D      | H      | Cable range (mm) | Cable tie <sup>(1)</sup> |          |
|---------------|---------------|------------------|---------------------------------|--------|--------|--------|--------|--------|------------------|--------------------------|----------|
| Black UL94 V2 | White UL94 V0 |                  |                                 |        |        |        |        |        |                  |                          |          |
| SMS2RDH1      | SMS2RDH3      | 2                | 0                               | 1.244" | 0.389" | 2.551" | 0.436" | 1.936" | 0.5-8.4          | TF4D                     |          |
| SMS3RDH1      | SMS3RDH3      | 3                | 0                               | 1.381" |        | 2.716" | 0.637" |        | 0.8-7.3          |                          |          |
| SMS4RDH1      | SMS4RDH3      | 4                | 0                               | 1.503" |        | 2.929" | 0.834" |        | 1.5-10           |                          |          |
| SMS6RDH1      | SMS6RDH3      | 6                | 2                               | 0.362" | 0.590" | 2.858" | 0.637" | 2.003" | 1.7-9.2          | TF5D                     |          |
| SMS9RDH1      | SMS9RDH3      | 9                | 4                               | 1.409" | 0.787" | 2.964" |        | 2.055" | 3.9-14.2         |                          |          |
| SMS12RDH1     | SMS12RDH3     | 12               | 6                               | 1.499" | 0.988" | 2.834" |        | 2.074" | 4.0-15.0         |                          |          |
| SMS15RDH1     | SMS15RDH3     | 15               | 8                               | 1.413" | 1.188" | 3.200" | 0.834" | 2.173" | 5.0-16.2         | TF5D                     |          |
| SMS18RDH1     | SMS18RDH3     | 18               | 10                              | 1.421" | 1.389" |        |        | 3.558" | 2.251"           |                          | 5.8-20.3 |
| SMS24RDH1     | SMS24RDH3     | 24               | 15                              | 1.562" |        |        |        | 5.039" | 1.834"           |                          | 2.492"   |
| SMS36RDH1     | SMS36RDH3     | 36               | 24                              | 2.149" | 0.988" | 5.039" | 1.834" | 2.492" | 8.8-24.5         |                          |          |

\*Contacts supplied separately (1) Cable tie not included

Cable plug with integrated strain relief hood





| Part number   |               | Nbr. of contact* | Nbr. of discrimination cavities | A      | B      | C      | D      | H      | Cable range (mm) | Cable tie <sup>(1)</sup> |          |
|---------------|---------------|------------------|---------------------------------|--------|--------|--------|--------|--------|------------------|--------------------------|----------|
| Black UL94 V2 | White UL94 V0 |                  |                                 |        |        |        |        |        |                  |                          |          |
| SMS2PDH1      | SMS2PDH3      | 2                | 0                               | 1.555" | 0.645" | 2.551" | 0.555" | 2.247" | 0.5-8.4          | TF4D                     |          |
| SMS3PDH1      | SMS3PDH3      | 3                | 0                               | 1.692" |        | 2.716" | 0.732" |        | 0.8-7.3          |                          |          |
| SMS4PDH1      | SMS4PDH3      | 4                | 0                               | 1.814" |        | 2.929" | 0.933" |        | 1.5-10           |                          |          |
| SMS6PDH1      | SMS6PDH3      | 6                | 2                               | 1.673" | 0.846" | 2.858" | 0.732" | 2.314" | 1.7-9.2          | TF5D                     |          |
| SMS9PDH1      | SMS9PDH3      | 9                | 4                               | 1.720" | 1.051" | 2.964" |        | 2.366" | 3.9-14.2         |                          |          |
| SMS12PDH1     | SMS12PDH3     | 12               | 6                               | 1.810" | 1.248" | 2.834" |        | 2.366" | 4.0-15.0         |                          |          |
| SMS15PRDH1    | SMS15PDH3     | 15               | 8                               | 1.724" | 1.444" | 3.200" | 0.933" | 2.484" | 5.0-16.2         | TF5D                     |          |
| SMS18PDH1     | SMS18PDH3     | 18               | 10                              | 1.732" | 1.645" |        |        | 3.558" | 2.562"           |                          | 5.8-20.3 |
| SMS24PDH1     | SMS24PDH3     | 24               | 15                              | 1.873" |        |        |        | 5.039" | 1.933"           |                          | 2.842"   |
| SMS36PDH1     | SMS36PDH3     | 36               | 24                              | 2.460" | 1.248" | 5.039" | 1.933" | 2.842" | 8.8-24.5         |                          |          |

\*Contacts supplied separately (1) Cable tie not included

Note: all dimensions are in inches

## Accessories for standard Quick Mating connectors

### Pin protection shroud for panel mount receptacle



When pins are inserted into the panel mount receptacle half (SMS...R1) of the Quick Mating connector, an optional pin protection shroud can be installed.

The shroud is mounted at the same time as the receptacle by holding the shroud against the mating side of the panel with both cut-outs lined up. The receptacle is then inserted in place, trapping the shroud between the receptacle and panel. The use of the pin protection shroud reduces the allowable thickness of the panel from 2.3 to 1.6 mm max.

| Part number          | Nbr. of contact position | A      | B      |
|----------------------|--------------------------|--------|--------|
| <b>Black UL94 V2</b> |                          |        |        |
| SMS2CSB1             | 2                        | 0.779" | 0.740" |
| SMS3CSB1             | 3                        | 0.921" |        |
| SMS4CSB1             | 4                        | 1.118" |        |
| SMS6CSB1             | 6                        | 0.921" | 0.940" |
| SMS9CSB1             | 9                        |        | 1.141" |
| SMS12CSB1            | 12                       |        | 1.338" |
| SMS15CSB1            | 15                       |        | 1.539" |
| SMS18CSB1            | 18                       |        | 1.740" |
| SMS24CSB1            | 24                       | 1.118" |        |
| SMS36CSB1            | 36                       | 2.129" | 1.338" |

### Strain relief hoods



Separate strain relief hoods are available for all standard plugs SMS...P1. The hoods consist of identical halves that snap into position on the plug and are secured in place with the cable tie drawn tightly around the cable entry collar.

Catalog numbers designate a complete hood (2 halves) SMS...H1.

The cable tie is not included (TF4D – TF5D).

Two three and four position hoods are single piece units.

| Part number          | Nbr. of contact position |
|----------------------|--------------------------|
| <b>Black UL94 V2</b> |                          |
| SMS2H1               | 2                        |
| SMS3H1               | 3                        |
| SMS4H1               | 4                        |
| SMS6H1               | 6                        |
| SMS9H1               | 9                        |
| SMS12H1              | 12                       |
| SMS15H1              | 15                       |
| SMS18H1              | 18                       |
| SMS24H1              | 24                       |
| SMS36H1              | 36                       |

### Discrimination pins

For discrimination pins on both standard Quick Mating and Quick Mating Pin Headers cable and board mount:  
See accessories section.

Note: all dimensions are in inches