

USB Type B Connector Receptacle

4Pos Thd



Specifications:

Material:

Insulator : PBT, glass filled
 Insulator Colour : Black
 Contacts : Phosphor Bronze
 Shell : Copper Alloy, Nickel plated

Plating:

Gold Flash over Nickel underplate on contact area, Tin over Copper underplate on PCB tails

Electrical:

Operating Voltage : 30V AC max.
 Current Rating : 1A max.
 Contact Resistance : 30mΩ max.
 Insulation Resistance : 1,000MΩ min.
 Dielectric Withstanding Voltage : 500V AC for 1 minute


Temperature Rating:

Operating Temperature : -20°C to +85°C

Environmental:

Lead free
 Recommended Soldering Temp : 235 for 5 sec.

**RoHS
Compliant**



Part Number Table

Description	Part Number
USB, Type B, Single Port, Right Angle, Thru-Hole, Gold Flash	USB-B-S-RA

Dimensions : Inches (Millimetres)

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicom is the registered trademark of the Group. © Premier Farnell plc 2012.

