ESD Ring Binder





ESD Ring Binder

FEATURES:

- Dual fold spine construction ring binder with 2 x 25mm D-ring mechanism
- 2.25mm recycled grey board covered with 0.35mm thick permanently antistatic light blue PVC
- Marked with the ESD warning symbol to BS EN 61340-5-1 on the front and on the spine.



SPECIFICATION:

DETAILS	STANDARD	TYPICAL VALUE
Surface Resistance Rs	DIN53482	10 ¹¹ Ω/m²
Decay Time	EIA 541 app F	T ₁₀₀₀ <4 secs

PRODUCT CODE:	DESCRIPTION:	SIZE:	ADDITIONAL NOTES:
105-0020	ESD Ring Binder	A4	2 x 25mm Rings
105-0016	ESD Ring Binder	A4	2 x 50mm Rings

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. ® Premier Farnell plc 2011.

