

## Bloc'Lube

**Product Code: BLR/BLV**

### PRODUCT DESCRIPTION

**Electrolube Bloc'Lube** is a one part, air-drying, tamper evident seal for screws, nuts, tuneable items and other "factory fixed" components where evidence of unauthorised access is required. It is also ideal for application onto rotary controls to ensure that settings do not move under vibration loads etc.

**Bloc'Lube** is available as a red or green lacquer.

### TYPICAL PROPERTIES

Colour: Red or Green  
Flash Point: 3.3°C

### DIRECTIONS FOR USE

**Bloc'Lube** should be applied directly onto the component with the brush contained in the lid of the bottle. It should be applied in an even film in sufficient quantity to be easily visible.

The coating will be tack free after 10 minutes but remains flexible for up to 24 hours. This is to allow fine tuning. After this time the seal will become brittle and any interference or tampering will break the seal and become self-evident.

### REMOVAL

**Bloc'Lube** is usually removed physically with a screwdriver or similar. Any chips remaining may be removed using **Electrolube Ultrasolve** or **Printasolve** (take care with these solvents on sensitive plastics)

### PACKAGING

Bloc'Lube - Red  
Bloc'Lube - Green

### ORDER CODE

BLR15ML  
BLV15ML

TECHNICAL  
DATA  
SHEET



### **Copyright Electrolube 2003**

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

