



## **Standard T&B Catalog Number:**

TY27M-2

**UPC Number:** 78621084500 Active

Pk, Military Specified (MIL-SPEC MS3367-3-2)

Status:

**Description:** 

Cable Tie 120lb 13" Red Nylon with Stainless Steel Locking Device Bulk

Eastures	.0 W.00007 0 2)
Features	
	Oval low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time. Because there are no notches, Ty-Rap ties provide an infinite number of locking positions while fastening the tie at the precise bundle diameter needed.
	The No-Slip Tail provides easy grip during tension- ing. Ty-Rap ties feature a unique friction surface de- signed to reduce slippage during installation.
	Smooth, notchless body reduces stress concentration points under tension, making the tie stronger and lower profile than notched body ties. Ribbed and Stippled body grips the bundle and prevents slippage. Rounded edges protect insulation, preventing sharp edges from damaging cables.
General	
Material	Nylon 6.6
Color	Red
Dimension Information	
Nominal Length (inches)	13
Length (inches)	13.4
Width (inches)	.270
Max. Wire Bundle Diameter (inches)	3.5
Specifications	
Temperature Rating	-40°F to 185°F
Flammability Rating	UL 94 V-2
Tooling	
Application Tools	WT197, ERG120
Packaging	
TSP Order Multiple	500
T&B Order Multiple T&B Inner Pack	500
	1000
Package in Units Package Type	Bulk
T&B Sold in UOM	Each
T&B Weight Per UOM	1.06 lbs. per 100
Application Support	1.00 lbs. pci 100
Application Support	



Overview	Available on Website
Material Selection Guide	Available on Website
Available Colors	Available on Website
Certifications	
RoHS Compliance	Yes

## For further technical assistance, please contact us...

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com