


5500FE Multi-Conductor - Commercial Audio Systems - 2 Conductors Cabled

For more Information
please call

1-800-Belden1



General Description:

Security & Alarm Cable, Riser-CMR, 2-22 AWG stranded bare copper conductors with polyolefin insulation, Beldfoil® shield and PVC jacket with ripcord

Usage (Overall)

Suitable Applications: Intercom/PA Systems, Sound/Audio Systems

Physical Characteristics (Overall)

Conductor

AWG:

| # Conductors | AWG | Stranding | Conductor Material |
|--------------|-----|-----------|--------------------|
| 2 | 22 | 7x30 | BC - Bare Copper |

Total Number of Conductors: 2

Insulation

Insulation Material:

| Insulation Material | Wall Thickness (mm) |
|---------------------|---------------------|
| PP - Polypropylene | 0.203 |

Outer Shield

Outer Shield Material:

| Outer Shield Trade Name | Type | Outer Shield Material | Coverage (%) |
|-------------------------|------|--|--------------|
| Beldfoil® | Tape | Aluminum Foil-Polyester Tape w/Shorting Fold | 100 |

Outer Shield Drain Wire AWG:

| AWG | Stranding | Drain Wire Conductor Material |
|-----|-----------|-------------------------------|
| 24 | Solid | TC - Tinned Copper |

Outer Jacket

Outer Jacket Material:

| Outer Jacket Material | Nom. Wall Thickness (mm) |
|--------------------------|--------------------------|
| PVC - Polyvinyl Chloride | 0.432 |

Outer Jacket Ripcord: Yes

Overall Cable

Overall Cabling Lay Length & Direction:

| Length (mm) | Direction | Twists (twist/m) |
|-------------|-----------|------------------|
| 63.500 | Left Hand | 15.749 |

Overall Cabling Color Code Chart:

| Number | Color |
|--------|-------|
| 1 | Black |
| 2 | Red |

Overall Nominal Diameter: 3.200 mm

Mechanical Characteristics (Overall)

Operating Temperature Range: -20°C To +75°C

UL Temperature Rating: 75°C

Bulk Cable Weight: 14.138 Kg/Km

5500FE Multi-Conductor - Commercial Audio Systems - 2 Conductors Cabled

| | |
|-----------------------------------|-----------|
| Max. Recommended Pulling Tension: | 105.422 N |
| Min. Bend Radius/Minor Axis: | 31.750 mm |

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

| | |
|---------------------------------------|------------|
| NEC/(UL) Specification: | CMR |
| NEC Articles: | 800 |
| CEC/C(UL) Specification: | CMG |
| EU Directive 2011/65/EU (ROHS II): | Yes |
| EU CE Mark: | Yes |
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2002/95/EC (RoHS): | Yes |
| EU RoHS Compliance Date (mm/dd/yyyy): | 04/01/2005 |
| EU Directive 2002/96/EC (WEEE): | Yes |
| EU Directive 2003/11/EC (BFR): | Yes |
| CA Prop 65 (CJ for Wire & Cable): | Yes |
| MII Order #39 (China RoHS): | Yes |

Flame Test

| | |
|-------------------|-----------------------|
| UL Flame Test: | UL1666 Vertical Shaft |
| C(UL) Flame Test: | FT4 |

Suitability

| | |
|-----------------------|-----|
| Suitability - Indoor: | Yes |
|-----------------------|-----|

Plenum/Non-Plenum

| | |
|----------------|--------|
| Plenum Number: | 6500FE |
|----------------|--------|

Surface Printing (Overall)

Electrical Characteristics (Overall)

Nom. Capacitance Conductor to Conductor:

| |
|--------------------|
| Capacitance (pF/m) |
| 113.195 |

Nom. Capacitance Cond. to Other Conductor & Shield:

| |
|--------------------|
| Capacitance (pF/m) |
| 203.422 |

Nom. Conductor DC Resistance:

| |
|---------------------|
| DCR @ 20°C (Ohm/km) |
| 52.8241 |

Nominal Outer Shield DC Resistance:

| |
|---------------------|
| DCR @ 20°C (Ohm/km) |
| 52.8241 |

Max. Operating Voltage - UL:

| |
|-----------|
| Voltage |
| 300 V RMS |

Max. Recommended Current:

| Description | Current |
|----------------------|---------------------------------------|
| 10C Temperature Rise | 2.8 Amps per conductor @ 25°C ambient |

Put Ups and Colors:

5500FE Multi-Conductor - Commercial Audio Systems - 2 Conductors Cabled

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|-----------------|--------|-------------|-------|-------|-------------------|
| 5500FE 008U1000 | 305 MT | 4.990 KG | GRAY | | 2 #22 PP FS FRPVC |
| 5500FE 008U500 | 152 MT | 2.722 KG | GRAY | | 2 #22 PP FS FRPVC |
| 5500FE 0081000 | 305 MT | 4.990 KG | GRAY | | 2 #22 PP FS FRPVC |
| 5500FE 008500 | 152 MT | 2.495 KG | GRAY | | 2 #22 PP FS FRPVC |
| 5500FE 009U1000 | 305 MT | 4.990 KG | WHITE | | 2 #22 PP FS FRPVC |
| 5500FE 010U1000 | 305 MT | 4.990 KG | BLACK | | 2 #22 PP FS FRPVC |

Revision Number: 3 Revision Date: 10-02-2013

© 2013 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.