

Page 1 of 7

Prep	pared to OSHA, ACC,	, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 2	2.1 MS	DS Revision Date: 01/29/	/2011		
1.	1. PRODUCT IDENTIFICATION CHEMICAL RESPONSE CARD: 02						
1.1	Product Name:	DeoxIT® D-Series, D5S-6, 5% Spray, 142 g	RESPONSE		_		
1.2	Chemical Name:	See ingredients listed in section 3	TEAM PPE:				
1.3	Synonyms:	DeoxIT®, D5S-6, 5% Spray					
1.4	Trade Names:	DeoxIT [®] , D5S-6, 5% Spray	WHMIS:)		
1.5	Product Use:	Clean, deoxidize & improve electrical contacts & connectors	HEALTH:		1		
1.6	Manufacturer's Name:	CAIG Laboratories, Inc.	FLAMMABI	2			
1.7	Manufacturer's Address:	12200 Thatcher Court, Poway, CA 92064-6876	PHYSICAL H	HAZARDS:	0		
1.8	Business Phone:	+1 (800)-224-4123	PERSONAL	PROTECTION:	B		
1.9	Emergency Phone:	CHEMTREC 1-800-424-9300/1-703-527-388	7				
1.10	Other Product Names:	DeoxIT®, D5MS-15, 5% Spray, 14 g					
2.1	1	2. HAZARD IDENTIFICATION					
	Hazard Identification: Colorless, volatile liquid with ethereal and faint sweetish odor. Flammable aerosol. Overexposure may cause dizziness and loss of concentration. At higher levels, CNS depression and cardiac arrhythmia may result from exposure. Vapors displace air and can cause asphyxiation in confined spaces. This product is Classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS according to the classification criteria of [NOHSC: 1088 (2004)] and ADG Code (Australia).						
2.2	Routes of Entry:	Inhalation: YES Absorption	YES	Ingestion:	YES		
2.3	Effects of Exposure: FYES: Mild to moderate irritation. SKIN: Irritant and potential skin sensitizer. Prolonged or repeated contact may cause contact dermatitis (localized redness or rash). INGESTION: Gastrointestinal irritation and central nervous system depression. INHALATION: Central nervous system depressant.						
2.4	Symptoms of Overexposure: EYES: Mild irritation, redness, and watering. SKIN: Contact dermatitis, characterized by localized red or puffy dry skin and itching. INGESTION: Nausea, vomiting, and diarrhea. INHALATION: Mouth, nose, and throat irritation, dizziness, nausea, light-headedness, drunkenness, and loss of coordination.						
2.5	Acute Health Effects: INGESTION: Gastrointestinal irritation and central nervous system depression. EYES: Mild to moderate irritation. SKIN: Irritant and potential skin sensitizer. Prolonged or repeated contact may cause contact dermatitis (localized redness or rash). INGESTION: Gastrointestinal irritation and central nervous system depression.						
2.6	INHALATION: Chronic Health Effects:	Central nervous system depressant. Irritating to the upper respirate	οιλ μασι.				
	EYES: Mild to moderate irritation. SKIN: Irritant and potential skin sensitizer. Prolonged or repeated contact may cause contact dermatitis (localized redness or rash). INGESTION: Gastrointestinal irritation and central nervous system depression.						
0.7		Central nervous system depressant. Irritating to the upper respirate	bry tract.				
2.7	Target Organs: Eyes, skin and resp	iratory system.					
		ot Determined; NE = Not Established; NF = Not Found; C = Ceiling Limit; See S formation is included. It is located in appropriate sections based on the AN			ied		



Page 2 of 7

Pren	Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 2.1 MSDS Revision Date: 01/29/2011													
Πep														
		2 001	DOCITION					ATIO						
		3. COM	POSITION	& INGRE	DIEN									
						10		EXPOSU						1
						AC	-	·	Ppm	•	,	DSHA ppm		OTHER
								ES-	ES-	ES-		ppm		OTTLER
	CHEMICAL NAM	E(S) CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	TWA	STEL	-	TLV	STEL	IDLH	
PETRO	DLEUM NAPHTHA	64742-88-7	XS5250000	265-191-7	≤ 75	100	NE	100	NE	NE	100	NE	NE	
DIFLU	OROETHANE	75-37-6	KI4100000	200-866-1	≤ 20	1000	NA	1000	NA	NA	1000	NA	NA	SKIN
Deox	IT® D100L	TRADE SECRET	NA	NA	≤ 5	NA	NA	NA	NA	NA	NA	NA	NA	
			4. FI	RST AID M	EASU	RES								
4.1	First Aid:													
	EYES:	Flush eyes thoroughly complete flushing. If in							s, hol	ding e	yelid(s) ope	en to	ensure
	SKIN:	Remove contaminated	-						er. If	irritatic	on pers	ists, s	eek r	prompt
		medical attention. Do	not wear con	taminated clo	thing u	ntil after								•
	INGESTION:	Drink plenty of water. I	f irritation per	sists, contact c	a physic	ian.								
	INHALATION: Remove victim to fresh air at once. If breathing is difficult, administer supplemental oxygen and seek immediate medical attention. If breathing stops, perform artificial respiration.				ediate									
4.2	Medical Conditions Aggravated by Exposure:					1								
	None reported by the manufacturer.				2									
							_					•		
	PHYSICAL HAZAR		ARD	S		0								
								PROT	ECTI	VE E	QUIP	MEI	TI	
								EYES	SK	(IN				
			5. FIRE	FIGHTING	MEA	SURES	S							
5.1	Flashpoint & Method:													
5.0	1	(120 °F – 130 °F). Level 2	aerosol.											
5.2	Autoignition Temperat	ture:												
5.3	Flammability Limits:		Lower Explos	sive Limit (LEL):		NA		Upper E		ve Limit	· (UEL):		Ν	Α
5.4	Fire & Explosion Hazard													
	Carbon dioxide,	carbon monoxide, hydro	ocarbons.											
5.5	Extinguishing Methods													
	CO ₂ , Alcohol for	am, Dry Chemical, Water	Fog									2		
5.6	Firefighting Procedure										1		0	
		HA approved self-contai											U	/
		ontainers involved in fire											\searrow	,
		ct flame contact should									Ì			
	weakening of container structure. Keep containers cool until well after the fire is out to prevent rupture. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any													
	natural waterway			ing sewers, un	anis, ul	inking (soppiy,	or un	,				



6.1

Spills:

MATERIAL SAFETY DATA SHEET

Page 3 of 7

MSDS-E-D5S-A

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards N

MSDS Revision: 2.1

MSDS Revision Date: 01/29/2011

6. ACCIDENTAL RELEASE MEASURES

Secure spill area and deny entry to all unprotected individuals. Individuals involved in the cleanup should wear appropriate personal protective equipment. Area may become slippery. Absorb product onto porous material, such as sand, clay, diatomaceous earth or commercial absorbent material. Place into leak-proof, U.S. DOT-approved containers. If necessary, cover all drains and dike well ahead of the spill to prevent runoff into sewers, drains, and all waterways. Contact appropriate local or provincial authorities for assistance and/or reporting requirements.

7. HANDLING & STORAGE INFORMATION

7.1 Work & Hygiene Practices:

 Wash hands thoroughly after using this product and before eating, drinking, or smoking. Remove soiled clothing to prevent prolonged skin contact.

 Storage & Handling:

7.2 Storage & Handli

Store at temperatures between 59 °F and 95 °F (15 °C and 35 °C) in a dry, well-ventilated location. Keep away from heat, sparks, open flame, and other sources of ignition. Normal shelf-life: 2-3 years.

7.3 Special Precautions:

Empty containers can contain flammable vapors. Do not cut, drill, grind, weld or perform similar operations on or near containers.

8. EXPOSURE CONTROLS & PERSONAL PROTECTION

8.1 Ventilation & Engineering Controls

Respiratory Protection:

Use with adequate ventilation (e.g., open doors and windows, local exhaust ventilation). Ensure appropriate decontamination equipment is available (e.g., sink, safety shower, eye-wash station).

None required, when used with adequate ventilation.

8.3 Eye Protection:

8.2

Wear safety glasses with side shields (ANSI Z87) under normal use conditions.

8.4 Hand Protection

None required under normal conditions of use. However, may cause skin irritation in some sensitive individuals. In such cases, wear rubber or impervious plastic gloves.

8.5 Body Protection:

Use as necessary to prevent skin contact.

9.1	Density:	0.75
9.2	Boiling Point:	171.1 °C – 204 °C @ 760 mmHg
9.3	Melting Point:	ΝΑ
9.4	Evaporation Rate:	0.11 (n-Butyl Acetate = 1.0)
9.5	Vapor Pressure:	35 psig @ 20 °C, 50 psig @ 50 °C
9.6	Molecular Weight:	ΝΑ
9.7	Appearance & Color:	Light red, aerosol
9.8	Odor Threshold:	Ethereal/hydrocarbon odor
9.9	Solubility:	Not soluble in water
9.10	рН	ND
9.11	Viscosity:	10.0 cps
9.12	VOC (grams/liters)	588 g/l
9.13	Other Information:	Vapor Density = 4.9 (Air = 1.0)



Page 4 of 7

		10. STABILITY & REACTIVITY				
0.1	Stability:	Stable under normal conditions of use (see section 7).				
0.2	Hazardous Decomposition Products:	Change in color signifies exposure to ultraviolet light or exceeding shelf life. Will not degrade unstable products. Discard solution.				
0.3	Hazardous Polymerization:	Will not occur.				
0.4	Conditions to Avoid:	Use or storage near open flames, sparks, high heat (>100 °F) or other heat sources, and proximity to incompatible substances and heavily trafficked areas.				
0.5	Incompatible Substances:	Strong oxidizers.				
		11. TOXICOLOGICAL INFORMATION				
1.1	Toxicity Data:	This product has not been tested on animals to obtain toxicological data. There are toxicology dat for the components of this product, which are found in the scientific literature. These data have n been presented in this document.				
11.2	Acute Toxicity:	See section 3.5				
1.3	Chronic Toxicity:	See section 3.6				
1.4	Suspected Carcinogen:	NE				
11.5	Reproductive Toxicity:	This product is not reported to produce reproductive toxicity in humans.				
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.				
	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.				
	Teratogenicity:	This product is not reported to produce teratogenic effects in humans.				
	Reproductive Toxicity:	This product is not reported to produce reproductive effects in humans.				
1.6	Irritancy of Product:	See Section 3.3				
1.7	Biological Exposure Indices:	NE				
1.8	Physician Recommendations:	Treat symptomatically.				
		12. ECOLOGICAL INFORMATION				
2.1	Environmental Stability:	This product will slowly volatile from soil. Components of this product will slowly decompose in organic compounds.				
2.2	Effects on Plants & Animals:	There is no specific data available for this product.				
2.3	Effects on Aquatic Life:	Releases of large volumes of this product are expected to be harmful or fatal to overexpose aquatic life.				
2.4	Environmental Impact (Percent by Weight):	CFC: 0.0% HCFC: 0.0% CL.SOLV.: 0.0% VOC: 75.0% HFC: 20.0% ODP: 0.0%				
		VOC. 75.0% INC. 20.0% ODF: 0.0%				
		13. DISPOSAL CONSIDERATIONS				
3.1	Waste Disposal: Dispose of in accordance with	federal, state or local regulations.				
13.2	Dispose of in accordance with federal, state or local regulations. Special Considerations:					



Page 5 of 7

Prep	ared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 2.1	MSDS Revision Date: 01/29/2011
	14. TRANSPORTATION INFORMATION	
	pasic description (ID Number, proper shipping name, hazard class & division, packing group) is show tional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.	vn for each mode of transportation.
14.1	49 CFR (GND): CONSUMER COMMODITY, ORM-D	
14.2	IATA (AIR): CONSUMER COMMODITY, 9, ID8000 (≤ 500 ml) UN1950, AEROSOLS, 2.1 (> 500 ml)	
14.3	IMDG (OCN): UN1950, AEROSOLS, 2.1, LTD QTY (≤ 1.0 L)	
14.4	TDGR (Canadian GND): MARK PACKAGE "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (≤ 1.0 L)	
14.5	ADR/RID (EU): 1950 AEROSOLS, 2.1, ADR, LTD QTY	
14.6	SCT (Mexico): UN1950, AEROSOLS, 2.1, CANTIDAD LIMITADA	
14.7	ADGR (Australia): UN1950, AEROSOLS, 2.1, LTD QTY	
	15. REGULATORY INFORMATION	
15.1	SARA Reporting Requirements: NA	
15.2	SARA Threshold Planning Quantity: NA	
15.3	TSCA Inventory Status: All chemical substances of this product are listed on the TSCA inventory or are otherwise exempt fi	rom inventory status.
15.4	CERCLA Reportable Quantity (RQ):	
15.5	Other Federal Requirements: NA	
15.6	Other Canadian Regulations This product has been classified according to the hazard criteria of the Controlled Products Regu (CPR) and the MSDS contains all of the information required by the CPR. The components of this p are listed on the DSL/NDSL. None of the components of this product are listed on the Pr Substances List.	roduct (//)()()()
15.7	State Regulatory Information: The primary component of this product is not listed on the following state lists: California Massachusetts Right to Know List of Chemicals; New Jersey Right to Know List 8:59 Appendix A; F List 34 323 Appendix A; Wisconsin Hazardous Substances List NR 605.09; Minnesota Hazardous Substances List.	ennsylvania Hazardous Substances
15.8	67/548/EEC (European Union) Requirements: The primary component of this product is listed in Annex I of EU Directive 67/548/EEC: <u>Petroleum Naphtha</u> : Flammable, Harmful (F, Xn). R: 10-65 – Flammable. Harmful: may cause damage if swallowed. S: 2-23-24-62 – Keep away from children. Do not breathe gas, fumes, vo spray. Avoid contact with skin. If swallowed, do not induce vomiting: seek medical advice immed and show this MSDS or the container label.	por or



Page 6 of 7

MSDS-E-D5S-A

MSDS Revision: 2.1 MSDS Revision Date: 01/29/2011 Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards **16. OTHER INFORMATION** 16.1 Other Information: NA Terms & Definitions: 16.2 See last page of this MSDS. 16.3 Disclaimer This Material Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & CAIG Laboratories, Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition. 16.4 Prepared for: CAIG Laboratories. Inc. 12200 Thatcher Court Poway, CA 92064-6876 +1 (800) CAIG-123 (244-4123) phone +1 (858) 486-8398 fax http://www.caig.com/ 16.5 Prepared by: ShipMate, Inc. P.O. Box 787 ShipMa 780 Buckaroo Trail Suite D Sisters, OR 97759 Dangerous Goods +1 (310) 370-3600 phone Training & Consulting +1 (310) 370-5700 fax http://www.shipmate.com



Page 7 of 7

MSDS-E-D5S-A

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 2.1

DEFINITION OF TERMS

MSDS Revision Date: 01/29/2011

A large number of abbreviations and acronyms appear on a MSDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No. Chemical Abstract Service Number

EXPOSURE LIMITS IN AIR:

ACGIH American Conference on Governmental Industrial Hygienists		
TLV Threshold Limit Value		
OSHA U.S. Occupational Safety and Health Administration		
PEL Permissible Exposure Limit		
IDLH	Immediately Dangerous to Life and Health	

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person					
	whose heart has stopped receives manual chest					
	compressions and breathing to circulate blood and provide					
	oxygen to the body.					

HEALTH


HYSICAL HAZARDS

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS

HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard	FLAMMABILITY
1	Slight Hazard	
2	Moderate Hazard	PHYSICAL HAZARD
3	Severe Hazard	PERSONAL PROTECTION
4	Extreme Hazard	

PERSONAL PROTECTION RATINGS:



OTHER STANDARD ABBREVIATIONS:

NA	Not Available
NR	No Results
NE	Not Established
NF	Not Found
ND	Not Determined
ML	Maximum Limit
SCBA	Self-Contained Breathing Apparatus


NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:

Autoignition	Minimum temperature required to initiate combustion
Temperature	in air with no other source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by
	volume, that will explode or ignite in the presence of
	an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air,
	by volume, that will explode or ignite in the presence of
	an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
₩-	Use No Water
ох	Oxidizer



TOXICOLOGICAL INFORMATION:

LD 50	Lethal Dose (solids & liquids) which kills 50% of the exposed animals s
LC 50	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD _{lo}	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD _{io} , LD _{io} , & LD _o or	Lowest dose (or concentration) to cause lethal or
TC, TC _o , LC _{lo} , & LC _o	toxic effects
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TLm	Median threshold limit
log Kow or log Koc	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System				
DOT	U.S. Department of Transportation				
TC	Transport Canada				
EPA	U.S. Environmental Protection Agency				
DSL	Canadian Domestic Substance List				
NDSL	Canadian Non-Domestic Substance List				
PSL	Canadian Priority Substances List				
TSCA	U.S. Toxic Substance Control Act				
EU	European Union (European Union Directive 67/548/EEC)				

EC INFORMATION:

		A	¥		B	×	×
С	E	F	Ν	0	T+	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful