

SECTION 1: CHEMICAL PRODUCT AND COMPANY INFORMATION**Company Address:**8125 Cobb Center Drive
Kennesaw, GA 30152Product Information: 800-TECH-401
Customer Service: 800-645-5244Emergency: (Chemtrec) 800-424-9300
Revision Date: February 17, 2010**Product Identification****KONFORM[®] SR HIGH VISCOSITY (Liquid)****Product Code:** CTSR-HV1, CTSR-HV5**SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS#	Wt. % Range
Silicone polymer	68952-93-2	50.0-80.0
Toluene	108-88-3	10.0-25.0
Isohexane, a mixture of:		
2-methylpentane	107-83-5	0.1-10.0
3-methylpentane	96-14-0	0.1-10.0
2,3-dimethylbutane	79-29-8	0.1-10.0
2,2-dimethylbutane	75-83-2	0.1-10.0
n-hexane	110-54-3	0.1-1.0
Acetone	67-64-1	1.0-10.0
Propylene glycol methyl ether acetate	108-65-6	3.0-8.0

SECTION 3: HAZARD IDENTIFICATION**Emergency Overview:** Translucent, slightly green liquid with hydrocarbon odor. This product is extremely flammable. Liquid will irritate eyes and skin under repeated or prolonged exposure. Breathing high concentrations of product vapor may produce drowsiness and a headache.**Potential Health Effects:****Eyes:** Liquid, aerosols and vapors of this product are irritating and can cause pain, tearing, reddening and swelling accompanied by a stinging sensation.**Skin:** Contact causes skin irritation.**Ingestion:** Harmful if swallowed. Irritating to mouth, throat and stomach. May cause optic nerve damage.**Inhalation:** Harmful if inhaled. High concentrations of vapors in immediate area can displace oxygen and can cause dizziness, unconsciousness, and even death with longer exposure. Keep people away from such vapors without self-contained breathing apparatus.**Pre-Existing Medical Conditions Aggravated by Exposure:** Heart, lung, skin, eye.**SECTION 4: FIRST AID MEASURES****Eyes:** Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Have eyes examined and tested by medical personnel if irritation develops or persists.**Skin:** Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists. Wash clothing separately before reuse.**Ingestion:** Do not induce vomiting. Get immediate medical attention.**Inhalation:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.**SECTION 5: FIRE FIGHTING MEASURES****Flash Point:** 60 F (16C) (TCC) **LEL/UEL:** Not established (% by volume in air)**Extinguishing Media:** Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.**Fire Fighting Instructions:** As in any fire, wear self-contained breathing apparatus (pressure-demand, MSHA/NIOSH approved or equivalent) and full protective gear.**SECTION 6: ACCIDENTAL RELEASE MEASURES****Large Spills:** Shut off leak if possible and safe to do so. Wear self-contained breathing apparatus and appropriate personal protective equipment. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container for proper disposal. Do not flush to sewer. Avoid runoff into storm sewers and ditches which lead to waterways. **Small Spills:** Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container for proper disposal.**SECTION 7: HANDLING AND STORAGE**

Avoid prolonged or repeated contact with eyes, skin, and clothing. Wash hands before eating. Use with adequate ventilation. Avoid breathing product vapor or mist. Do not reuse this container. Store in a cool dry place away from heat, sparks and flame. Keep container closed when not in use. Do not store in direct sunlight.

KEEP OUT OF REACH OF CHILDREN.**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION****Exposure Guidelines:**

CHEMICAL NAME	ACGIH TLV	OSHA PEL	ACGIH STEL
Isohexanes	500ppm	NA	1000ppm
Toluene	20 ppm	200 ppm	300 ppm Ceiling
Acetone	500 ppm	1000 ppm	750 ppm
Propylene glycol methyl ether acetate	NA	NA	NA

Work/Hygienic Practices: Good general ventilation should be sufficient to control airborne levels. Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product. If vapor concentration exceeds TLV, use NIOSH approved organic vapor cartridge respirator. Wear safety glasses with side shields (or goggles) and rubber or other chemically resistant gloves when handling this material.

NFPA and HMIS Codes:	NFPA	HMIS
Health	2	2
Flammability	3	3
Reactivity	1	1
Personal Protection	-	B

