

MATERIAL SAFETY DATA SHEET

Finished Product



Date Issued: 01/18/2003
MSDS No: 3500-A
Date Revised: 02/01/2012
Revision No: 7

Heavy Duty Adhesive Spray**1. PRODUCT AND COMPANY IDENTIFICATION**

PRODUCT NAME: Heavy Duty Adhesive Spray
PRODUCT DESCRIPTION: Contact Adhesive
PRODUCT CODE: 3500-11S

MANUFACTURER

Techspray, L.P.
 1001 N.W. 1st Street
 P.O. Box 949
 Amarillo, TX 79107

Emergency Contact: Chemtrec
Emergency Phone: 1-800-858-4043
Service Number: 1-800-858-4043

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC CCN#21858 (US Transportation) :(800) 424 - 9300
CANUTEC (Canadian Transportation) :(613) 996 - 6666
Emergency Phone :(800) 858 - 4043

2. HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW**

PHYSICAL APPEARANCE: Clear to amber, sticky resin.

POTENTIAL HEALTH EFFECTS

EYES: Liquid contact can cause irritation, which may be severe.

SKIN: Prolonged or repeated contact may cause skin irritation.

INGESTION: Harmful if swallowed.

INHALATION: Prolonged or excessive inhalation may cause respiratory tract irritation.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Symptoms of overexposure include: stinging, tearing, redness and pain.

SKIN: May cause slight irritation.

INGESTION: Not a likely route of exposure.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS	EINECS
Hexane	10 - 50	110-54-3	203-777-6
L.P.G.	10 - 25	68476-85-7	
Acetone	10 - 30	67-64-1	200-662-2
Petroleum Distillates	0	64742-89-8	
N-Butane	< 5	106-97-8	

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Get immediate medical attention.

SKIN: Wash with soap and water. Get medical attention if irritation develops or persists.

MATERIAL SAFETY DATA SHEET

Finished Product



Date Issued: 01/18/2003
MSDS No: 3500-A
Date Revised: 02/01/2012
Revision No: 7

Heavy Duty Adhesive Spray

INGESTION: Ingestion is unlikely because of the physical properties and is not expected to be hazardous. Do not induce vomiting unless instructed to do so by a physician.

INHALATION: Remove to fresh air.

5. FIRE FIGHTING MEASURES

FLASHPOINT AND METHOD: -20°C (-4°F) CC

FLAMMABLE LIMITS: 1.8 % to 9.5 %

GENERAL HAZARD: Flammable Liquid. Can release vapors that form explosive mixtures at temperatures at or above the flash point.

EXTINGUISHING MEDIA: Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

HAZARDOUS COMBUSTION PRODUCTS: Smoke, fumes and oxides of carbon.

EXPLOSION HAZARDS: Vapors may form explosive mixture with air.

FIRE FIGHTING EQUIPMENT: As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Avoid runoff into storm sewers and ditches which lead to waterways.

LARGE SPILL: -Implement cleanup procedures. -If in public area, keep public away and advise authorities. -Recover by pumping (use an explosion proof or hand pump) or with a suitable absorbent.

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: This material is a water pollutant and should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water.

RELEASE NOTES: Spills and releases may have to be reported to Federal and/or local authorities.

SPECIAL PROTECTIVE EQUIPMENT: Only personnel equipped with proper respiratory and skin/eye protection should be permitted in area. See Section 8 for details.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Keep container closed when not in use.

HANDLING: Ground and bond containers when transferring material.

STORAGE: Keep away from sources of ignition.

STORAGE TEMPERATURE: Minimum to (120°F) Maximum

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

MATERIAL SAFETY DATA SHEET

Finished Product



Date Issued: 01/18/2003
 MSDS No: 3500-A
 Date Revised: 02/01/2012
 Revision No: 7

Heavy Duty Adhesive Spray**EXPOSURE GUIDELINES**

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)							
		EXPOSURE LIMITS					
		OSHA PEL		ACGIH TLV		Supplier OEL	
Chemical Name		ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
Hexane	TWA	50 ppm ^[1]	180 mg/m ³ ^[1]	50 ppm	176 mg/m ³	NL ppm	NL mg/m ³
	STEL	NL ppm	NL mg/m ³	NL ppm	NL mg/m ³	NL ppm	NL mg/m ³
L.P.G.	TWA			1000			
Acetone	TWA	750 ppm ^[1]	1800 mg/m ³ ^[1]	750 ppm	1780 mg/m ³	NL ppm	NL mg/m ³
	STEL	1000 ppm	2400 mg/m ³	1000 ppm	2380 mg/m ³	NL ppm	NL mg/m ³

OSHA TABLE COMMENTS:
 1. NL = Not Listed

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

SKIN: The glove(s) listed below may provide protection against permeation. Gloves of other chemically resistant materials may not provide adequate protection. Viton, Solvex, Butyl, Buna, Neoprene.

RESPIRATORY: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Low odor.

COLOR: Straw-colored.

pH: Not Applicable

PERCENT VOLATILE: Not Applicable

BOILING POINT: > 37.7°C (100°F)

FLASHPOINT AND METHOD: -20°C (-4°F) CC

EVAPORATION RATE: > 1

SPECIFIC GRAVITY: 0.635 @ 25°C

VISCOSITY: Not Determined

(VOC): 54.800 % by weight

MATERIAL SAFETY DATA SHEET

Finished Product



Date Issued: 01/18/2003
 MSDS No: 3500-A
 Date Revised: 02/01/2012
 Revision No: 7

Heavy Duty Adhesive Spray**10. STABILITY AND REACTIVITY****STABLE:** Yes**HAZARDOUS POLYMERIZATION:** No**STABILITY:** Stable under normal conditions.**HAZARDOUS DECOMPOSITION PRODUCTS:** Oxides of Carbon (CO and CO₂) may form when heated to decomposition.**11. TOXICOLOGICAL INFORMATION****ACUTE**

Chemical Name	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)	INHALATION LC ₅₀ (rat)
Acetone	5800 mg/kg	20 g/kg	50100 ppm

EYE EFFECTS: May be mildly irritating to eyes.**CARCINOGENICITY**

Chemical Name	NTP Status	IARC Status	OSHA Status
Acetone	NOT LISTED	NOT LISTED	NOT LISTED

12. ECOLOGICAL INFORMATION**ENVIRONMENTAL DATA:** There is limited information available on the environmental fate and effects of this material. The primary environmental concern for release is the impact on aquatic and terrestrial species. Due care should be taken to avoid the accidental release of this material into the environment.**ECOTOXICOLOGICAL INFORMATION:** Rainbow trout LC₅₀=5540 mg/L/96H, Static conditions, 11-13 degrees C, Fathead Minnow LC₅₀=7280 - 8120 mg/L/96H Flow-through conditions, Bluegill LC₅₀ = 8300 mg/L/96H**13. DISPOSAL CONSIDERATIONS****DISPOSAL METHOD:** Federal, State, and Local laws governing disposal of materials can differ. Ensure compliance with proper authorities before disposal.**GENERAL COMMENTS:** Dispose of in a manner consistent with federal, state, and local regulations.**14. TRANSPORT INFORMATION****DOT (DEPARTMENT OF TRANSPORTATION)****PROPER SHIPPING NAME:** CONSUMER COMMODITY ORM-D**TECHNICAL NAME:** Mixed Aliphatic Hydrocarbons**PRIMARY HAZARD CLASS/DIVISION:** No classification**ROAD AND RAIL (ADR/RID)****KEMLER NUMBER:** UN1950

MATERIAL SAFETY DATA SHEET

Finished Product



Date Issued: 01/18/2003
 MSDS No: 3500-A
 Date Revised: 02/01/2012
 Revision No: 7

Heavy Duty Adhesive Spray**HAZARD CLASS:** 2.1**AIR (ICAO/IATA)****SHIPPING NAME:** CONSUMER COMMODITY ID8000**UN/NA NUMBER:** ID8000**PRIMARY HAZARD CLASS/DIVISION:** 9**PACKING GROUP:** NA**VESSEL (IMO/IMDG)****SHIPPING NAME:** AEROSOLS IN LIMITED QUANTITIES OF CLASS 2**UN/NA NUMBER:** 1950**PRIMARY HAZARD CLASS/DIVISION:** 2.1**PACKING GROUP:** NA**15. REGULATORY INFORMATION****UNITED STATES****SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)****313 REPORTABLE INGREDIENTS:** Acetone (CAS# 67-67-1) n-Hexane (110-54-3)**EPCRA SECTION 313 SUPPLIER NOTIFICATION**

Chemical Name	Wt. %	CAS
Hexane	10 - 50	110-54-3
Acetone	10 - 30	67-64-1

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)**CERCLA REGULATORY:** Acetone (67-64-1)

Chemical Name	Wt. %	CERCLA RQ
Acetone	10 - 30	5000 lbs.

CERCLA RQ: 5000 lbs**TSCA (TOXIC SUBSTANCE CONTROL ACT)**

Chemical Name	CAS
Hexane	110-54-3
Acetone	67-64-1

TSCA STATUS: All components of this product are either listed or exempt from listing in the TSCA inventory.**CANADA****WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM):** This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.**WHMIS CLASS:** Class A, B5, D2B (Aerosol, Flammable Aerosol, Toxic Materials)**DOMESTIC SUBSTANCE LIST (INVENTORY):** All components of this product are listed on the Canadian DSL.

MATERIAL SAFETY DATA SHEET

Finished Product



Date Issued: 01/18/2003
MSDS No: 3500-A
Date Revised: 02/01/2012
Revision No: 7

Heavy Duty Adhesive Spray


16. OTHER INFORMATION

APPROVED BY: Pierce A. Pillon **TITLE:** Chemist

PREPARED BY: Steve Cook

REVISION SUMMARY: This MSDS replaces the 05/19/2011 MSDS.

NFPA CODES



MANUFACTURER DISCLAIMER: To the best of our knowledge, the information contained herein is accurate. However, neither Tech Spray, L.P., or any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.