

GC Electronics
1801 Morgan Street
Rockford, IL 61102
Phone: (815) 968-9661
Fax: (815) 968-9731
www.gcelectronics.com

Product Name: Super Glue
MSDS Number: 140
Revision Date: 12/30/09
Supersedes Date: 6/23/06

MATERIAL SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Type: Cyanoacrylate Adhesive
Product Name: **Super Glue**
Part Number(s): **10-120**

Emergency Contact: Chemtrec
Phone (24 hours): (800) 424-9300

Section 1 - Identification of Product

Product Name: RP, SI, FS, HT, MG Series
Product Type: Ethyl-2-Cyanoacrylate Ester
Molecular Formula: C₆H₇NO₂

HMIS RATINGS		NFPA		Least	0
Health:	2	Health:	2	Slight	1
Flammability:	2	Fire Hazard:	2	Moderate	2
Reactivity:	2	Reactivity:	2	High	3
Physical hazard:	1			Extreme	4
				Gloves, Safety Glasses	B

Section 2 - Hazardous Ingredients

Hazardous Components	Cas #	% Wt	Exposure Limits (TWA)		
			ACGIH (TLV)	OSHA (PEL)	Other
Ethyl-2-Cyanoacrylate	7085-85-0	86-100	0.2ppm (TWA)	N/A	0.3ppm (STEL)

Section 3 - Physical Data

Form: Liquid
Color: Water White/Straw-Colored
Odor: Sharp, irritating
Boiling Point: >100°C
Vapor Pressure @25°C: <0.5mm Hg
Specific Gravity @ 25°C: 1.1
VOC content: <20g/L estimated (California SCAQMD Method 316B)
Solubility in Water: Immiscible in water
Flash Point: >81°C

Section 4 - Fire & Explosion Hazard Data

Flash Point:	150 - 200°F (>81°C) (method TCC)
Extinguishing Media:	Foam, dry chemical, water spray or CO2
Special Fire Fighting Procedures:	Wear self-contained breathing apparatus
Hazardous Products Formed by Fire or Thermal Decomp:	Irritating organic vapors may be formed
Unusual Fire or Explosion Hazards:	No applicable information found
Explosive Limits:	
(% by volume in air) Lower	Not available
(% by volume in air) Upper	Not available

Section 5 - Health Hazard Data

Label Precautionary Statements:	Irritant. Irritating to eyes, skin and respiratory system. Cyanoacrylate. Danger. Bonds skin and eyes in seconds.
Primary Route(s) of Entry:	None known
Toxicity:	Skin contact may cause burns Bonds skin rapidly Skin and eye irritant Estimated oral LD 50 more than 5,000 mg/kg Estimated dermal LD 50 more than 2,000 mg/kg
Symptoms of Exposure:	Vapor is irritating to eyes and breathing. Prolonged and repeated overexposure to vapors may lead to non-allergic asthma.
Medical conditions aggravated by exposure:	No applicable information found.

Ethyl Cyanoacrylate is not listed as a carcinogen in the US National Toxicology Program Annual report on carcinogens, or by the International Agency for Research on Cancer.

Target Organs and Other Health Effects:

		Carcinogens		
		NTP	IARC	OSHA
Ethyl Cyanoacrylate:	Allergen, irritant, respiratory	No	No	No
Poly (methyl methacrylate):	Irritant	No	N/A	No
Hydroquinone	ACGIH animal carcinogen, blood, Bone marrow, central nervous system, eye, immune system, irritant, liver, skin, mutagen, thyroid.	No	N/A	No

First Aid Measures and Personal Protection:

Ingestion:	Ingestion is not likely due to polymerization.
Inhalation:	Remove to fresh air. If symptoms persist, obtain medical attention.
Skin Contact:	Soak in warm soapy water.
Eye Contact:	Flush with water. Seek medical attention.

GC Electronics
1801 Morgan Street
Rockford, IL 61102
Phone: (815) 968-9661
Fax: (815) 968-9731
www.gcelectronics.com

Product Name: Super Glue
MSDS Number: 140
Revision Date: 12/30/09
Supersedes Date: 6/23/06

Personal Protection:

Eye: Chemical safety glasses or goggles
Skin: Polyethylene gloves and/or aprons. DO NOT use cotton/cloth-type gloves.
Respiration: Always use appropriate filter mask / respirator.
Ventilation: Positive draft exhaust ventilation should be provided to maintain vapor concentration levels below TLV.

Supplement:

Skin Adhesion: First immerse the bonded surface in warm soapy water. Peel or roll the surface apart with the aid of a blunt edge such as a pencil, spoon handle, etc. Do this gradually in a gentle fashion, with care not to be too forceful. Then remove the adhesive from the skin with soap and water. DO NOT try to pull surface apart with a direct opposing action.

Eyelid to Eyelid or Eyeball Adhesion:

In the event that eyelids are stuck together or bonded to the eyeball, wash thoroughly with warm water and apply a gauze patch. The eye will open without further action, typically in one to four days. There will be no residual damage. Do not try to open eyes by manipulation. Let the natural cleansing action of the eye take place.

Adhesive on the Eyeball:

Cyanoacrylate introduced into the eyes will attach itself to the eye protein and will disassociate from it over intermittent periods, generally covering several hours. This will cause periods of tearing until clearance is achieved. The adhesive residue will flush out of the eye normally in a matter of hours.

Mouth:

If lips are accidentally stuck together, apply lots of warm water to the lips and encourage maximum wetting and pressure from saliva inside the mouth. Peel or roll the lips apart. Do not try to pull the lips apart with a direct opposing action. It is almost impossible to swallow cyanoacrylate. The adhesive solidifies and adheres in the mouth. Saliva will lift the adhesive in 12 to 48 hours.

Burns:

Cyanoacrylates give off heat on solidification. In rare cases a large amount will increase in temperature enough to cause a burn. Should this occur treat using normal medical procedures.

Section 6 - Reactivity Data

Stability:	Stable
Incompatibility	Polymerized by contact with water, bases, amines
Hazardous Polymerization:	Will not occur
Conditions to Avoid:	Not available
Hazardous decomposition products:	No applicable information found.

Section 7 - Spill or Leak Procedures

If a spill or leak occurs, ventilate area of spill. Flood area with water to polymerize (cure) the material. Absorb with sand/earth and dispose to chemical waste bin. Dispose in accordance with pertinent national legislation.

Disposal: Incinerate following EPA and local regulations.
EPA Hazardous Waste Number: NH – Not a RCRA Hazardous Waste Material

Section 8 - Special Protection Information

Note: See Section 5 for emergency procedures and additional first aid information. (See Section 2 for exposure limit information.)
Eyes: Chemical safety glasses or goggles suitable for use with chemicals.
Skin: Coveralls, Nitrile/Polyethylene gloves and aprons. DO NOT use cotton or cloth materials.
Ventilation: Good general or local exhaust ventilation is required for ventilation.
Respiratory: Always use appropriate filter mask/respirator.

Section 9 – Special Precautions

Precautions to be taken in handling and storing: When using large volumes ensure that operational area is well ventilated. Store between 5-25°C; avoid strong light and heat sources. Incompatible with amine, bases, water. Avoid skin contact and inhalation of vapor.

Cyanoacrylates must be disposed of in accordance with all national and local regulations.

Section 10 - Regulatory Information

CA Proposition 65: No Prop 65 Chemicals known to be present
TCSA: All ingredients of this product are listed, or are exempt from listing on the TSCA inventory.
Canada DSL: All ingredients of this product are listed, or are exempt from listing on the Canada DSL.
DOT (49CFR 172)
Domestic Ground Transport
Proper Shipping Name : Unrestricted
Hazard Class: Not Regulated

GC Electronics

1801 Morgan Street
Rockford, IL 61102
Phone: (815) 968-9661
Fax: (815) 968-9731
www.gcelectronics.com

Product Name: Super Glue

MSDS Number: 140
Revision Date: 12/30/09
Supersedes Date: 6/23/06

IATA

Proper Shipping Name:	Unrestricted
Class or Division:	Unrestricted
UN or ID Number	None

Not considered hazardous for the purpose of transportation.

Disclaimer

GC Electronics believes that the information contained herein is accurate and reliable as of the date of this material safety data sheet, but no representation guarantee or warranty, express or implied, is made as to the accuracy, reliability, or completeness of the information. Persons receiving this information are encouraged to make their own determination as to the information's suitability and completeness for their particular application. NO INFORMATION CONTAINED HEREIN CONSTITUTES A PRODUCT WARRANTY OF ANY KIND, WHETHER EXPRESS OR IMPLIED; AND ALL IMPLIED WARRANTIES OF MERCHANT ABILITY AND OF FITNESS FOR A PARTICULAR PURPOSE ARE HEREBY DISCLAIMED BY GC ELECTRONICS.