Finished Product



Date Issued: 12/23/2002 **MSDS No:** 1667-A

Date Revised: 07/25/2012

Revision No: 9

Blue Shower II

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Blue Shower II **GENERAL USE:** Maintenance Cleaner **PRODUCT CODE:** 1667/CAN/EUR-8S, 18S

ACTIVE INGREDIENT(S): 3,3-Dichloro-1,1,1,2,2-pentafluoropropane (HCFC-225ca); 1,3-Dichloro-1,1,2,2,3-

pentafluoropropane (HCFC-225cb)

MANUFACTURER

Techspray, L.P. 1001 N.W. 1st Street P.O. Box 949 Amarillo, TX 79107

Emergency Contact: Chemtrec Emergency Phone: 1-800-858-4043 Service Number: 1-800-858-4043

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC CCN#21858 (US Transportation): (800) 424 - 9300 CANUTEC (Canadian Transportation): (613) 996 - 6666 Emergency Phone: (800) 858 - 4043

2. HAZARDS IDENTIFICATION

HAZARD DESIGNATION

"Xn" - Harmful

R20 - Harmful by inhalation.

R36/38 - Irritating to eyes and skin.

EMERGENCY OVERVIEW

PHYSICAL APPEARANCE: Transparent, colorless liquid.

IMMEDIATE CONCERNS: Warning! High concentrations of vapor can reduce oxygen available for breathing. Harmful if inhaled. May decompose on contact with flames or extremely hot metal surfaces to produce toxic and corrosive products.

POTENTIAL HEALTH EFFECTS

EYES: Avoid contact with eyes; may cause redness, irritation and conjunctivitis.

SKIN: Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

INGESTION: Ingestion of large amounts may produce abdominal pain, nausea and vomiting. Swallowing small amounts is not likely to produce harmful effects.

INHALATION: High concentrations in immediate area can displace oxygen and can cause dizziness, unconsciousness, and possibly death with longer exposure. Keep people away from such vapors without self-contained breathing apparatus.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Liquid splashed in the eye may cause redness, irritation and conjunctivitis.

SKIN: Prolonged exposure causes redness, pain, drying and cracking of the skin.

INGESTION: For large amounts; abdominal pain, nausea and vomiting.

INHALATION: High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches, paralysis and loss of consciousness).

Finished Product



Date Issued: 12/23/2002 **MSDS No:** 1667-A

Date Revised: 07/25/2012

Revision No: 9

Blue Shower II

ACUTE TOXICITY: Overexposure may cause dizziness and loss of concentration. At higher levels, CNS depression and cardiac arrhythmia may result.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS	EINECS
3,3-Dichloro-1,1,1,2,2-pentafluoropropane (HCFC-225ca)	60 - 70	422-56-0	2070169
1,3-Dichloro-1,1,2,2,3-pentafluoropropane (HCFC-225cb)	< 5	507-55-1	2080769
1,1,1,2-Tetrafluoroethane	15 - 25	811-97-2	212-337-0
Carbon dioxide	2 - 5	124-38-9	
Ethanol	7 - 15	64-17-5	200-578-6
Methanol	< 2	67-56-1	200-659-6

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

SKIN: Immediately flush skin with plenty of water. Remove clothing. Get medical attention immediately. Wash clothing separately before reuse.

INGESTION: If swallowed, gently wipe or rinse the inside of the mouth with water. DO NOT induce vomiting. Sips of water may be given if person is fully conscious. Never give anything by mouth to an unconscious or convulsing person. Immediately contact a poison control center, emergency room or physician as further treatment may be necessary.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

5. FIRE FIGHTING MEASURES

FLASHPOINT AND METHOD: None FLAMMABLE LIMITS: NA to NA

EXTINGUISHING MEDIA: Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

FIRE FIGHTING PROCEDURES: Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product decomposition.

FIRE FIGHTING EQUIPMENT: As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH approved or equivalent) and full protective gear.

HAZARDOUS DECOMPOSITION PRODUCTS: Toxic oxides of carbon and corrosive vapors of hydrogen chloride.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Contain spill with dike to prevent entry into sewers.

LARGE SPILL: If this material is released into a work area, evacuate the area immediately.

GENERAL PROCEDURES: Dike area to contain spill. Take precautions as necessary to prevent contamination of ground and surface waters. Recover spilled material on adsorbent, such as sawdust or vermiculite, and sweep

Finished Product



Date Issued: 12/23/2002 MSDS No: 1667-A

Date Revised: 07/25/2012

Revision No: 9

Blue Shower II

into closed containers for disposal. After all visible traces, including vapors, have been removed thoroughly wet vacuum the area. Do not flush to sewer. If area of spill is porous, remove as much contaminated earth, gravel, etc. as necessary and place in closed containers for disposal.

SPECIAL PROTECTIVE EQUIPMENT: Only personnel equipped with proper respiratory and skin/eye protection should be permitted in area. See Section 8 for details.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Use only in a well ventilated area.

HANDLING: Use with sufficient ventilation to keep employee exposure below recommended limits. Provide adequate ventilation for storage, handling and use, especially for enclosed or low spaces. Avoid contact of liquid with eyes and prolonged skin exposure. Do not allow product to contact open flame or electrical heating elements because dangerous decomposition products may form.

STORAGE: Store in a cool, well-ventilated area of low fire risk. Storage in subsurface locations should be avoided. If container temperature exceeds boiling point, cool the container before opening.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Finished Product



Date Issued: 12/23/2002 MSDS No: 1667-A Date Revised: 07/25/2012

Revision No: 9

Blue Shower II

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)							
	EXPOSURE LIMITS						
		OSHA PEL		ACGI	CGIH TLV SupplierOEI		erOEL
Chemical Name		ppm	mg/m³	ppm	mg/m³	ppm	mg/m³
3,3-Dichloro-1,1,1,2,2-pentafluoropropane	TWA	[1]	[1]	[1]	[1]	50* ppm ^[2]	[2]
(HCFC-225ca)	STEL	[1]	[1]	[1]	[1]		
3-Dictriol 0-1,1,2,2,3-perical autoropi opane	TWA	[1]	[1]	[1]	[1]	400* ppm ^[2]	[2]
(HCFC-225cb)	STEL	[1]	[1]	[1]	[1]		
1,1,1,2-Tetrafluoroethane	TWA	NE		NE		1,000 ppm ^[2]	[2]
Ethanol	TWA	1000 ppm	1900 mg/m3	1000 ppm	1880 mg/m3	NL	NL
	STEL	NL ppm	NL mg/m3	NL ppm	NL mg/m3	NL	NL
Methanol	TWA	S 200 ppm ^[3]	260 mg/m3 ^[3]	S 200 ppm	262 mg/m3	NL ppm	NL mg/m3
меналог	STEL	250 ppm	310 mg/m3	250 ppm	328 mg/m3	NL ppm	NL

OSHA TABLE COMMENTS:

- 1. NOT ESTABLISHED
- 2. * (AEL)=Acceptable Exposure Limit as established by the manufacture
- **3**. S = Skin

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

SKIN: The glove(s) listed below may provide protection against permeation. Gloves of other chemically resistant materials may not provide adequate protection. Viton, Solvex, Butyl, Buna, Neoprene.

RESPIRATORY: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

OTHER USE PRECAUTIONS: Emergency shower and eyewash facility should be in close proximity.

9. PHYSICAL AND CHEMICAL PROPERTIES

Finished Product



Date Issued: 12/23/2002 **MSDS No:** 1667-A

Date Revised: 07/25/2012

Revision No: 9

Blue Shower II

Chemical Name	Boiling Point (°C)	Freezing Point (°C)	Solubility in Water	Specific Gravity
1,1,1,2-Tetrafluoroethane	-26.4	-101	NEGLIGIBLE	1.21

ODOR: Faint ethereal odor

APPEARANCE: Clear, Colorless liquid **PERCENT VOLATILE:** 100 at 20°C (68°F)

VAPOR DENSITY: 7 (Air=1)

BOILING POINT: to 54°C (129°F) **FLASHPOINT AND METHOD:** None **SOLUBILITY IN WATER:** Insoluble

EVAPORATION RATE: > 1 (n-Butyl Acetate=1)

SPECIFIC GRAVITY: to 1.55 (water=1)

(**VOC**): 8.560 % by weight (EPA) **Notes:** 75% weight VOC (CARB)

COMMENTS: Product manufactured after 31 December 2007 conforms to California VOC requirements in Category

Electronic Cleaner with a cap of 75%

10. STABILITY AND REACTIVITY

STABILITY: Stable.

POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: Stable. However, may decompose if heated.

HAZARDOUS DECOMPOSITION PRODUCTS: When exposed to high temperatures or flames this product may

form hydrochloric and hydrofluoric acids - possibly carbonyl halides. **INCOMPATIBLE MATERIALS:** Oxidizing agents, alkalies and bases.

11. TOXICOLOGICAL INFORMATION

ACUTE

Chemical Name	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)	INHALATION LC ₅₀ (rat)
3,3-Dichloro-1,1,1,2,2-pentafluoropropane (HCFC-225ca)	> 5000 mg/kg	> 2000 mg/kg	37300 ppm
1,3-Dichloro-1,1,2,2,3-pentafluoropropane (HCFC-225cb)	> 5000 mg/kg	> 2000 mg/kg	36800 ppm
1,1,1,2-Tetrafluoroethane			> 500000 ppm
Methanol	6.2 to 12.98 mg/kg	16 g/kg	64000 ppm

EYES: Moderately to severely irritating

DERMAL LD₅₀: Mildly to moderately irritating.

ORAL LD₅₀: Slight to very low toxicity.

Finished Product



Date Issued: 12/23/2002 MSDS No: 1667-A Date Revised: 07/25/2012

Revision No: 9

Blue Shower II

INHALATION LC₅₀: Slight to very low toxicity.

CARCINOGENICITY

Chemical Name	NTP	IARC	OSHA
	Status	Status	Status
3,3-Dichloro-1,1,1,2,2-pentafluoropropane (HCFC-225ca)	NOT	NOT	NOT
	LISTED	LISTED	LISTED
1,3-Dichloro-1,1,2,2,3-pentafluoropropane (HCFC-225cb)	NOT	NOT	NOT
	LISTED	LISTED	LISTED
1,1,1,2-Tetrafluoroethane	NOT	NOT	NOT
	LISTED	LISTED	LISTED
Ethanol	NOT	NOT	NOT
	LISTED	LISTED	LISTED
Methanol	NOT	NOT	NOT
	LISTED	LISTED	LISTED

TERATOGENIC EFFECTS: Test results indicate this compound/mixture is not teratogenic.

GENERAL COMMENTS: Data from acute toxicity studies indicate that HCFC-225ca and HCFC-225cb have very low acute toxicity. Neither isomer causes eye irritation nor dermal toxicity in standardized tests; skin application of both isomers at high doses (2,000 mg/kg body weight) produces no adverse effects. Therefore, the dermal LD50s are greater than 2,000 mg/kg body weight. Oral administration of either isomer at high doses (5,000 mg/kg body weight) does not cause any mortality and the oral LD50s are greater than 5,000 mg/kg body weight. Both isomers also have very low acute inhalation toxicity as measured by the concentration that cause 50% mortality in experimental animals. In 28-day inhalation studies with rat, the activity and responsiveness of the animals was reduced at 5,000 ppm or greater for each isomer. Toxicity was otherwise confined to the liver; liver enlargement and induction of peroxisomes was seen following treatment with either of the isomers. HCFC-225ca was more potent than HCFC-225cb in eliciting these lever effects. In a 90-day study of HCFC-225ca/HCFC-225cb mixture (45/55%) with rat, toxic effects were observed in the liver; liver enlargement and induction of peroxisomes. In a 28-day study with marmoset, exposure to HCFC-225ca at 1,000 ppm caused effects on the liver, such as slight fat deposition associated with changes in serum biochemical parameters. In the same study, exposure to HCFC-225cb at 5,000 ppm caused somnolence during exposure and an increase of cytochrome P-450, indicative of an adaptive response to HCFC-225cb. However, no liver enlargement was seen and virtually no peroxisome induction was observed in either isomer.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: There is limited information available on the environmental fate and effects of this material. The primary environmental concern for release is the impact on aquatic and terrestrial species. Due care should be taken to avoid the accidental release of this material into the environment.

ECOTOXICOLOGICAL INFORMATION: Invertebrate toxicity: LC50 (30 min) Photobacterium phosphoreum = 1540 ppm Microtoxicity test.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Recover by distillation or remove to permitted waste disposal facility. Comply with Federal, State and Local regulations.

FOR LARGE SPILLS: Contaminated sawdust, vermiculite, or porous surfaces must be disposed of in a permitted

Finished Product



Date Issued: 12/23/2002 **MSDS No:** 1667-A

Date Revised: 07/25/2012

Revision No: 9

Blue Shower II

hazardous waste management facility. Recovered liquids may be reprocessed or incinerated or must be treated in a permitted hazardous waste management facility.

GENERAL COMMENTS: Dispose of in a manner consistent with federal, state, and local regulations.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: CONSUMER COMMODITY ORM-D

UN/NA NUMBER: N/A
PACKING GROUP: N/A
ROAD AND RAIL (ADR/RID)
KEMLER NUMBER: UN1950

HAZARD CLASS: 2.2 AIR (ICAO/IATA)

SHIPPING NAME: CONSUMER COMMODITY ID8000

UN/NA NUMBER: N/A
PACKING GROUP: N/A

NOTE: Domestic shipments only. When shipping International contact TechSpray shipping department.

VESSEL (IMO/IMDG)

SHIPPING NAME: AEROSOLS IN LIMITED QUANTITIES OF CLASS 2

NOTE: Page 2102

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: IMMEDIATE / DELAYED

EPCRA SECTION 313 SUPPLIER NOTIFICATION

Chemical Name	Wt.%	CAS		
3,3-Dichloro-1,1,1,2,2-pentafluoropropane (HCFC-225ca)	60 - 70	422-56-0		
1,3-Dichloro-1,1,2,2,3-pentafluoropropane (HCFC-225cb)	< 5	507-55-1		
Methanol	< 2	67-56-1		

TITLE III NOTES: Not listed as an Extremely Hazardous Substance.

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

CERCLA REGULATORY: Releases to air, land, or water which exceed the RQ must be reported to the National Response Center [(800)424-8802] and to your Local Emergency Planning Committee.

Chemical Name	Wt.%	CERCLA RQ
Methanol	< 2	5000 lbs.

Finished Product



Date Issued: 12/23/2002 **MSDS No:** 1667-A

Date Revised: 07/25/2012

Revision No: 9

Blue Shower II

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
3,3-Dichloro-1,1,1,2,2-pentafluoropropane (HCFC-225ca)	422-56-0
1,3-Dichloro-1,1,2,2,3-pentafluoropropane (HCFC-225cb)	507-55-1
1,1,1,2-Tetrafluoroethane	811-97-2
Ethanol	64-17-5
Methanol	67-56-1

TSCA REGULATORY: This product is listed on the TSCA Inventory.

CLEAN AIR ACT

Chemical Name	Wt.%	CAS
3,3-Dichloro-1,1,1,2,2-pentafluoropropane (HCFC-225ca)	60 - 70	422-56-0
1,1,1,2-Tetrafluoroethane	15 - 25	811-97-2

CALIFORNIA PROPOSITION 65: This product contains components (methanol, CAS# 67-56-1; nitromethane, CAS# 75-52-5) known to the State of California to cause cancer and/or be reproductive toxins.

CANADA

WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM): This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

WHMIS CLASS: Class A, Class D2B.

EUROPEAN COMMUNITY

EEC LABEL SYMBOL AND CLASSIFICATION



"Xn" - Harmful

R20 - Harmful by inhalation.

R36/38 - Irritating to eyes and skin.

GENERAL COMMENTS: Product manufactured after 31 December 2007 conforms to California VOC requirements in Category Electronic Cleaner with a cap of 75%

COMMENTS WARNING: Contains 1,1,1,2-tetrafluoroethane (HFC-134a), a greenhouse gas which may contribute to global warming.

16. OTHER INFORMATION

APPROVED BY: Pierce A. Pillon **TITLE:** Chemist

PREPARED BY: Steve Cook

REVISION SUMMARY: This MSDS replaces the 07/17/2012 MSDS.

Finished Product



Date Issued: 12/23/2002 MSDS No: 1667-A Date Revised: 07/25/2012

Revision No: 9

Blue Shower II

HMIS RATING HEALTH 2 FLAMMABILITY 1 PHYSICAL HAZARD 0 PERSONAL PROTECTION



DATA SOURCES: Code of Federal Regulations (CFR) The Sigma-Aldrich Library of Regulatory and Safety Data OSHA Hazard Communication Standard (29CFR1910.1200) Various Federal, State and Local Regulations

MANUFACTURER DISCLAIMER: To the best of our knowledge, the information contained herein is accurate. However, neither Tech Spray, L.P., or any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.