ITW CHEMTRONICS MSDS #0706

#### SECTION 1: CHEMICAL PRODUCT AND COMPANY INFORMATION

Company Address:

8125 Cobb Center Drive Kennesaw, GA 30152

Product Information: 800-TECH-401 Emergency: (Chemtrec) 800-424-9300 Customer Service: 800-645-5244 Revision Date: February 17, 2010

**Product Identification** 

CHEMASK W
 A CONTRACTOR OF THE CONTRACTOR

#### Product Code: CW1, CW5, CW8, CW1C, CW5C, CW8C

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS						
Product Ingredient Information	CAS#	Wt. % Range				
Deionized water	7732-18-5	35.0-40.0				
Acrylic polymer	mixture	10.0-30.0				
Magnesium aluminum silicate	12174-11-7	5.0-10.0				
Glycerin	56-81-5	1.0-5.0				
Isopropanol	67-63-0	1.0-5.0				
Methanol	67-56-1	1.0-5.0				
Titanium dioxide	13463-67-7	0.1-1.0				

# **SECTION 3: HAZARD IDENTIFICATION**

Emergency Overview: Viscous, opaque blue liquid with mild odor. This product is not flammable. Liquid will irritate eyes and skin under repeated or prolonged exposure.

Potential Health Effects:

Eyes: Liquid, aerosols and vapors of this product are irritating and can cause pain, tearing, reddening and swelling accompanied by a stinging sensation.

Skin: Contact causes skin irritation.

Ingestion: Harmful if swallowed. Irritating to mouth, throat and stomach. May cause vomiting.

Inhalation: Harmful if inhaled. High concentrations of vapors in immediate area can displace oxygen and can cause dizziness, unconsciousness, and even death with longer exposure. Keep people away from such vapors without self-contained breathing apparatus.

Pre-Existing Medical Conditions Aggravated by Exposure: None known

#### SECTION 4: FIRST AID MEASURES

Eyes: Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Have eyes examined and tested by medical personnel if irritation develops or persists.

<u>Skin</u>: Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persist. Wash clothing separately before reuse. <u>Ingestion</u>: If swallowed, induce vomiting immediately as directed by medical personnel. Keep head below knees to minimize chance of aspirating material into the lungs. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

#### SECTION 5: FIRE FIGHTING MEASURES

Flash Point: None to boiling (TCC)

<u>LEL/UEL</u>: Not established (% by volume in air)

Extinguishing Media: Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

Fire Fighting Instructions: As in any fire, wear self-contained breathing apparatus (pressure-demand, MSHA/NIOSH approved or equivalent) and full protective gear.

# SECTION 6: ACCIDENTAL RELEASE MEASURES

<u>Large Spills:</u> Shut off leak if possible and safe to do so. Wear self-contained breathing apparatus and appropriate personal protective equipment. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container for proper disposal. Do not flush to sewer. Avoid runoff into storm sewers and ditches which lead to waterways.(mist)

Small Spills: Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container for proper disposal.

# SECTION 7: HANDLING AND STORAGE

Avoid prolonged or repeated contact with eyes, skin, and clothing. Wash hands before eating. Use with adequate ventilation. Avoid breathing product vapor or mist. Do not reuse this container. Store in a cool dry place away from heat, sparks and flame. Keep container closed when not in use. Do not store in direct sunlight. **KEEP OUT OF REACH OF CHILDREN.** 

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines:				
CHEMICAL NAME	ACGIH TLV	OSHA PEL	ACGIH STEL	
Isopropanol	200 ppm	400 ppm	400 ppm	
Methanol	200 ppm	200 ppm	250 ppm	
Glycerin	10 mg/m (mist)	NA	NA	
Acrylic polymer	NΔ	NΔ	NΑ	

Work/Hygienic Practices: Good general ventilation should be sufficient to control airborne levels. Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product. If vapor concentration exceeds TLV, use NIOSH approved organic vapor cartridge respirator. Wear safety glasses with side shields (or goggles) and rubber or other chemically resistant gloves when handling this material.

NFPA and HMIS Codes:	NFPA	HMIS
Health	1	1
Flammability	0	0
Reactivity	0	0
Personal Protection	-	В

® W CHEMTRONICS

ITW CHEMTRONICS MSDS #0706

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

 Physical State:
 Opaque blue
 Solubility in Water:
 Dispersible

 Odor:
 Mild
 Specific Gravity:
 1.00 (Water = 1)

Vapor Pressure:12 mm Hg @ 20CEvaporation Rate: >1Vapor Density:<1 (Air=1)</td>(Butyl Alcohol= 1)

Boiling Point:: 200F (93C) (initial) Percent Volatile: 5.0% by weight

pH: 5.7-6.3 Melting Point: NA

# SECTION 10: STABILITY AND CHEMICAL PROPERTIES

Stability - This product is stable. Conditions to Avoid: Do not spray near open flames, red hot surfaces or other sources of ignition.

Incompatibility: Do not mix with powdered alkali and alkaline earth metals or strong oxidizing agents.

Products of Decomposition: Thermal decomposition may release carbon monoxide, carbon dioxide and incompletely burned hydrocarbons.

Hazardous Polymerization: Will not occur Conditions to Avoid: NA

SECTION 11: TOXICOLOGICAL INFORMATION

Ingestion: Ingestion:

 Isopropanol
 LC50/rats
 12,000ppm/8hrs
 Isopropanol
 LD50/rats
 5,800 mg/kg

 Methanol
 LC50/rats
 64,000ppm/4hrs
 Methanol
 LD50
 5,628 mg/kg

Skin: Eyes:

Isopropanol rabbit MLD Isopropanol rabbit MLD-MOD

Cancer Information: No ingredients listed as human carcinogens by NTP or IARC

Reproductive effects: none Teratogenic effects: none Mutagenic effects: none

### SECTION 12: ECOLOGICAL INFORMATION

Environmental Impact Information Avoid runoff into storm sewers and ditches which lead to waterways. Water runoff can cause environmental damage.

#### REPORTING

US regulations require reporting spills of this material that could reach any surface waters. The toll free number for the US Coast Guard National Response Center is: 1-800-424-8802

#### SECTION 13: DISPOSAL CONSIDERATIONS

Dispose of in accordance with all federal, state and local regulations. Water runoff can cause environmental damage.

# SECTION 14: TRANSPORTATION INFORMATION

Air: Cleaning Compound Not Regulated

Ground: Cleaning Compound Not Regulated

# SECTION 15: REGULATORY INFORMATION

SECTION 313 SUPPLIER NOTIFICATION

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372).

Chemical Name CAS# Wt. % Range

Methanol 67-56-1 1.0-5.0 This information should be included on all MSDSs copied and distributed for this material.

TOXIC SUBSTANCES CONTROL ACT (TSCA).

All ingredients of this product are listed on the TSCA Inventory.

WHMIS: Class D2B

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

### SECTION 16: OTHER INFORMATION

Normal ventilation for standard manufacturing practices is usually adequate. Local exhaust should be used when large amounts are released.

To the best of our knowledge, the information contained herein is accurate. However, all materials may present unknown hazards and should be used with caution. In particular, improper use of our products and their inappropriate combination with other products and substances may produce harmful results which cannot be anticipated. Final determination of the suitability of any material is the sole responsibility of the user. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that may exist.