

MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product number 092-002

Product name Fast Tack 92 Hi Temp Heavy Duty Trim Adhesive

Effective date 07-May-2009
Company information Sprayway, Inc. 1005 Westgate

Addison, IL 60101 United States

Company phone General Assistance 630-543-7600

Emergency telephone US 800-424-9300 **Emergency telephone outside US** 703-527-3887

Version # 05

Supersedes date 02-Jan-2009

2. Hazards Identification

Emergency overview FLAMMABLE

CONTENTS UNDER PRESSURE. Aerosol. Pressurized container may explode when

exposed to heat or flame.

Irritating to eyes. Prolonged exposure may cause chronic effects.

Potential health effects

Eyes Causes eye irritation.

Skin Prolonged or repeated contact can result in defatting and drying of the skin which may

result in skin irritation and dermatitis (rash).

Intentional misuse by concentrating and inhaling the product can be harmful or fatal.

Prolonged inhalation may be harmful.

Ingestion Exposure by ingestion of an aerosol is unlikely. Ingestion may cause gastrointestinal

irritation, nausea, vomiting and diarrhea. May cause delayed lung damage.

Target organs Central nervous system. Respiratory system.

Chronic effects May cause central nervous system disorder (e.g., narcosis involving a loss of

coordination, weakness, fatigue, mental confusion, and blurred vision) and/or damage.

May cause delayed lung damage.

3. Composition / Information on Ingredients

Components	CAS#	Percent
Methyl Acetate	79-20-9	15 - 20
Dimethyl Ether	115-10-6	15 - 20
Cyclohexane	110-82-7	10 - 15
Isobutane	75-28-5	10 - 15
Acetone	67-64-1	8 - 10
Pentane	109-66-0	5 - 8
Propane	74-98-6	3 - 5
Non-hazardous and other components below reportable levels		10 - 20

4. First Aid Measures

First aid procedures

Skin contact

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact

lenses, if present and easy to do. Get medical attention if irritation develops or persists. Immediately take off all contaminated clothing. Wash off with warm water and soap. Get

medical attention if irritation develops or persists.

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

trade_name MSDS US

Have victim rinse mouth thoroughly with water. Do not induce vomiting without medical advice. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

5. Fire Fighting Measures

Flammable properties

Containers may explode when heated. Vapor or gas may spread to distant ignition sources and flash back.

Extinguishing media

Suitable extinguishing media

Protection of firefighters

Specific hazards arising from the chemical

Protective equipment and precautions for firefighters

Water fog. Foam. Alcohol foam. Dry chemical. Carbon dioxide (CO2). Do not use water.

Fire may produce irritating, corrosive and/or toxic gases.

In the event of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Containers should be cooled with water to prevent vapor pressure build up. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

6. Accidental Release Measures

Methods for containment

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable.

Methods for cleaning up

Should not be released into the environment.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean contaminated surface thoroughly.

7. Handling and Storage

Handling

Pressurized container: Do not pierce or burn, even after use. Do not handle or store near an open flame, heat or other sources of ignition. Do not use if spray button is missing or defective. Use only with adequate ventilation. Do not get this material in contact with eyes. Do not get this material in contact with skin. Wear personal protective equipment. Avoid prolonged exposure.

Storage

Level 3 Aerosol.

Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Avoid exposure to long periods of sunlight. Keep in an area equipped with sprinklers. Keep out of the reach of children.

8. Exposure Controls / Personal Protection

Exposure limits

ACGIH

Components	CAS#	TWA	STEL	Ceiling
Methyl Acetate	79-20-9	200 ppm	250 ppm	Not established
Cyclohexane	110-82-7	100 ppm	Not established	Not established
Isobutane	75-28-5	1000 ppm	Not established	Not established
Acetone	67-64-1	500 ppm	750 ppm	Not established
Pentane	109-66-0	600 ppm	Not established	Not established
Propane	74-98-6	1000 ppm	Not established	Not established

trade_name MSDS US

OSHA

Components	CAS#	TWA	STEL	Ceiling
Methyl Acetate	79-20-9	200 ppm	Not established	Not established
Cyclohexane	110-82-7	300 ppm	Not established	Not established
Acetone	67-64-1	1000 ppm	Not established	Not established
Pentane	109-66-0	1000 ppm	Not established	Not established
Propane	74-98-6	1000 ppm	Not established	Not established

Personal protective equipment

Eye / face protection Wear chemical goggles.

Skin protection Wear appropriate chemical resistant gloves.

Respiratory protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

9. Physical & Chemical Properties

Appearance Compressed liquefied gas. **Boiling point** 68 °F (20 °C) estimated

Color Amber.

Flammability (HOC) 40.674 kJ/g estimated

Flash back No

Flash point -156 °F (-104.4 °C)

Form Aerosol.

Odor Solvent.
pH Not applicable

Physical state Liquid.

Pressure 50 - 60 psig @70°F

Solubility Partially

Sensitization

Reproductive effects Teratogenicity

Specific gravity 0.7428 estimated

10. Chemical Stability & Reactivity Information

Chemical stability Risk of ignition.

Conditions to avoid Heat, flames and sparks.

Incompatible materialsHazardous decomposition productsMay include oxides of oxides of carbon.

11. Toxicological Information

Acute effects Acute LD50: 7544 mg/kg estimated, Rat, Dermal

Acute LC50: 85 mg/l/4h estimated, Rat, Inhalation Not expected to be hazardous by OSHA criteria. Not expected to be hazardous by OSHA criteria. Not expected to be hazardous by OSHA criteria.

12. Ecological Information

Ecotoxicity LC50 28.64 mg/L estimated, Fish, 96.00 Hours,

EC50 5355 mg/L estimated, Daphnia, 48.00 Hours, IC50 555 mg/L estimated, Algae, 72.00 Hours,

13. Disposal Considerations

Waste codes D001: Waste Flammable material with a flash point <140 F

Disposal instructionsContents under pressure. Do not allow this material to drain into sewers/water supplies. If

discarded, this product is considered a RCRA ignitable waste, D001. Dispose in

accordance with all applicable regulations.

14. Transport Information

Department of Transportation (DOT) Requirements

Basic shipping requirements:

Proper shipping name Consumer commodity

Hazard class ORM-D Subsidiary hazard class None

Additional information:

Packaging exceptions156, 306Packaging non bulk156, 306Packaging bulkNone

IMDG

Basic shipping requirements:

Proper shipping name AEROSOLS

Hazard class2.1UN number1950

Additional information:

Packaging exceptionsLTD QTYItem5FLabels requiredNoneTransport Category2

IATA

Basic shipping requirements:

Proper shipping name Aerosols, flammable

Hazard class2.1UN number1950

Additional information:

Packaging exceptions LTD QTY
Labels required 2.1





15. Regulatory Information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

Cyclohexane 110-82-7 1.0 % de minimis concentration

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous Yes

chemical

CERCLA (Superfund) reportable quantity

Cyclohexane: 1000.0000 Acetone: 5000.0000

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

Section 302 extremely No

hazardous substance

Section 311 hazardous chemical Yes

trade_name Msps us

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of New and Existing Chemicals (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations

U.S. - Pennsylvania - RTK (Right to Know) List

Acetone	67-64-1	Environmental hazar
Cyclohexane	110-82-7	Environmental hazar
Dimethyl Ether	115-10-6	Present
Isobutane	75-28-5	Present
Methyl Acetate	79-20-9	Present
Pentane	109-66-0	Present
Propane	74-98-6	Present

16. Other Information

HMIS® ratings Health: 1*

Flammability: 4 Physical hazard: 0

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our

knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified

in the text.

MSDS sections updated Product and Company Identification: Product and Company Identification

Physical & Chemical Properties: Physical & Chemical Properties Transport Information: Product Shipping Name/Packing Group

trade_name MSDS US