# **Material Safety Data Sheet**





Revision Number: 003.1 Issue date: 10/12/2009

# 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: LOCTITE® 567™ PST® PIPE SEALANT IDH number: 234451

THREAD SEALANT

Product type:Anaerobic SealantItem number:56707Region:United States

Company address:Contact information:Henkel CorporationTelephone: 860.571.5100

One Henkel Way Emergency telephone: 860.571.5100 Rocky Hill, Connecticut 06067 Internet: www.henkelna.com

#### 2. HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW** 

HMIS:

Physical state:PasteHEALTH:\*2Color:WhiteFLAMMABILITY:1Odor:MildPHYSICAL HAZARD:1

Personal Protection: See MSDS Section 8

WARNING: CAUSES EYE IRRITATION.

MAY CAUSE ALLERGIC SKIN REACTION.

MAY CAUSE RESPIRATORY TRACT IRRITATION.

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects

**Inhalation:** May cause respiratory tract irritation.

**Skin contact:** May cause skin irritation. May cause allergic skin reaction.

**Eye contact:** Contact with eyes will cause irritation. **Ingestion:** Not expected to be harmful by ingestion.

Existing conditions aggravated by

exposure:

IDH number: 234451

Eye, skin, and respiratory disorders.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR

1910.1200).

See Section 11 for additional toxicological information.

# 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%	
Bisphenol A fumarate resin	39382-25-7	30 - 60	
Polyglycol dimethacrylate	25852-47-5	10 - 30	
Polyglycol laurate	9004-81-3	10 - 30	
Polyethylene glycol monococoate	61791-29-5	10 - 30	
Titanium dioxide	13463-67-7	1 - 5	
Silica, amorphous, fumed, crystal-free	112945-52-5	1 - 5	
Saccharin	81-07-2	1 - 5	
Epichlorohydrin-4,4'-isopropylidene diphenol resin	25068-38-6	1 - 5	
Ethylene glycol	107-21-1	0.1 - 1	

## 4. FIRST AID MEASURES

Inhalation: Move to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. If symptoms develop and persist, get medical attention.

Skin contact: Remove contaminated clothing and footwear. Wash with soap and water.

Wash clothing before reuse. If symptoms develop and persist, get medical

attention.

Eye contact: Flush with copious amounts of water, preferably, lukewarm water for at least

15 minutes, holding eyelids open all the time. Get medical attention.

**Ingestion:** Do not induce vomiting. Keep individual calm. Get medical attention.

#### 5. FIRE FIGHTING MEASURES

Flash point: > 93.3 °C (> 199.94 °F)

Autoignition temperature:

Flammable/Explosive limits - lower:

Not available
Flammable/Explosive limits - upper:

Not available

**Extinguishing media:** Foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

Unusual fire or explosion hazards: None

IDH number: 234451

Hazardous combustion products: Oxides of carbon. Oxides of nitrogen. Oxides of sulfur. Toxic fluorine

compounds. Irritating organic vapours.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Do not allow product to enter sewer or waterways.

Clean-up methods: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder,

universal binder, sawdust). Store in a partly filled, closed container until

disposal.

## 7. HANDLING AND STORAGE

Handling: Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist.

Wash thoroughly after handling.

**Storage:** For safe storage, store at or below 38 °C (100.4 °F)

Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Bisphenol A fumarate resin	None	None	None	None
Polyglycol dimethacrylate	None	None	None	None
Polyglycol laurate	None	None	None	None
Polyethylene glycol monococoate	None	None	None	None
Titanium dioxide	10 mg/m3 TWA	15 mg/m3 TWA Total dust.	None	None
Silica, amorphous, fumed, crystal-free	10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction.	20 MPPCF TWA 0.8 mg/m3 TWA	None	None
Saccharin	None	None	None	None
Epichlorohydrin-4,4'-isopropylidene diphenol resin	None	None	None	None
Ethylene glycol	100 mg/m3 Ceiling Aerosol.	None	None	None

Engineering controls: No specific ventilation requirements noted, but forced ventilation may still be

required if concentrations exceed occupational exposure limits.

Respiratory protection: Use a NIOSH approved supplied air respirator with an organic cartridge if the

potential to exceed established exposure limits exists.

**Eye/face protection:** Safety goggles or safety glasses with side shields.

Skin protection: Neoprene, Butyl-rubber, or nitrile-rubber gloves. Use impermeable gloves and

protective clothing as necessary to prevent skin contact.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:PasteColor:WhiteOdor:MildOdor threshold:Not availablepH:Not applicable

 Vapor pressure:
 < 5 mm hg (27 °C (80.6 °F))</td>

 Boiling point/range:
 > 300 °F (> 148.9 °C) none

Melting point/ range:

Specific gravity:

Vapor density:

Not available
1.14

Not available

Flash point: > 93.3 °C (> 199.94 °F)

Flammable/Explosive limits - lower:

Flammable/Explosive limits - upper:

Autoignition temperature:

Evaporation rate:

Solubility in water:

Partition coefficient (n-octanol/water):

VOC content:

Not available

Not available

Slight

Not available

0.13 %; 1.38 g/l

## 10. STABILITY AND REACTIVITY

Stability: Stable

IDH number: 234451

Hazardous reactions: Will not occur.

Hazardous decomposition products: Oxides of nitrogen. Oxides of carbon. Oxides of sulfur. Toxic fluorine

compounds. Phenolics. Irritating organic vapours.

Incompatible materials: Free radical initiators. Amines. Aldehydes. Alkalis. Copper Aluminum. Rust.

Bases. Acids. Strong oxidizing agents. Peroxides. Iron. Reducing agents.

Zinc.

Conditions to avoid: Heat, flames, sparks and other sources of ignition. See "Handling and

Storage" (Section 7) and "Incompatibility" (Section 10). Exposure to sunlight.

## 11. TOXICOLOGICAL INFORMATION

Acute oral product toxicity: LD50 (rat) > 10,000 mg/kg

Acute dermal product toxicity: LD50 (rabbit) > 2,000 mg/kg

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Bisphenol A fumarate resin	No	No	No
Polyglycol dimethacrylate	No	No	No
Polyglycol laurate	No	No	No
Polyethylene glycol monococoate	No	No	No
Titanium dioxide	No	Group 2B	No
Silica, amorphous, fumed, crystal-free	No	No	No
Saccharin	No	No	No
Epichlorohydrin-4,4'-isopropylidene diphenol resin	No	No	No
Ethylene glycol	No	No	No

Hazardous components	Health Effects/Target Organs		
Bisphenol A fumarate resin	Irritant, Allergen		
Polyglycol dimethacrylate	Irritant, Allergen		
Polyglycol laurate	Allergen, Irritant		
Polyethylene glycol monococoate	No Target Organs		
Titanium dioxide	Irritant, Respiratory, Some evidence of carcinogenicity		
Silica, amorphous, fumed, crystal-free	Nuisance dust		
Saccharin	No Target Organs		
Epichlorohydrin-4,4'-isopropylidene diphenol resin	Allergen, Irritant		
Ethylene glycol	Blood, Bone Marrow, Central nervous system, Developmental, Eyes, Irritani Kidney, Liver, Metabolic		

## 12. ECOLOGICAL INFORMATION

Ecological information: Not available

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Not a RCRA hazardous waste.

## 14. TRANSPORT INFORMATION

The shipping classifications in this sections are for non-bulk packaging only (unless otherwise specified). Shipping classification may be different for bulk packaging.

## U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:
Hazard class or division:
Identification number:
Packing group:
Not regulated
None
None
None

# International Air Transportation (ICAO/IATA)

IDH number: 234451

Proper shipping name:Not regulatedHazard class or division:NoneIdentification number:NonePacking group:None

#### Water Transportation (IMO/IMDG)

Proper shipping name:
Hazard class or division:
Identification number:
Packing group:

Not regulated
None
None

## 15. REGULATORY INFORMATION

#### **United States Regulatory Information**

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12(b) Export Notification: None above reporting de minimus

CERCLA/SARA Section 302 EHS:
CERCLA/SARA Section 311/312:
CERCLA/SARA 313:

None above reporting de minimus
Immediate Health, Delayed Health
None above reporting de minimus

**California Proposition 65:** This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

Canada Regulatory Information

WHMIS hazard class:

IDH number: 234451

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List. D.2.A, D.2.B

## 16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format

Prepared by: Kyra Kozak Woods, Manager, Regulatory Affairs

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.