



TECHNICAL CHARACTERISTICS

MATERIAL

>Basic: PC UL HB

MOUNTING INSTRUCTION

>For reflow soldering only to be fitted after the soldering process

PACKAGING INFORMATION

>Tray

P/N	Laser carving sign	Base color
714 401 001		black
714 401 002		black
714 401 003		black
714 409 0100	no	transparent

Scale - 2:1

This electronic component is designed and developed with the intention for use in general electronics equipments.

Before incorporating the components into any equipments in the field such as aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. where higher safety and reliability are especially required or if there is possibility of direct damage or injury to human body, Wurth Elektronik must be asked for a written approval.

In addition, even electronic component in general electronic equipments, when used in electrical circuits that require high safety, reliability functions or performance, the sufficient reliability evaluation-check for the safety must be performed before by the user before usage.

Projection						GENERAL TOLERANCE		Basic material			
						.x = +/- 0,2 .xx = +/- 0,15					
						Date		Name		DESCRIPTION	
						Drawn		12-10-15		Jelisarow	
						Checked				SwCaps	
										Caps 12x12mm illuminated tact switch WS-TLT	
								Scale		2:1	
								Position			
								Drawing.- No.		714401xxx	
										SIZE	
										A4	
REV	FILE	DATE	BY	EDV NO	714401xxx.dft						
											System: Solid Edge ST4

