

## General Information

<b>Extended Product Type:</b>	DB25/25A
<b>Product ID:</b>	1SAZ201108R0001
<b>EAN:</b>	4013614237737
<b>Catalog Description:</b>	DB25/25A Single Mounting Kit
<b>Long Description:</b>	DB25/25A Single mounting kit for TA25DU

## Categories

Products » Low Voltage Products and Systems » Control Products »  
Contactors » Thermal Overload Relays Accessories

## Ordering

<b>EAN:</b>	4013614237737
<b>Minimum Order Quantity:</b>	1 piece
<b>Customs Tariff Number:</b>	85389099



## Dimensions

<b>Product Net Width:</b>	44.0 mm
<b>Product Net Height:</b>	70.5 mm
<b>Product Net Depth:</b>	85.8 mm
<b>Product Net Weight:</b>	0.055 kg

## Container Information

<b>Package Level 1 Units:</b>	10 piece
<b>Package Level 1 Width:</b>	238.0 mm
<b>Package Level 1 Height:</b>	140.0 mm
<b>Package Level 1 Length:</b>	82.0 mm
<b>Package Level 1 Gross Weight:</b>	0.655 kg
<b>Package Level 1 EAN:</b>	4013614442117

## Technical

<b>Rated Operational Voltage:</b>	Main Circuit 690 V AC
<b>Rated Operational Current AC-3 (I<sub>e</sub>):</b>	25 A
<b>Rated Frequency (f):</b>	Main Circuit 50 Hz Main Circuit 60 Hz
<b>Rated Impulse Withstand Voltage (U<sub>imp</sub>):</b>	Main Circuit 6 kV
<b>Rated Insulation Voltage (U<sub>i</sub>):</b>	690 V
<b>Number of Poles:</b>	3
<b>Pollution Degree:</b>	3
<b>Suitable For:</b>	TA25DU
<b>Standards:</b>	UL 60947-1 UL 60947-4-1

## Environmental

<b>Ambient Air Temperature:</b>	Operation -25 ... +55 °C Storage -40 ... +70 °C
---------------------------------	--

## Technical UL/CSA

---

**Maximum Operating Voltage** Main Circuit 600 V AC  
**UL/CSA:**  
**Ampere Rating UL/CSA:** 25 A

---

## Certificates and Declarations (Document Number)

---

**ABS Certificate:** No Certificate Needed  
**cUL Certificate:** cUL\_E48139  
**Declaration of Conformity - CE:** 1SAD938508-0043  
**DNV Certificate:** No Certificate Needed  
**GL Certificate:** No Certificate Needed  
**GOST Certificate:** 1SAA941000-2704  
**LR Certificate:** No Certificate Needed  
**RINA Certificate:** No Certificate Needed  
**UL Certificate:** UL\_E48139

---

## Classifications

---

**Object Classification Code:** Q  
**E-nummer:** 3229000  
**ETIM 4.0:** EC002498 - Accessories for low-voltage switch technology  
**ETIM 5.0:** EC002498 - Accessories for low-voltage switch technology  
**UNSPSC:** 39120000

---