Inductive Series M5 Short Housing






Features:

- · Inductive sensor, style: cylinder shape, diameter: 5mm
- DC 3-wire (10-30V DC)
- Connection mode: 3 wire
- Mounting distance: shielded (1mm) or unshielded (2mm)
- · With LED operation indicate lamp, easily identifiable
- · Brass chrome plated, proof of oil, water acid, alkaline
- Standard sensing object: iferrous metals
- · Protection rate: IP67, water resistant
- Over-current protection
- Widely applied in measuring, Counting, RPM measuring in mechanism, chemical, paper manufacture light industry, etc.

Technical Specifications:

Property Project	Specific Parameter			
Mounting Distance	1mm shielded / 2mm unshielded			
Sensing Distance	Shielded (0-0.8mm) / -			
Power Supply	DC 10-30V			
Frequency	≤ 600Hz			
Current Output	≤ 100mA			
Ambient Temperature	-20°C to +70°C			
Protection	Over-Current / Against Polarity			
IP Rating	IP67			

Electrical Connection Drawing:




www.element14.com www.farnell.com www.newark.com






Picture of Product Mix:



Dimensions : Millimetres

Part Number Explanation:



Part Number Table

Description	Output Type	Mounting Dis- tance	Current Output	Power Supply	Connector Model	Part Number
M5 Short Housing - Inductive Series	NPN NO	1mm, Shielded	≤ 100mA	DC 10-30V	3 Wire	MCPIN-T5S-001
		2mm, Unshielded				MCPIN-T5S-002
	PNP NO	1mm, Shielded				MCPIP-T5S-001
		2mm, Unshielded				MCPIP-T5S-002

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com www.farnell.com www.newark.com

