TECHNICAL DATA

Version 9

AT293 Premier Closure Plate Tape

General Description

A polythene extruded gloss cloth tape coated with Surefire® thermosetting adhesive.

- PRS10 approved
- Unique Surefire® thermosetting adhesive •
- Very high tack •
- Good high and low temperature resistance
- Strong •
- Can be written on •
- Excellent conformability to awkward shapes
- Good abrasion resistance
- Non-corrosive adhesive
- Water resistant finish
- Easy tear

Specification

*Meets British Gas specification PRS10 issue 2

Technical Details

Typical Values

Thickness	0.28mm
Breaking Load	75N/cm
Elongation	30%
Adhesion Steel	4.5 N/cm
Self	3.2 N/cm
Aluminium	4.4 N/cm
RoHS compliant	Yes
Service Temperature	-50°C to +110°C
Application Temperature	+5°C to +45°C
Storage Temperature	+12°C to +25°C



NOTE

NOTE Except where indicated otherwise, the figures stated are average values and should not be regarded as MAXIMUM or MINIMUM values for specification purposes. The Company reserves the right to improve products and any change in specification will result in a re-issue of the relevant 'Technical Data Sheet'. Customers should satisfy themselves that the tape is suitable for their requirements but the sufficient of the requirements of the requirements of the requirement of the require whether after such modifications or otherwise. Please check that you have the latest issue of the 'Technical Data Sheet'. All slitting and length tolerances are to British Standards. Before use the customer is advised to consult the Health & Safety Data Sheet produced by the company for this product, which is available on request.

STORAGE

Tapes stored below the minimum recommended temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.



AFERA

Association des Fabricants Européens de Rubans Auto-Adhésifs.

*Standard charge for certificate: £25.00.

Adding more to adhesive tape

Advance Tapes International Limited Westmoreland Avenue Thurmaston Leicester LE4 8PH England

Tel. +44 (0)116 251 0191 Fax. +44 (0)116 265 2046 contact@advancetapes.com



005026

www.advancetapes.com