

DIP Switches

Half Pitch



RoHS
Compliant



Features

- Low profile 2.2mm height
- Gold contact for high reliability
- Top tape type for washing process


Application:

Industrial Control
Automatic machines control
NB, electronic devices

Specifications:

| | |
|-----------------------|----------------------|
| Contact Rating | : 25mA, 24V DC |
| Contact Resistance | : 100mΩ max. Initial |
| Insulation Resistance | : 100MΩ min. 500V DC |
| Dielectric Strength | : 300V AC/1 minute |
| Operating Force | : 500gf |
| Travel | : 0.8mm |
| Operating Life | : 1,000 Cycles |
| Operating Temp. | : -40°C to +85°C |
| Storage Temp. | : -40°C to +85°C |

Diagram:



| Prod. No. | No. of Pos | Dim A |
|-----------|------------|-------|
| MCDHA-08 | 8 | 11.29 |

Dimensions : Millimetres

www.element14.com
www.farnell.com
www.newark.com




DIP Switches

Half Pitch



Circuit:



Part Number Table

| Description | Part Number |
|----------------------------|-------------|
| Switch, 8 Way, SPST, Flush | MCDHA-08TQR |

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com
www.farnell.com
www.newark.com

