

8413 Multi-Conductor - Two-Conductor, Low-Impedance Cable

For more Information
please call

1-800-Belden1



General Description:

24 AWG stranded (45x40) TC alloy conductors, EPDM rubber insulation, conductive textile wrap (100% coverage), TC braid shield (60% coverage), cotton spiral, EPDM jacket.

Physical Characteristics (Overall)

Conductor

AWG:

# Conductors	AWG	Stranding	Conductor Material	Dia. (mm)
2	24	45x40	Tinned Copper Alloy	0.6096

Total Number of Conductors: 2

Insulation

Insulation Material:

Insulation Material	Dia. (mm)
EPDM - Ethylene Propylene Diene Monomer Rubber	1.651

Outer Shield

Outer Shield Material:

Layer #	Type	Outer Shield Material	Coverage (%)
1	Tape	Conductive Textile	100.000
2	Braid	TC - Tinned Copper	60.000
3	Spiral Serve	Cotton	

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
EPDM - Ethylene Propylene Diene Monomer Rubber

Overall Cable

Overall Cabling Color Code Chart:

Number	Color
1	White
2	Black

Overall Nominal Diameter: 5.055 mm

Mechanical Characteristics (Overall)

Operating Temperature Range: -40°C To +90°C

Non-UL Temperature Rating: 90°C

Bulk Cable Weight: 37.205 Kg/Km

Max. Recommended Pulling Tension: 213.514 N

Min. Bend Radius/Minor Axis: 50.800 mm

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

EU CE Mark: Yes

EU Directive 2002/95/EC (RoHS): No

Plenum/Non-Plenum

Plenum (Y/N): No

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

METRIC MEASUREMENT VERSION

8413 Multi-Conductor - Two-Conductor, Low-Impedance Cable

Impedance (Ohm)

55

Nom. Inductance:

Inductance (µH/m)

0.62339

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/m)

98.43

Nom. Capacitance Cond. to Other Conductor & Shield:

Capacitance (pF/m)

180.455

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)

94.1647

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km)

37.3378

Max. Operating Voltage - Non-UL:

Voltage

300 V RMS

Max. Recommended Current:

Current

2.2 Amps per conductor @ 25°C

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
8413 010U500	152 MT	6.350 KG	BLACK		2 #24 EPDM SHLD EPDM
8413 010100	30 MT	1.452 KG	BLACK		2#24 EPDM SHLD EPDM
8413 010500	152 MT	6.124 KG	BLACK		2 #24 EPDM SH EPDM

Revision Number: 2 Revision Date: 08-29-2012

© 2013 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.