

## 6200UE Multi-Conductor - Commercial Audio Systems - 2 Conductors Cabled



For more Information  
please call

1-800-Belden1



### General Description:

Security & Commercial Audio Cable, Plenum-CMP 2-16 AWG stranded bare copper conductors with Flamarrest® insulation, Flamarrest® jacket with ripcord

### Usage (Overall)

**Suitable Applications:** Intercom/PA Systems, Sound/Audio Systems

### Physical Characteristics (Overall)

#### Conductor

**AWG:**

# Conductors	AWG	Stranding	Conductor Material
2	16	19x29	BC - Bare Copper

**Total Number of Conductors:** 2

#### Insulation

**Insulation Material:**

Insulation Trade Name	Insulation Material	Wall Thickness (mm)
Flamarrest®	LS PVC - Low Smoke Polyvinyl Chloride	0.203

#### Outer Shield

**Outer Shield Material:**

Outer Shield Material
Unshielded

#### Outer Jacket

**Outer Jacket Material:**

Outer Jacket Trade Name	Outer Jacket Material	Nom. Wall Thickness (mm)
Flamarrest®	LS PVC - Low Smoke Polyvinyl Chloride	0.381

**Outer Jacket Ripcord:** Yes

#### Overall Cable

**Overall Cabling Lay Length & Direction:**

Length (mm)	Direction	Twists (twist/m)
76.200	Left Hand	13.124

**Overall Cabling Color Code Chart:**

Number	Color
1	Black
2	Red

**Overall Nominal Diameter:** 4.470 mm

### Mechanical Characteristics (Overall)

**Operating Temperature Range:** 0°C To +75°C

**UL Temperature Rating:** 75°C

**Bulk Cable Weight:** 35.717 Kg/Km

**Max. Recommended Pulling Tension:** 270.451 N

**Min. Bend Radius/Minor Axis:** 44.450 mm

## 6200UE Multi-Conductor - Commercial Audio Systems - 2 Conductors Cabled

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

NEC/(UL) Specification:	CMP
NEC Articles:	800
CEC/C(UL) Specification:	CMP
EU Directive 2011/65/EU (ROHS II):	Yes
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

#### Flame Test

UL Flame Test:	NFPA 262
CSA Flame Test:	FT6

#### Suitability

Suitability - Indoor:	Yes
-----------------------	-----

#### Plenum/Non-Plenum

Non-Plenum Number:	5200UE
--------------------	--------

### Electrical Characteristics (Overall)

#### Nom. Inductance:

Inductance (µH/m)
0.476

#### Nom. Capacitance Conductor to Conductor:

Capacitance (pF/m)
119.757

#### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)
12.4678

#### Max. Operating Voltage - UL:

Voltage
300 V RMS

#### Max. Recommended Current:

Description	Current
10C Temperature Rise	6.25 Amps per conductor @ 25°C ambient

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
6200UE 0041000	305 MT	11.340 KG	YELLOW		2 #16 FLRST FLRST
6200UE 0071000	305 MT	11.340 KG	VIOLET		2 #16 FLRST FLRST
6200UE 008U1000	305 MT	10.886 KG	GRAY		2 #16 FLRST FLRST
6200UE 009U1000	305 MT	10.886 KG	WHITE		2 #16 FLRST FLRST
6200UE 009U250	76 MT	3.175 KG	WHITE		2 #16 FLRST FLRST
6200UE 009U500	152 MT	5.897 KG	WHITE		2 #16 FLRST FLRST
6200UE 010U1000	305 MT	10.886 KG	BLACK		2 #16 FLRST FLRST

## METRIC MEASUREMENT VERSION

### 6200UE Multi-Conductor - Commercial Audio Systems - 2 Conductors Cabled

6200UE 010U250	76 MT	3.175 KG	BLACK		2 #16 FLRST FLRST
6200UE 010U500	152 MT	5.897 KG	BLACK		2 #16 FLRST FLRST
6200UE 0101000	305 MT	11.340 KG	BLACK		2 #16 FLRST FLRST
6200UE 877U1000	305 MT	10.886 KG	NATURAL		2 #16 FLRST FLRST
6200UE 877U250	76 MT	3.175 KG	NATURAL		2 #16 FLRST FLRST
6200UE 8771000	305 MT	11.340 KG	NATURAL	C	2 #16 FLRST FLRST
6200UE 877500	152 MT	5.670 KG	NATURAL		2 #16 FLRST FLRST

**Notes:**

C = CRATE REEL PUT-UP.

Revision Number: 2    Revision Date: 08-08-2013

© 2013 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.