Electronic and General Purpose Cleaning

Technical Data Sheet





SSS Screen and Stencil Solvent

SSS is a non-flammable cleaning solvent designed for the removal of solder pastes and adhesives. SSS is water rinseable and suitable for use in automated stencil cleaning equipment.

- Removes solder and adhesive residues; ideal for cleaning stencils and related equipment
- Available in bulk and trigger spray bottle; suitable for manual and automated application
- Non-flammable solvent blend; eliminates the use of flammable materials
- Non-foaming product; can be used in spray applications

Approvals	RoHS-2 Compliant (2011/65/EU):	Yes
Typical Properties	Boiling Point (°C) Flash Point	>100 61
	Density (g/ml)	1.025

<u>Description</u>	<u>Packaging</u>	Order Code	Shelf Life
Screen and Stencil Solvent	500ml Trigger Spray	SSS500ML	72 Months
	5 Litre	SSS05L	72 Months
	25 Litre	SSS25L	72 Months

Directions for Use

SSS is classified as non-flammable, hence flame proof equipment is not required. The solution is highly effective at ambient temperatures thus keeping running costs to a minimum. If desired, SSS may be heated to 35-40°C with the appropriate equipment; no extraction is required under normal conditions.

SSS is non-foaming and surfactant free which means that there is minimal re-deposition of solder particles onto stencils and screens. SSS maintains a high load of excess paste in suspension to enable a good level of filtration. This results in clean stencils and screens without excess deposits of solder particles on the base of the cleaning equipment, reducing down time and cost.

A short cleaning cycle of three minutes for light deposits and five minutes for heavy, aged deposits makes this material suitable for a high speed production environment.

Revision 1: Oct 2013

Copyright Electrolube 2013

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification.

Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

Ashby Park, Coalfield Way, Ashby de la Zouch, Leicestershire LE65 1JR T +44 (0)1530 419 600 F +44 (0)1530 416 640 BS EN ISO 9001:2008 Certificate No. FM 32082