

SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 2.1

Revision Date: 02.12.2011

Superseded date: 05.07.2011

DOW CORNING(R) SE 9187 L CLEAR**1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY**

1.1 Product name	:	DOW CORNING(R) SE 9187 L CLEAR	
1.2 Identified uses	:	Coatings Adhesive, binding agents	
Uses advised against	:	None known.	
1.3 Company	:	Dow Corning Europe S.A. rue Jules Bordet - Parc Industriel - Zone C B-7180 Seneffe Belgium	
E-mail address (Safety Data Sheet)	:	sdseu@dowcorning.com	
Customer Service	:	English Deutsch Français Italiano Español	Tel: +49 611237507 Tel: +49 611237500 Tel: +32 64511149 Tel: +32 64511170 Tel: +32 64511163
			Fax: +32 64888683
1.4 Emergency Phone Number	:	Dow Corning (Barry U.K. 24h) Dow Corning (Wiesbaden 24h) Dow Corning (Seneffe 24h)	Tel: +44 1446732350 Tel: +49 61122158 Tel: +32 64 888240

2. HAZARDS IDENTIFICATION**2.1 Classification of the substance or mixture**

According to EU Directives 67/548/EEC or 1999/45/EC:

R43 May cause sensitization by skin contact.

2.2 Label elements**Labelling according to EEC Directive**

Contains	:	Trimethoxy(methyl)silane
Symbols	:	Xi Irritant.
R-phrases	:	R43 May cause sensitization by skin contact.
S-phrases	:	S23(S) Do not breathe spray. S24 Avoid contact with skin. S37 Wear suitable gloves. S51 Use only in well-ventilated areas.

SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 2.1

Revision Date: 02.12.2011

Superseded date: 05.07.2011

DOW CORNING(R) SE 9187 L CLEAR

2.3 Other hazards

Vapours may form explosive mixtures with air.

3. COMPOSITION / INFORMATION ON INGREDIENTS**Chemical characterization:** Silicone Sealant**According to EU Directives 67/548/EEC or 1999/45/EC:**

Name	CAS-No.	EINECS/ ELINCS No.	REACH Registration Number	Conc. (% w/w)	Classification
Trimethylated silica	68909-20-6	272-697-1	-	4.0	R66
Trimethoxy(methyl)silane	1185-55-3	214-685-0	01-21195174 36-40	2.0	R43 F R11

According to Regulation (EC) No. 1272/2008:

Name	CAS-No.	EINECS/ ELINCS No.	REACH Registration Number	Conc. (% w/w)	Classification
Trimethylated silica	68909-20-6	272-697-1	-	4.0	Substance with a Community workplace exposure limit
Trimethoxy(methyl)silane	1185-55-3	214-685-0	01-21195174 36-40	2.0	Flammable liquid: Category 2 - H225 Skin sensitization: Category 1 - H317

For the full text of the R-phrases mentioned in this Section, see Section 16.

For the full text of the H-Statements mentioned in this Section, see Section 16.

CLP classifications are based on all current available data including from known international organizations. These classifications are subject to revision as more information becomes available.

4. FIRST AID MEASURES**4.1 Description of First Aid Measures:**

- On contact with eyes** : Flush with water.
- On skin contact** : Flush with water. Wipe off. Obtain medical attention.
- If inhaled** : Remove to fresh air.
- On ingestion** : Obtain medical attention.

- 4.2 Most important symptoms/effects, acute and delayed** : May cause sensitization by skin contact.

SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 2.1
Revision Date: 02.12.2011
Superseded date: 05.07.2011**DOW CORNING(R) SE 9187 L CLEAR****5. FIRE-FIGHTING MEASURES**

- 5.1 Suitable extinguishing media** : On large fires use dry chemical, foam or water spray (fog). On small fires use carbon dioxide (CO₂), dry chemical or water spray. Water can be used to cool fire exposed containers.
- Unsuitable extinguishing media** : None known.
- 5.2 Hazards during fire fighting** : Vapours may form explosive mixtures with air.
- Hazardous Combustion Products** : Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Silica. Carbon oxides and traces of incompletely burned carbon compounds. Formaldehyde. Nitrogen products.
- 5.3 Special protective equipment/procedures** : A self-contained respirator and protective clothing should be worn. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.

6. ACCIDENTAL RELEASE MEASURES

- 6.1 Personal precautions, protective equipment and emergency procedures** : Wear proper protective equipment.
- 6.2 Environmental precautions** : Prevent from spreading or entering into drains, ditches or rivers by using sand, earth or other appropriate barriers.
- 6.3 Methods and materials for containment and cleaning up** : Determine the need to evacuate or isolate the area according to your local emergency plan. Very large spills should be contained by bunding, etc... procedures. Mop, wipe or soak up with absorbent material and place in a container with a lid. The spilled product produces an extremely slippery surface.

7. HANDLING AND STORAGE

- 7.1 Advice on safe handling** : General ventilation is required. Local ventilation is recommended. Avoid skin and eye contact. Do not ingest. Do not breathe vapour. Do not breathe spray or mist. Do not empty into drains.
- 7.2 Advice on storage** : Do not store with oxidizing agents.
Vapours may form explosive mixtures with air.
Storage temperature: minimum 0 °C, maximum 32 °C
- 7.3 Specific uses** : Refer to technical data sheet available on request.

SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 2.1
 Revision Date: 02.12.2011
 Superseded date: 05.07.2011

DOW CORNING(R) SE 9187 L CLEAR

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Name	CAS-No.	Exposure Limits
Trimethylated silica	68909-20-6	4 mg/m3 TWA Respirable dust 10 mg/m3 TWA Inhalable dust
Trimethoxy(methyl)silane	1185-55-3	50 ppm (8h TWA) - Dow Corning recommendation.

8.2 Exposure controls

Engineering Controls : Ventilation : Refer to Section 7.1

Personal protection equipment

Respiratory protection : Contact with water or humid air will form methanol. Please take into account any occupational exposure limits for methanol which are applicable in your country.
 -
 Suitable respiratory protection should be worn if the product is used in large quantities, confined spaces or in other circumstances where the OEL may be approached or exceeded.
 A suitable respirator must be worn if the product is used in any circumstances where an aerosol or mist may be generated, such as during spraying or similar activities.
 Depending on the working conditions, wear a respiratory mask with filter(s) AXP or use a self-contained respirator.
 The choice of a filter type depends on the amount and type of chemical being handled in the workplace. Regarding filter characteristics, contact your respiratory protection supplier.

Hand protection : Chemical protective gloves or gauntlets should be worn and removed correctly to avoid skin contamination: Silver shield(TM). 4H(TM). Regarding glove's breakthrough time, contact your chemical protective glove supplier.

Eye/face protection : Safety glasses should be worn.

Skin protection : Wear impervious overalls in circumstances where significant skin contact can occur.

Hygiene measures : Exercise good industrial hygiene practice. Wash after handling, especially before eating, drinking or smoking. Remove contaminated clothing immediately.

Additional information : These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions. For further information regarding the use of silicones / organic oils in consumer aerosol applications, please refer to the guidance document regarding the use of these types of materials in consumer aerosol applications that has been developed by the silicone industry (www.SEHSC.com) or contact the Dow Corning customer service group.

Environmental exposure controls : Refer to section 6 and 12.

SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 2.1

Revision Date: 02.12.2011

Superseded date: 05.07.2011

DOW CORNING(R) SE 9187 L CLEAR**9. PHYSICAL AND CHEMICAL PROPERTIES**

Form	:	Liquid
Colour	:	Colorless to pale yellow
Odour	:	Alcoholic
Boiling point/range	:	> 100 °C
Flash point	:	63 °C (Seta Closed Cup)
Explosive properties	:	No Vapours may form explosive mixtures with air.
Specific Gravity	:	1.00
Viscosity	:	12 Poise at 25°C.
Oxidizing properties	:	No

The above information is not intended for use in preparing product specifications. Contact Dow Corning before writing specifications.

10. STABILITY AND REACTIVITY

10.1 Reactivity	:	This product releases methanol.
10.2 Stability	:	Stable under normal usage conditions.
10.3 Possibility of hazardous reactions	:	None known.
10.4 Conditions to avoid	:	None established.
10.5 Materials to avoid	:	Can react with strong oxidising agents.
10.6 Hazardous decomposition products	:	Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Silica. Carbon oxides and traces of incompletely burned carbon compounds. Formaldehyde. Nitrogen products.

11. TOXICOLOGICAL INFORMATION**Acute toxicity:**

On contact with eyes	:	May cause temporary discomfort.
On skin contact	:	Large amount in contact with significant skin surface areas may cause systemic adverse effects.
If inhaled	:	May cause dizziness, drowsiness, confusion, headaches, nausea, and at high concentrations, unconsciousness.

SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 2.1

Revision Date: 02.12.2011

Superseded date: 05.07.2011

DOW CORNING(R) SE 9187 L CLEAR

On ingestion : Forms methanol. Swallowing large amounts may cause systemic adverse effects and blindness.

Chronic toxicity:

On skin contact : Prolonged or repeated dermal contact may cause systemic adverse effect. Repeated contact can cause sensitisation and allergic dermatitis.

If inhaled : Prolonged or repeated inhalation may cause systemic adverse effects.

On ingestion : Repeated swallowing may cause systemic adverse effects.

Toxicokinetics, metabolism and distribution : Dangerous amounts can be absorbed through the skin.

Other Health Hazard Information : This product contains (a) powder(s) hazardous by inhalation. This is not relevant to the current physical form of the product, which is not in a respirable form.

¹ Based on product test data.

² Based on test data from similar products.

12. ECOLOGICAL INFORMATION**12.1 Ecotoxicity effects**

No adverse effects on aquatic organisms are predicted.

12.2 Persistence and degradability

Siloxanes are removed from water by sedimentation or binding to sewage sludge. In soil, siloxanes are degraded. This product hydrolyses in water or moist air, releasing methanol and organosilicons.

12.3 Bioaccumulation

No bioaccumulation is predicted.

12.4 Release to waters / Mobility in soil**Fate and effects in waste water treatment plants:**

No adverse effects on bacteria are predicted. Removed > 90% by binding onto sewage sludge. The siloxanes in this product do not contribute to the BOD.

SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 2.1
Revision Date: 02.12.2011
Superseded date: 05.07.2011**DOW CORNING(R) SE 9187 L CLEAR****13. DISPOSAL CONSIDERATIONS**

Product and packaging disposal : Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

14. TRANSPORT INFORMATION**Road / Rail (ADR/RID)**

Not subject to ADR/RID.

Sea transport (IMDG)

Not subject to IMDG code.

Air transport (IATA)

Not subject to IATA regulations.

15. REGULATORY INFORMATION**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****Status**

TSCA : All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

IECSC : All ingredients listed or exempt.

KECL : All ingredients listed, exempt or notified.

DSL : Consult your local Dow Corning office.

EINECS : Not determined.

AICS : One or more ingredients are not listed or exempt.

PICCS : One or more ingredients are not listed or exempt.

SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 2.1

Revision Date: 02.12.2011

Superseded date: 05.07.2011

DOW CORNING(R) SE 9187 L CLEAR**16. OTHER INFORMATION**

This product safety data sheet was prepared in compliance with article 31 and Annex II of the EU REACH Regulation as well as its relevant amendments, on the approximation of laws, regulations and administrative provisions relative to the classification, packaging and labelling of dangerous substances and preparations.

It is the responsibility of persons in receipt of this Product Safety Data Sheet to ensure that the information contained herein is properly read and understood by all people who may use, handle, dispose or in any way come in contact with the product. If the recipient subsequently produces a formulation containing the Dow Corning product, it is the recipient's sole responsibility to ensure the transfer of all relevant information from the Dow Corning Product Safety Data Sheet to their own Product Safety Data Sheet in compliance with article 31 and Annex II of the EU REACH Regulation.

All information and instructions provided in this Safety Data Sheet (SDS) are based on the current state of scientific and technical knowledge at the date indicated on the present SDS. Dow Corning shall not be held responsible for any defect in the product covered by this SDS, should the existence of such defect not be detectable considering the current state of scientific and technical knowledge.

As stated above, this Safety Data Sheet has been prepared in compliance with applicable European law. If you purchase this material outside Europe, where compliance laws may differ, you should receive from your local Dow Corning supplier a SDS applicable to the country in which the product is sold and intended to be used. Please note that the appearance and content of the SDS may vary - even for the same product - between different countries, reflecting the different compliance requirements. Should you have any question, please refer to your local Dow Corning supplier.

Source of information: Internal data and publically available information

R11 Highly flammable., **R43** May cause sensitization by skin contact., **R66** Repeated exposure may cause skin dryness or cracking.

H225 Highly flammable liquid and vapour., **H317** May cause an allergic skin reaction.