

Quick-Connect Surge Protector, 8-Wire RS-232

Get convenient quick-connect surge protection for RS-232 Ethernet 8-wire connections.

Put avalanche diode protection where you need it.

Specifications

Application: RS-232 / digital 4-20 mA Current Loop

Ground Wire: Yes

Maximum Shunt Capacitance: <40 pF

Peak Pulse Current: 60 amps

Pins Protected: All

Protection Type: Avalanche diode technology

Response Time: <5 ns

Standard Clamping Voltage: 18 volts

Connectors: 8-position terminal block (14 to 26 AWG)

Overview

This quick-connect surge protector guards Ethernet 8-wire connections for RS-232 connectors.

What's included

- Quick-Connect Surge Protector
- Specification sheet

© Copyright 2010. Black Box Corporation. All rights reserved. Printed in U.S.A. Black Box® and the Double Diamond logo are registered trademarks of BB Technologies, Any third-party trademarks appearing in this publication are acknowledged to be the property of their respective owners.

SP606A, rev. 1

Customer Support Information Order toll-free in the U.S.: Call 877-877-BBOX (outside U.S. call 724-746-5500) FREE technical support 24 hours a day, 7 days a week: Call 724-746-5500 or fax 724-746-0746 Mailing address: Black Box Corporation, 1000 Park Drive, Lawrence, PA 15055-1018 Web site: www.blackbox.com • E-mail: info@blackbox.com