



PRH.N0.3GL.AC65GZ

MECHANICAL DETAILS

Shell Style Model PR* : Free receptacle with cable collet and nut for fitting a bend relief


Keying 2 keys (beta=170; plug: female contacts, receptacle: male contacts)

Housing Material PSU (Polysulfone), gray

Cable Fixing 5.3 - 6.5 mm

Variant 2 G : Gray collet nut for bend relief

	Col	Col	Col	Col	Col	Col	Col	Col
Mm.								
In.								



PERFORMANCE DETAIL

Insert 1P.N03 : 3 High Voltage

Insulator

Specifications

Note: Increased creepage distance, pin 3 longer

Contact Type: Solder

Max. Matings: 2000

Contact Dia.: 0.9 mm (0.04in)

Bucket Dia.: 1.4 mm (0.055in)

Max. Solid 1 mm² (AWG 18)

Max. Stranded 1 mm² (AWG 18)

R (max): 4.5 mOhm

Cable type: |A|H07



OTHER CHARACTERISTICS

Shell Style/Model Libellé

F ret (min): 50 N

F ret (max): 150 N

IP Rating 50



Available Download

[P_series_catalog.pdf](#)

Related links

- [Contact](#)
- [Quote Request](#)
- [Catalogs Downloads](#)
- [Catalogs Requests](#)
- [Sample Request](#)
- [3D drawings](#)