



Main

| | |
|---------------------------|---|
| Range of product | Harmony XVS |
| Product or component type | Siren |
| Device short name | XVS |
| Colour | White |
| Signalling type | 2 tones siren |
| [Us] rated supply voltage | 24 V AC/DC 12 V AC/DC |
| Noise level | 106 dB (continuous or intermittent tone) at 1 m |

Complementary

| | |
|--|----------------------------|
| Material | PC (body) |
| Product weight | 0.8 kg |
| Marking | CE |
| [Uimp] rated impulse withstand voltage | 0.8 kV |
| Current consumption | 500 mA 300 mA at 24 V |
| Clamping connection capacity | <= 1 x 1.5 mm ² |
| Electrical connection | Cable: 6.5...8.5 mm |
| Width | 114 mm |
| Height | 114 mm |
| Depth | 153.2 mm |

Environment

| | |
|--|-------------------------------------|
| Standards | EN/IEC 60947-1 EN/IEC 60947-5-1 |
| Protective treatment | TC |
| Ambient air temperature for storage | -35...70 °C |
| Ambient air temperature for operation | -30...50 °C |
| Class of protection against electric shock | Class II conforming to EN/IEC 61140 |
| IP degree of protection | IP53 conforming to EN/IEC 60529 |

Offer Sustainability

| | |
|--------------------------|---|
| Sustainable offer status | Not Green Premium product |
| RoHS | Compliant - since 0808 - Schneider Electric declaration of conformity |

Siren

Dimensions

