

# IR Thermometer



## Specification Table

Technical Specifications	
Temperature Range	-18°C to 280°C
High Measurement Precision	±2°C or 2% (condition 23°C ± 2°C)
Repeat Precision	<±0.5°C / <±0.5%
Resolution	0.1
D:S (Distance to Spot Size)	10 to 1
Response Time	500 mS
Emissivity	0.95
°C / °F Selection	✓
Laser Switch	✓
Display Backlight	✓
Maximum Measurement	✓
Minimum Measurement	✓
Sleep Mode	✓
Low Battery Display	✓

## General Characteristics

Power	9 V Battery (6F22)
LCD Size	22 × 22 mm
Product Net Weight	185 g
Product Size	145 × 80 × 40 mm
Standard Accessories	Battery, English Manual
Standard Individual Packing	Blister
Standard Quantity Per Carton	40 pcs
Standard Carton Measurement	530 × 485 × 320 mm (0.082 CBM per standard carton)
Standard Carton Gross Weight	10 kg

## Part Number Table

Description	Part Number
IR Thermometer Spot Ratio 10:1	72-8730

**Important Notice :** This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. TENMA™ is the registered trademark of the Group. © Premier Farnell plc 2012.

# Clamp Meter



## Safety Rating:

CAT II 600 V  
CAT III 300 V

## Specifications

Basic Functions	Range	Best Accuracy
AC Current (A)	2 A / 20 A / 200 A / 400 A	± (1.5% + 5)
AC Voltage (V)	2 V / 20 V / 200 V / 600 V	± (1.2% + 5)
DC Voltage (V)	200 mV / 2 V / 20 V / 200 V / 600 V	± (0.8% + 1)
Resistance (Ω)	200 Ω / 2 KΩ / 20 KΩ / 200 KΩ / 2 MΩ / 20 MΩ	± (1% + 2)
Temperature (°C)	-40°C to 1,000°C	± (1% + 3)
Temperature (°F)	-40°F to 1,832°F	± (1% + 6)
<b>Features</b>		
Display count	1,999	
Auto range	✓	
Jaw capacity	28 mm	
Diode	✓	
Auto power off		

[www.element14.com](http://www.element14.com)  
[www.farnell.com](http://www.farnell.com)  
[www.newark.com](http://www.newark.com)  
[www.cpc.co.uk](http://www.cpc.co.uk)  
[www.mcmelectronics.com](http://www.mcmelectronics.com)



# Clamp Meter



## Specifications

Basic Functions	Range	Best Accuracy
<b>Features</b>		
Continuity buzzer	✓	
Low battery indication		
Data hold		
Maximum mode		
Full icon display		
Input impedance for DCV	Around 10 MΩ	

## General Characteristics

Power	1.5 V batteries (R03) × 2
LCD size	35.6 × 18 mm
Product colour	Orange and grey
Product net weight	220 g
Product size	210 × 75.6 × 30 mm
Standard accessories	Battery, test lead, carrying bag, point contact temperature probe
Standard individual packing	Gift box, English manual

## Part Number Table

Description	Part Number
Clamp Meter, With Temperature	72-7222

**Important Notice :** This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. TENMA™ is the registered trademark of the Group. © Premier Farnell plc 2011.

