

Triple RG179 Coaxial Multiconductor Cable **pro-POWER**



Triple RG179 solid conductor coaxial multicore with grey overall jacket.



Triple RG179 solid conductor coaxial multicore with black overall jacket

Physical Characteristics:

Coaxial type	: (Triple) RG179 Coax
Conductor	: 1 × 0.36mm
Dielectric	: Foamed Polyethylene
Dielectric diameter	: 1.65mm
Screen	: 97% Tinned Copper Braid
Element outer jacket	: PVC – Red, Green, Blue
Element overall diameter	: 2.55mm
Overall outer jacket	: PVC – Grey (210602)
	: PVC - Black (210600)
Overall diameter	: 7mm
Weight	: 65Kg/Km

Electrical Characteristics:

Conductor DC Resistance	: 189.7Ω/Km
Rated temperature	: 80°C
Rated voltage	: 300V
Insulation resistance	: >100MΩ/Km
Nominal capacitance	: 54pF/m
Velocity Ratio	: 82%
Attenuation	: dB/100m @20°C
10MHz	: 6
100MHz	: 19.5
200MHz	: 28

Part Number Table

Description	Colour	Part Number
Coaxial Cable, 75R, 3 Core, 100m	Grey	210602
Coaxial Cable, 75R, 3 Core, 100m	Black	210600
Coaxial Cable, 75R, 3 Core, Per m	Grey	210602
Coaxial Cable, 75R, 3 Core, Per m	Black	210600

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.