

# BS4808 0.75mm<sup>2</sup> (24/0.2mm) PVC Equipment Wire

pro-POWER

RoHS  
Compliant

## Reference Standard

BS4808 Part 2 Class 3 and Def. Stan. 61-12(Pt6) Type 3



## Specifications:

Conductor Material	: Tinned Copper
Conductor Area CSA	: 0.75mm <sup>2</sup>
Construction	: T0.2± 0.008×24
Stranded Dia.(mm)	: 1.13
Jacket Material	: PVC
Jacket Thickness	: 0.59
Jacket Dia.(±0.1mm)	: 2.3+0.15/-0.1
Reel Length (Metric)	: 100m

## Electrical Characteristics:

Max. Conductor DC Resistance at 20°C (Ω/Km)	: <25.2
Min. Insulation DC Resistance at 20°C (MΩ/Km)	: 200
Rated Temperature(°C)	: -25 to +85
Rated Voltage(V)	: 1,500
Flame Performance	: UL1581VW-1 IEC60332-1

## Part Number Table

Description	Colour	Reel Length (m)	Part Number
Wire, 24/0.2mm, Tinned Copper	Black	100	PP000045
	Brown		PP000046
	Red		PP000047
	Orange		PP000048
	Yellow		PP000049
	Green		PP000379
	Blue		PP000380
	Violet		PP000381
	Grey		PP000382
	White		PP000383
	Pink		PP000384
	Green / Yellow		PP000385
	Black		500
	White	PP000387	

**Important Notice** : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com  
www.farnell.com  
www.newark.com  
www.cpc.co.uk

pro-POWER