

BS 4808 0.22mm² (7/0.2mm) PVC Equipment Wire Kit

pro-POWER

RoHS
Compliant

Reference Standard

BS4808 Part 2 Class 2 and Def. Stan. 61-12(Pt6) Type 2



Specifications:

Conductor Material	: Tinned Copper
Conductor Area CSA	: 0.22mm ²
Construction	: T0.20± 0.008×7
Stranded Dia.(mm)	: 0.60
Jacket Material	: PVC
Jacket Colours	: Black, Brown, Red, Orange, Yellow, Green, Blue, Grey, White, Violet, Pink
Jacket Thickness	: 0.3
Jacket Dia.(±0.1mm)	: 1.2
Reel Length (Metric)	: 100m

Electrical Characteristics:

Max. Conductor DC Resistance at 20°C (Ω/Km)	: <86.2
Min. Insulation DC Resistance at 20°C (MΩ/Km)	: 200
Rated Temperature(°C)	: -25 to +85
Rated Voltage(V)	: 1,000
Flame Performance	: UL1581VW-1 IEC60332-1

Kit contains 11 100m reels of 7/0.2mm equipment wire in 11 different colours.

Part Number Table

Description	Part Number
Wire Kit, 7/0.2mm, 11 100m Reels	PP000076

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.