

# Keysight Remote Link

Data Sheet



Reach MORE. Accomplish MORE. Expect MORE.

## Introduction

The remote link solution – Keysight's next generation wireless connectivity solution lets you measure further, easier and faster. With the new U1117A IR-to-Bluetooth® adapter and U1115A remote logging display, you get instant wireless Bluetooth connection and measure safely from an extended distance.

- Extended measurement distance of up to 100 meters
- Supported on both iOS/Android based smart device\*\*
- View readings of up to four handheld meters simultaneously\*
- Compatible with Keysight U1117A / U1177A IR-to-Bluetooth Adapter
- 60,000 points interval logging\*
- Download logged data to a Windows PC via Bluetooth connection\*
- Micro USB external power port\*
- Indoor and outdoor viewing mode\*
- Compatible with ALL Keysight's U1200 Series handheld meters\*

\* U1115A only

\*\* U1117A only



## Improve work safety with 10 times MORE distance

On site testing in large industrial site can be challenging and hazardous when dealing with live machineries or high voltage equipment. By connecting your handheld meter to the remote link solution – U1117A IR-to-Bluetooth adapter and U1115A remote logging display, you can view and log measurements wirelessly up to 100 meters away. Get more wireless measurement distance to diagnose and evaluate live machinery from afar without having to be physically present – ensuring your safety and comfort level.

## Compatible with MORE handhelds

The remote link is able to communicate via Bluetooth to 20 Keysight U1200 Series handheld meters, including the new U1450/U1460A series insulation resistance testers. Now you can save investment cost by using existing Keysight handheld meters that you have already owned. The wide selection of handheld meters cater to various application needs to get real-time measurements from a basic, compact and low cost handheld meters.



Figure 1. Communicate via Bluetooth to all existing Keysight U1200 series handheld meters, including the U1450A/U1460A series insulation resistance testers

## Support MORE display devices

The remote link solution offers versatility to work with more display devices. Now you can log and display measurement readings either on the U1115A remote logging display, via iOS and Android smart devices or on a Windows PC. With the wide supportability range, it allows you to multi-task by being able to measure various test points at the same time.



Figure 2. Monitoring handheld multimeter and clamp meter readings remotely via iOS/Android based smart devices



Figure 3. Monitoring handheld meter readings via the U1115A remote logging display

## New U1177A IR-to-Bluetooth adapter (Class 1)

- Supports Android and iOS smart devices
- 100 meters measurement range capability (Please refer to the connectivity distance table below)




Figure 4. The U1177A as illustrated

## Existing U1177A IR-to-Bluetooth adapter (Class 2)

- Supports Android smart devices
- 10 meters measurement range capability (Please refer to the connectivity distance table below)



Figure 5. The U1177A as illustrated



Figure 6. Multiple awards winning U1177A Infrared (IR)-to-Bluetooth adapter is being recognized as an innovative solution in Test & Measurement industry

	U1177A	U1117A	U1115A
U1177A	-	-	10-m
U1117A	-	-	100-m
U1115A	10-m	100-m	-
Other Class 1 devices	10-m	100-m	100-m
Other Class 2 devices	10-m	10-m	10-m

Figure 7. Connectivity distance (approximate) within the line-of-sight




Figure 8. Keysight remote link solution

# U1115A remote logging display



Figure 9. Monitor up to four handheld meters readings at once with the U1115A remote logging display

\* All images shown are for illustration purposes only

## Keysight Mobile Meter Application (iOS/Android)

Monitor up to three multimeter measurements at the same time with Keysight Mobile Meter.



iOS

Android

Figure 10. Up to three handheld meters measurements with the Keysight Mobile Meter Application

Keysight Mobile Meter is a free iOS or Android application software that allows iOS or Android based smart devices to connect, control and perform up to three handheld meter measurements.

- Log and monitor up to three measurements simultaneously without the need to be physically present
- Make measurements from a safe distance
- Eliminates the need to walk back and forth between measurement points
- Save money, time and achieve higher work productivity

## Keysight Mobile Logger Application (iOS/Android)

Perform data logging up to three multimeters – wirelessly and simultaneously!



iOS

Android

Figure 11. Data logging with Keysight Mobile Logger Application

Keysight Mobile Logger is the free iOS or Android application software that logs data and provides trending graphs from Keysight handheld meters.

- Capture data streams or plot trending graphs
- Used for analysis to identify intermittent behavior or detect drifts
- Email functions, Short Message Service (SMS), pan and zoom function via iOS/Android device's touch screen
- Create mathematical functions and plot trending graphs

## Keysight Insulation Tester Application (iOS/Android)

Perform remote testing, data logging and report generation with Keysight Insulation Tester Application



iOS

Figure 12. Remote testing and report generation interface on the Keysight Insulation Tester Application



Android

Figure 13. Data logging interface on the Keysight Insulation Tester Application

Keysight Insulation Tester Application is the free iOS or Android application software for the new U1450A/U1460A series insulation resistance testers to perform remote testing, data logging and generate test report via a smart phone or tablet.

- Acquire and analyze insulation resistance data from a distance
- Eliminates manual data entry errors for report generation
- Fastest way to generate accurate test reports
- Log data and provide trending graphs to identify intermittent problems (multimeter functionality)
- Saves money, time and achieve higher work productivity

Keysight Insulation Resistance Tester Application for iOS and Android can be downloaded from [www.keysight.com/find/insulationtesterapp](http://www.keysight.com/find/insulationtesterapp) or from Google Play Store (<https://play.google.com/>) App Store (<https://itunes.apple.com/>)

## Keysight Handheld Meter Logger software for Windows PC

The remote link solution also supports data logging and monitoring activities on a Windows PC via downloadable Keysight Handheld Meter Logger software.




Figure 14. View up to 10 handheld meters readings or trends with Keysight Handheld Meter Logger software




Figure 15. View insulation resistance test trendings and generate test report on a Windows PC

The Keysight Handheld Meter Logger software is a free software compatible with the U1210 Series, U1230 Series, U1240 Series\*, U1250 Series, U1270 Series, and U1450A/U1460A\*\*.

\* For the U1240 Series, you also need to purchase the U1179A IR Connectivity Bracket to enable IR connectivity

\*\* Only allows one connection at a time

- Connect up to 10 handheld meters – 5x IR-to-Bluetooth Adapter (U1177A, U1117A) and 5x IR-USB Cable (U1173B)
- Meter view (live measurements) and Logger view (graph with zoom and pan) mode
- Manage multi-session data logging within the software and export the data to other software (Excel)

Keysight Handheld Meter Logger Software can be downloaded from [www.keysight.com/find/hhmeterlogger](http://www.keysight.com/find/hhmeterlogger)

# Specifications

Product characteristics U1117A	
Radio specification	Frequency: 2402 MHz ~ 2480 MHz Transmit power: +17 dBm Number of channels: 79 Modulation: GFSK/PSK
Temperature	Operating condition: -20 to 55 °C Storage condition: -40 to 70 °C
Relative humidity (R.H.)	Operating condition: Up to 80% at 40 °C (non-condensing) Storage condition: Up to 95% at 40 °C (non-condensing)
Power consumption	Maximum 561 mVA for two 1.5 V AAA batteries
Battery lifespan	Lithium batteries: 30 hours Alkaline batteries: 20 hours
Battery type	Lithium 24-LF (ANSI) and FR03 (IEC) Alkaline 24 A (ANSI/NEDA) and LR03 (IEC) Zinc Chloride 24 D (ANSI/NEDA) and R03 (IEC)
Dimension (W x L x H)	39.0 mm x 71.0 mm x 37.0 mm
Weight	60 g with batteries
Warranty	Three months (does not cover normal wear and tear of mechanical parts and batteries)
Bluetooth	"Bluetooth" Version 2.1 + EDR compliant, SPP profile, Class 1 device (with approximately 100 meters connection range)
Regulatory	The U1117A complies with the requirements of the following product standards: <div style="border: 1px solid black; padding: 5px; width: fit-content; margin-top: 5px;">             Complies with IDA Standards DB 102425           </div> <ul style="list-style-type: none"> <li>- EN 301 489-1V1.9.2</li> <li>- EN 301 489-17:V2.1.1</li> <li>- EN 55022:2006+A1:2007</li> <li>- EN55024:1998+A1:2001+A2:2003</li> <li>- EN 300 328 V1.7.1 (2006-10)</li> <li>- EN 62311:2008</li> <li>- EN 60950-1:2006+A11:2009+A12:2011</li> <li>- India Equipment Type Approval (ETA) Certificate No: 1424/2011/WRLO</li> <li>- COFETEL Certificate No: RCPAGU111-1066, registered under Keysight Technologies Mexico S de RL de CV</li> </ul> <p>This telecommunication equipment conforms to the NTC technical requirement</p>
Compatibility	<p>Keysight Handheld Meter/Display:</p> <ul style="list-style-type: none"> <li>- Keysight U1200 Series Handheld Meters</li> <li>- Keysight U1450A/60A Series Insulation Resistance Testers<sup>1</sup></li> <li>- Keysight U1115A Remote Logging Display</li> </ul> <p>Keysight PC Application Software:</p> <ul style="list-style-type: none"> <li>- Keysight Handheld Meter Logger</li> </ul> <p>Keysight Mobile Application:</p> <ul style="list-style-type: none"> <li>- Keysight Mobile Meter</li> <li>- Keysight Mobile Logger</li> <li>- Keysight Insulation Tester</li> </ul> <p>Hardware Devices:</p> <ul style="list-style-type: none"> <li>- iPhone</li> <li>- iPad</li> <li>- iPod Touch</li> <li>- Android smartphone/tablet</li> <li>- Windows PC (with <i>Bluetooth</i> enabled)</li> </ul>

1. U1117A IR-Bluetooth Adapter is compatible with the U1450A/U1460A series to establish wireless connectivity on a Windows PC or iOS/Android smart devices. U1115A is not compatible with the U1450A/U1460A series.



## Product characteristics U1177A

Radio specification	Frequency: 2402 MHz ~ 2480 MHz Antenna power: 1 mW or less Number of channels: 79 Modulation: GFSK/PSK
Temperature	Operating condition: -20 to 55 °C Storage condition: -40 to 70 °C
Relative humidity (R.H.)	Operating condition: Up to 80% at 40 °C (non-condensing) Storage condition: Up to 95% at 40 °C (non-condensing)
Power consumption	Maximum 130 mVA for two 1.5 V AAA batteries
Battery life span	30 hours typical (based on continuous data transfer)
Battery type	Alkaline 24 A (ANSI/NEDA) and LR03 (IEC) Zinc Chloride 24 D (ANSI/NEDA) and R03 (IEC)
Dimension (W x L x H)	39.0 mm x 37.0 mm x 71.0 mm
Weight	60 g with batteries
Warranty	Three months (does not cover normal wear and tear of mechanical parts and batteries)
Bluetooth	"Bluetooth" Version 2.1 + EDR compliant, SPP profile, Class 2 device (with 10 meters connection range)
Regulatory	The U1177A complies with the requirements of the following safety and regulation standards: <ul style="list-style-type: none"><li>- FCC Part15C (Certification) (15.209, 15.247) FCC ID: ZKMKEYSIGHT-U1177A</li><li>- FCC Part15B (DoC) (15.109)</li><li>- RSS-210 Issue 8:2010 IC:6310A-U1177A</li><li>- ICES-003 Issue 4:2004</li><li>- EN 300 328 V1.7.1:2008</li><li>- EN 301 489-1V1.8.1:2008/-17 V2.11:2009</li><li>- EN 55022:2006+A1:2007/EN55024:1998+A1:2001+A2:2003</li><li>- EN 50371:2002</li><li>- EN 60950-1:2006/A11:2009/A1:2010</li><li>- Complies with IDA Standards (DB 102425)</li><li>- India Equipment Type Approval (ETA) Certificate No: 1424/2011/WRLO</li><li>- COFETEL Certificate No: RCPAGU111-1066, registered under Keysight Technologies Mexico S de RL de CV</li></ul> <p>This telecommunication equipment conforms to the NTC technical requirement</p>
Compatibility	Keysight Handheld Meter/Display: <ul style="list-style-type: none"><li>- Keysight U1200 Series Handheld Meters</li><li>- Keysight U1450A/60A Series Insulation Resistance Testers<sup>1</sup></li><li>- Keysight U1115A Remote Logging Display</li></ul> Keysight PC Application Software: <ul style="list-style-type: none"><li>- Keysight Handheld Meter Logger</li></ul> Keysight Mobile Application: <ul style="list-style-type: none"><li>- Keysight Mobile Meter</li><li>- Keysight Mobile Logger</li><li>- Keysight Insulation Tester</li></ul> Hardware Devices: <ul style="list-style-type: none"><li>- iPhone</li><li>- iPad</li><li>- iPod Touch</li><li>- Android smartphone/tablet</li><li>- Windows PC (with Bluetooth-enabled)</li></ul>

1. U1177A IR-Bluetooth Adapter is compatible with the U1450A/U1460A series to establish wireless connectivity on a Windows PC or iOS/Android smart devices. U1115A is not compatible with the U1450A/U1460A Series

## Product characteristics U1115A

Radio specification	Frequency: 2402 MHz ~ 2480 MHz Transmit power: +17 dBm Number of channels: 79 Modulation: GFSK/PSK
Temperature	Operating condition: -20 to 55 °C Storage condition: -40 to 70 °C
Relative humidity (R.H.)	Operating condition: Up to 80% at 40 °C (non-condensing) Storage condition: Up to 95% at 40 °C (non-condensing)
Power consumption	Maximum 1 VA for three AA batteries Maximum 5 V +10%, 250 mA for external power Auto Power Off mode, current consumption 3 mA
Battery lifespan	Lithium batteries: 30 hours Alkaline batteries: 20 hours
Battery type	Lithium 15-LF (ANSI) and FR06 (IEC) Alkaline 15 A (ANSI/NEDA) and LR06 (IEC) Zinc Chloride 15 D (ANSI/NEDA) and R06 (IEC)
Dimension (W x L x H)	92.0 mm x 107.9 mm x 33.5 mm
Weight	238 g with batteries, 170 g without batteries
Warranty	One year (does not cover normal wear and tear of mechanical parts and batteries)
Bluetooth	"Bluetooth" Version 2.1 + EDR compliant, SPP profile, Class 1 device (with approximately 100 meters connection range)
Regulatory	The U1115A complies with the requirements of the following product standards: <ul style="list-style-type: none"><li>- EN 301 489-1:V1.9.2</li><li>- EN 301 489-17:V2.1.1</li><li>- EN 55022:2006+A1:2007+A2:2010 (Group 1 Class A)</li><li>- EN55024:1998+A1:2001+A2:2003+A3:2010</li><li>- EN 300 328 V1.7.1 (2006-10)</li><li>- EN 62311:2008</li><li>- EN 60950-1:2006+A11:2009+A1:2010+A12:2011</li></ul> This telecommunication equipment conforms to the NTC technical requirement
Compatibility	Keysight Handheld Meter/Display: <ul style="list-style-type: none"><li>- Keysight U1200 Series Handheld Meters</li><li>- Keysight U1117A IR-to-Bluetooth Adapter</li><li>- Keysight U1177A IR-to-Bluetooth Adapter</li></ul> Keysight PC Application Software: <ul style="list-style-type: none"><li>- Keysight Handheld Meter Logger<sup>1</sup></li></ul> Hardware Device: <ul style="list-style-type: none"><li>- Windows PC (with Bluetooth enabled)</li></ul> Note: U1115A is not compatible with U1450A/60A series

1. Transfers logged data from U1115A remote logging display to Windows PC

**Ordering information**

U1115A Remote Logging Display



**Standard shipped accessories**

- Three 1.5 V AA batteries.
- USB to micro USB cable (for external power only).
- Soft Carrying Case
- Operating instruction

U1117A IR-to-Bluetooth adapter



- Two 1.5 V AAA batteries
- Operating instruction

U1177A IR-to-Bluetooth adapter



- Two 1.5 V AAA batteries
- Operating instruction



myKeysight

[www.keysight.com/find/mykeysight](http://www.keysight.com/find/mykeysight)

A personalized view into the information most relevant to you.

*Bluetooth* and the *Bluetooth* logos are trademarks owned by *Bluetooth SIG, Inc.*, U.S.A. and licensed to Keysight Technologies, Inc.

[www.keysight.com/find/hhgowireless](http://www.keysight.com/find/hhgowireless)

For more information on Keysight Technologies' products, applications or services, please contact your local Keysight office. The complete list is available at: [www.keysight.com/find/contactus](http://www.keysight.com/find/contactus)

#### Americas

Canada	(877) 894 4414
Brazil	55 11 3351 7010
Mexico	001 800 254 2440
United States	(800) 829 4444

#### Asia Pacific

Australia	1 800 629 485
China	800 810 0189
Hong Kong	800 938 693
India	1 800 112 929
Japan	0120 (421) 345
Korea	080 769 0800
Malaysia	1 800 888 848
Singapore	1 800 375 8100
Taiwan	0800 047 866
Other AP Countries	(65) 6375 8100

#### Europe & Middle East

Austria	0800 001122
Belgium	0800 58580
Finland	0800 523252
France	0805 980333
Germany	0800 6270999
Ireland	1800 832700
Israel	1 809 343051
Italy	800 599100
Luxembourg	+32 800 58580
Netherlands	0800 0233200
Russia	8800 5009286
Spain	0800 000154
Sweden	0200 882255
Switzerland	0800 805353
	Opt. 1 (DE)
	Opt. 2 (FR)
	Opt. 3 (IT)
United Kingdom	0800 0260637

For other unlisted countries:  
[www.keysight.com/find/contactus](http://www.keysight.com/find/contactus)  
(BP-07-10-14)