

DC Power Jack



**RoHS
Compliant**






Specifications:

Contact Rating	: 2A @ 16 VDC
Contact Resistance	: 30mΩ max.
Insulation Resistance	: 100mΩ min. @ 500 VDC
Operating Life	: 5,000 cycles
Withstand Voltage	: 500V AC for 1 min.


Materials

Bushing	: Brass, nickel plated
Cover	: Bakelite
Hardware	: Washer, nut, brass, nickel plated
Housing	: ABS plastic
Pin	: Brass, nickel plated
Pin Terminal	: Brass, nickel plated
Springs	: Brass, nickel plated



Dimensions : Millimetres

Item	Description	Qty.
1	Pin	1
2	Nut	
3	Washer	
4	Bushing	
5	Housing	
6	Cover	
7	Pin Terminal	
8	Sleeve Spring	
9	Sleeve Shunt	



Part Number Table

Description	Part Number
Connector, DC Power, Socket, 2A	SPC21472

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.