






Specifications:

Insulation Resistance : DC 300V, $10M\Omega$

Contactor Resistance : 3Ω Max.

Dielectric Strength : 100V AC/Minute, 1mA

Printing : USB 2.0 Cable, 28AWG × 1P + 28AWG × 2C



Dimensions: Millimetres

L = 1,800mm ±30mm

No.	Parts	Standard Specification	QTY
1	Cable	USB 2.0AWG (7/0.12BC × 1P) + 28AWG (7/0.12BC × 2C) +AB B=0.12/3 × 16 AL-MG Jacket : PVC/White OD : 3.8 ±0.2mm	1
2	USB A Type	USB A/M Type, The Pin Gold Plating 30µ", the shell for Nickel Plating	2
3	Outer Mold	Shore 88A PVC Colour : White	2

Part Number Table

Description	Part Number	
Computer Cable, USB2.0, 1.8m, White	11.99.8919	

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com www.farnell.com www.newark.com

