

Axial Lead Fuses

Slow Blow



Electrical Characteristics:

Rated Current (A)	1 In		2 In		3 In		8 In	
	Minimum	Maximum	Minimum	Maximum	Minimum	Maximum	Minimum	Maximum
0.375 to 7	4 Hours	1 Second	60 Seconds	200ms	3 Seconds	20ms	100ms	

Interrupting Rating:

50A at 250V AC

Environmental Specifications:

Operating Temperature	: -55°C to +125°C
Shock	: MIL-STD-202, method 213, condition 1 (100 G's peak for 6 milliseconds)
Vibration	: MIL-STD-202, method 201 (10-55 Hz); method 204, test condition C (55-2,000 Hz at 10 G's peak)
Salt Spray	: MIL-STD-202, method 101, test condition B (48 hours)
Insulation Resistance	: MIL-STD-202, method 302, (after opening) 10,000Ω minimum at 100V
Resistance to Solder Heat	: MIL-STD-202, method 210, test condition C (20 seconds at 260°C)
Thermal Shock	: MIL-STD-202, method 107, test condition B (-65°C to +125°C)
Moisture Resistance	: MIL-STD-202F, method 106 (90 to 98% RH), heat (65°C)


Physical Specification:

Materials

Encapsulated, Epoxy-Coated Body and Solder Coated Copper Wire Leads

Lead Wire : Diameter : 0.64 mm

Mechanical Dimensions:



Part Number Table

Description	Part Number
Fuse, Axial, Slow Blow, 0.5A	MCPMP 0.5A 250V
Fuse, Axial, Slow Blow, 1A	MCPMP 1A 250V
Fuse, Axial, Slow Blow, 1.25A	MCPMP 1.25A 250V
Fuse, Axial, Slow Blow, 2A	MCPMP 2A 250V
Fuse, Axial, Slow Blow, 3A	MCPMP 3A 250V
Fuse, Axial, Slow Blow, 5A	MCPMP 5A 250V
Fuse, Axial, Slow Blow, 7A	MCPMP 7A 250V

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.

