



## Safety Data Sheet according to Regulation (EC) No1907/2006

Page 1 of 13

Loctite 7400 Varnistop

SDS No. : 290260

V006.0

Revision: 03.06.2014

printing date: 20.09.2014

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Loctite 7400 Varnistop

#### Contains:

n-Butyl acetate

4-Methylpentan-2-one

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Coating

#### 1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 1442 278000

Fax-no.: +44 1442 278071

ua-productsafety.uk@uk.henkel.com

#### 1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (CLP):

Flammable liquids	Category 2
H225 Highly flammable liquid and vapor.	
Serious eye irritation	Category 2
H319 Causes serious eye irritation.	
Specific target organ toxicity - single exposure	Category 3
H336 May cause drowsiness or dizziness.	
Target organ: Central Nervous System	
Specific target organ toxicity - single exposure	Category 3
H335 May cause respiratory irritation.	
Target organ: respiratory tract irritation	

**Classification (DPD):**

F - Highly flammable  
R11 Highly flammable.  
Xn - Harmful  
R20 Harmful by inhalation.  
Xi - Irritant  
R36/37 Irritating to eyes and respiratory system.  
R66 Repeated exposure may cause skin dryness or cracking.

**2.2. Label elements**

**Label elements (CLP):**

**Hazard pictogram:**



**Signal word:**

Danger

**Hazard statement:**

H225 Highly flammable liquid and vapor.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.

**Supplemental information**

EUH066 Repeated exposure may cause skin dryness or cracking.

**Precautionary statement:**

\*\*\*For consumer use only: P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P501 Dispose of waste and residues in accordance with local authority requirements\*\*\*

**Precautionary statement:  
Prevention**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.  
No smoking.  
P261 Avoid breathing vapours.  
P280 Wear protective gloves/protective clothing.

**Precautionary statement:  
Response**

P337+P313 If eye irritation persists: Get medical advice/attention.

**Label elements (DPD):**

F - Highly flammable

Xn - Harmful

**Risk phrases:**

R11 Highly flammable.  
R20 Harmful by inhalation.  
R36/37 Irritating to eyes and respiratory system.  
R66 Repeated exposure may cause skin dryness or cracking.

**Safety phrases:**

S23 Do not breathe vapour.  
S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
S37 Wear suitable gloves.  
S51 Use only in well-ventilated areas.

**Additional labeling:**

For consumer use only: S2 Keep out of the reach of children.  
S46 If swallowed, seek medical advice immediately and show this container or label.

**Contains:**

4-Methylpentan-2-one

**2.3. Other hazards**

None if used properly.

**SECTION 3: Composition/information on ingredients****General chemical description:**

Solvent based coating

**Declaration of the ingredients according to CLP (EC) No 1272/2008:**

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
n-Butyl acetate 123-86-4	204-658-1 01-2119485493-29	>= 25- < 50 %	Flammable liquids 3 H226 Specific target organ toxicity - single exposure 3 H336
4-Methylpentan-2-one 108-10-1	203-550-1 01-2119473980-30	>= 25- < 50 %	Flammable liquids 2 H225 Acute toxicity 4; Inhalation H332 Serious eye irritation 2 H319 Specific target organ toxicity - single exposure 3 H335

For full text of the H - statements and other abbreviations see section 16 "Other information".  
Substances without classification may have community workplace exposure limits available.

**Declaration of ingredients according to DPD (EC) No 1999/45:**

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
n-Butyl acetate 123-86-4	204-658-1 01-2119485493-29	>= 25 - < 50 %	R10 R67 R66
4-Methylpentan-2-one 108-10-1	203-550-1 01-2119473980-30	>= 25 - < 50 %	F - Highly flammable; R11 Xn - Harmful; R20 Xi - Irritant; R36/37 R66

For full text of the R-Phrases indicated by codes see section 16 'Other Information'.  
Substances without classification may have community workplace exposure limits available.

**SECTION 4: First aid measures****4.1. Description of first aid measures****Inhalation:**

Move to fresh air. If symptoms persist, seek medical advice.

**Skin contact:**

Rinse with running water and soap.  
Obtain medical attention if irritation persists.

**Eye contact:**

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

**Ingestion:**

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

**4.2. Most important symptoms and effects, both acute and delayed**

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

EYE: Irritation, conjunctivitis.

Repeated exposure may cause skin dryness or cracking.

**4.3. Indication of any immediate medical attention and special treatment needed**

See section: Description of first aid measures

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media:**

Carbon dioxide, foam, powder

**Extinguishing media which must not be used for safety reasons:**

None known

**5.2. Special hazards arising from the substance or mixture**

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and nitrogen oxides (NO<sub>x</sub>) can be released.

**5.3. Advice for firefighters**

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

**Additional information:**

In case of fire, keep containers cool with water spray.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Avoid skin and eye contact.  
Ensure adequate ventilation.

**6.2. Environmental precautions**

Do not let product enter drains.

**6.3. Methods and material for containment and cleaning up**

For small spills wipe up with paper towel and place in container for disposal.  
For large spills absorb onto inert absorbent material and place in sealed container for disposal.  
Dispose of contaminated material as waste according to Section 13.

**6.4. Reference to other sections**

See advice in section 8

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

Use only in well-ventilated areas.  
Vapours should be extracted to avoid inhalation.  
Keep away from sources of ignition - no smoking.

**Hygiene measures:**

Wash hands before work breaks and after finishing work.  
Do not eat, drink or smoke while working.  
Good industrial hygiene practices should be observed.

**7.2. Conditions for safe storage, including any incompatibilities**

Store in a cool, well-ventilated place.  
Keep away from heat and direct sunlight.

**7.3. Specific end use(s)**

Coating

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Occupational Exposure Limits**

Valid for  
Great Britain

Ingredient	ppm	mg/m <sup>3</sup>	Type	Category	Remarks
BUTYL ACETATE 123-86-4	200	966	Short Term Exposure Limit (STEL):		EH40 WEL
BUTYL ACETATE 123-86-4	150	724	Time Weighted Average (TWA):		EH40 WEL
4-METHYLPENTAN-2-ONE 108-10-1	100	416	Short Term Exposure Limit (STEL):		EH40 WEL
4-METHYLPENTAN-2-ONE 108-10-1			Skin designation:	Can be absorbed through the skin.	EH40 WEL
4-METHYLPENTAN-2-ONE 108-10-1	50	208	Time Weighted Average (TWA):		EH40 WEL
4-METHYLPENTAN-2-ONE 108-10-1	20	83	Time Weighted Average (TWA):	Indicative	ECTLV
4-METHYLPENTAN-2-ONE 108-10-1	50	208	Short Term Exposure Limit (STEL):	Indicative	ECTLV

**Predicted No-Effect Concentration (PNEC):**

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
n-Butyl acetate 123-86-4	aqua (freshwater)					0,18 mg/L	
n-Butyl acetate 123-86-4	aqua (marine water)					0,018 mg/L	
n-Butyl acetate 123-86-4	aqua (intermittent releases)					0,36 mg/L	
n-Butyl acetate 123-86-4	STP					35,6 mg/L	
n-Butyl acetate 123-86-4	sediment (freshwater)				0,981 mg/kg		
n-Butyl acetate 123-86-4	sediment (marine water)				0,0981 mg/kg		
n-Butyl acetate 123-86-4	soil				0,0903 mg/kg		
4-Methylpentan-2-one 108-10-1	aqua (freshwater)					0,6 mg/L	
4-Methylpentan-2-one 108-10-1	aqua (marine water)					0,06 mg/L	
4-Methylpentan-2-one 108-10-1	sediment (freshwater)				8,27 mg/kg		
4-Methylpentan-2-one 108-10-1	sediment (marine water)				0,83 mg/kg		
4-Methylpentan-2-one 108-10-1	soil				1,3 mg/kg		
4-Methylpentan-2-one 108-10-1	STP					27,5 mg/L	
4-Methylpentan-2-one 108-10-1	aqua (intermittent releases)					1,5 mg/L	

**Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
n-Butyl acetate 123-86-4	worker	inhalation	Acute/short term exposure - systemic effects		960 mg/m3	
n-Butyl acetate 123-86-4	worker	inhalation	Acute/short term exposure - local effects		960 mg/m3	
n-Butyl acetate 123-86-4	worker	inhalation	Long term exposure - systemic effects		480 mg/m3	
n-Butyl acetate 123-86-4	worker	inhalation	Long term exposure - local effects		480 mg/m3	
n-Butyl acetate 123-86-4	general population	inhalation	Acute/short term exposure - systemic effects		859,7 mg/m3	
n-Butyl acetate 123-86-4	general population	inhalation	Acute/short term exposure - local effects		859,7 mg/m3	
n-Butyl acetate 123-86-4	general population	inhalation	Long term exposure - systemic effects		102,34 mg/m3	
n-Butyl acetate 123-86-4	general population	inhalation	Long term exposure - local effects		102,34 mg/m3	
4-Methylpentan-2-one 108-10-1	worker	inhalation	Acute/short term exposure - systemic effects		208 mg/m3	
4-Methylpentan-2-one 108-10-1	worker	inhalation	Acute/short term exposure - local effects		208 mg/m3	
4-Methylpentan-2-one 108-10-1	worker	inhalation	Long term exposure - systemic effects		83 mg/m3	
4-Methylpentan-2-one 108-10-1	worker	inhalation	Long term exposure - local effects		83 mg/m3	
4-Methylpentan-2-one 108-10-1	worker	Dermal	Long term exposure - systemic effects		11,8 mg/kg bw/day	
4-Methylpentan-2-one 108-10-1	general population	inhalation	Acute/short term exposure - systemic effects		155,2 mg/m3	
4-Methylpentan-2-one 108-10-1	general population	inhalation	Acute/short term exposure - local effects		155,2 mg/m3	
4-Methylpentan-2-one 108-10-1	general population	inhalation	Long term exposure - systemic effects		14,7 mg/m3	
4-Methylpentan-2-one 108-10-1	general population	inhalation	Long term exposure - local effects		14,7 mg/m3	
4-Methylpentan-2-one 108-10-1	general population	Dermal	Long term exposure - systemic effects		4,2 mg/kg bw/day	
4-Methylpentan-2-one 108-10-1	general population	oral	Long term exposure - systemic effects		4,2 mg/kg bw/day	

**Biological Exposure Indices:**

Ingredient	Parameters	Biological specimen	Sampling time	Conc.	Basis of biol. exposure index	Remark	Additional Information
4-METHYLPENTAN-2-ONE 108-10-1	4-methylpentan-2-one	Urine	Sampling time: End of shift.		UKEH40BMG V		

**8.2. Exposure controls:**

**Respiratory protection:**

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A

**Hand protection:**

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR;  $\geq 0.4$  mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR;  $\geq 0.4$  mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

**Eye protection:**

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

**Skin protection:**

Wear suitable protective clothing.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Appearance	liquid red
Odor	characteristic
Odour threshold	No data available / Not applicable
pH	No data available / Not applicable
Initial boiling point	114 °C (237.2 °F)
Flash point	12 °C (53.6 °F)
Decomposition temperature	No data available / Not applicable
Vapour pressure (20 °C (68 °F))	58,7 mbar
Density (20 °C (68 °F))	0,97 g/cm <sup>3</sup>
Bulk density	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Solubility (qualitative) (Solvent: Water)	Not miscible
Solidification temperature	No data available / Not applicable
Melting point	No data available / Not applicable
Flammability	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Explosive limits	
lower	1,7 % (V)
upper	10,4 % (V)
Partition coefficient: n-octanol/water	No data available / Not applicable
Evaporation rate	No data available / Not applicable
Vapor density	No data available / Not applicable
Oxidising properties	No data available / Not applicable

**9.2. Other information**

No data available / Not applicable



**SECTION 10: Stability and reactivity****10.1. Reactivity**

Reaction with strong acids.  
Reacts with strong oxidants.

**10.2. Chemical stability**

Stable under recommended storage conditions.

**10.3. Possibility of hazardous reactions**

See section reactivity

**10.4. Conditions to avoid**

No decomposition if used according to specifications.

**10.5. Incompatible materials**

See section reactivity

**10.6. Hazardous decomposition products**

Irritating organic vapours.

**SECTION 11: Toxicological information****11.1. Information on toxicological effects****General toxicological information:**

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

**Oral toxicity:**

May cause irritation to the digestive tract.

**Inhalative toxicity:**

May cause respiratory irritation.  
Vapors may cause drowsiness and dizziness.

**Skin irritation:**

Solvent may remove essential oils from the skin making it susceptible to attack from other chemicals.  
Repeated exposure may cause skin dryness or cracking.

**Eye irritation:**

Causes serious eye irritation.

**Acute oral toxicity:**

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
n-Butyl acetate 123-86-4	LD50	> 8.800 mg/kg	oral		rat	BASF Test
4-Methylpentan-2-one 108-10-1	LD50	2.080 mg/kg	oral		rat	OECD Guideline 401 (Acute Oral Toxicity)

**Acute inhalative toxicity:**

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
n-Butyl acetate 123-86-4	LC50	> 23,4 mg/l	inhalation	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
4-Methylpentan-2-one 108-10-1	Acute toxicity estimate (ATE)	11 mg/l	inhalation			Expert judgement
4-Methylpentan-2-one 108-10-1	LC50	8,2 - 16,4 mg/l		4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)

**Acute dermal toxicity:**

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
4-Methylpentan-2-one 108-10-1	LD50	> 2.000 mg/kg	dermal		rat	OECD Guideline 402 (Acute Dermal Toxicity)

**Skin corrosion/irritation:**

Hazardous components CAS-No.	Result	Exposure time	Species	Method
n-Butyl acetate 123-86-4	not irritating		rabbit	BASF Test
4-Methylpentan-2-one 108-10-1	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

**Serious eye damage/irritation:**

Hazardous components CAS-No.	Result	Exposure time	Species	Method
n-Butyl acetate 123-86-4	not irritating		rabbit	BASF Test
4-Methylpentan-2-one 108-10-1	slightly irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

**Respiratory or skin sensitization:**

Hazardous components CAS-No.	Result	Test type	Species	Method
n-Butyl acetate 123-86-4	not sensitising	Guinea pig maximisation test	guinea pig	
4-Methylpentan-2-one 108-10-1	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

**Germ cell mutagenicity:**

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
n-Butyl acetate 123-86-4	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		Ames Test
4-Methylpentan-2-one 108-10-1	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)

**SECTION 12: Ecological information****General ecological information:**

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

**12.1. Toxicity****Ecotoxicity:**

Do not empty into drains / surface water / ground water.

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
n-Butyl acetate 123-86-4	LC50	62 mg/l	Fish	96 h	Leuciscus idus	DIN 38412-15
n-Butyl acetate 123-86-4	EC50	72,8 mg/l	Daphnia	24 h	Daphnia magna	
n-Butyl acetate 123-86-4	EC10	295,5 mg/l	Algae	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
	EC50	674,7 mg/l	Algae	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
4-Methylpentan-2-one 108-10-1	LC50	600 mg/l	Fish	96 h	Salmo gairdneri (new name: Oncorhynchus mykiss)	OECD Guideline 203 (Fish, Acute Toxicity Test)
4-Methylpentan-2-one 108-10-1	EC50	170 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
4-Methylpentan-2-one 108-10-1	EC50	400 mg/l	Algae	96 h	Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)

## 12.2. Persistence and degradability

### Persistence and Biodegradability:

The product is not biodegradable.

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
n-Butyl acetate 123-86-4	readily biodegradable	aerobic	98 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
4-Methylpentan-2-one 108-10-1	readily biodegradable	aerobic	99 %	OECD Guideline 301 E (Ready biodegradability: Modified OECD Screening Test)

## 12.3. Bioaccumulative potential / 12.4. Mobility in soil

### Mobility:

The product evaporates readily.

### Bioaccumulative potential:

No data available.

Hazardous components CAS-No.	LogKow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
n-Butyl acetate 123-86-4	1,81				23 °C	OECD Guideline 107 (Partition Coefficient (n- octanol / water), Shake Flask Method)
4-Methylpentan-2-one 108-10-1	1,31				20 °C	

## 12.5. Results of PBT and vPvB assessment

Hazardous components CAS-No.	PBT/vPvB
n-Butyl acetate 123-86-4	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
4-Methylpentan-2-one 108-10-1	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

## 12.6. Other adverse effects

No data available.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods**

Product disposal:

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

Disposal must be made according to official regulations.

Waste code

14 06 03 - other solvents and solvent mixtures

**SECTION 14: Transport information****14.1. UN number**

ADR	1993
RID	1993
ADNR	1993
IMDG	1993
IATA	1993

**14.2. UN proper shipping name**

ADR	FLAMMABLE LIQUID, N.O.S. (Methyl isobutyl ketone, Butylacetate)
RID	FLAMMABLE LIQUID, N.O.S. (Methyl isobutyl ketone, Butylacetate)
ADNR	FLAMMABLE LIQUID, N.O.S. (Methyl isobutyl ketone, Butylacetate)
IMDG	FLAMMABLE LIQUID, N.O.S. (Methyl isobutyl ketone, Butylacetate)
IATA	Flammable liquid, n.o.s. (Methyl isobutyl ketone, Butylacetate)

**14.3. Transport hazard class(es)**

ADR	3
RID	3
ADNR	3
IMDG	3
IATA	3

**14.4. Packaging group**

ADR	II
RID	II
ADNR	II
IMDG	II
IATA	II

**14.5. Environmental hazards**

ADR	not applicable
RID	not applicable
ADNR	not applicable
IMDG	not applicable
IATA	not applicable

**14.6. Special precautions for user**

ADR	Special provision 640D
-----	------------------------

RID	Tunnelcode: (D/E)
ADNR	Special provision 640D
IMDG	Special provision 640D
IATA	not applicable
	not applicable

**14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

VOC content 74,74 %  
(1999/13/EC)

**15.2. Chemical safety assessment**

A chemical safety assessment has not been carried out.

**SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

R10 Flammable.  
R11 Highly flammable.  
R20 Harmful by inhalation.  
R36/37 Irritating to eyes and respiratory system.  
R66 Repeated exposure may cause skin dryness or cracking.  
R67 Vapours may cause drowsiness and dizziness.  
H225 Highly flammable liquid and vapor.  
H226 Flammable liquid and vapor.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.

**Further information:**

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.