

Screened FTP Cat 7A LSZH Cable 1,200MHz

pro-POWER

RoHS
Compliant



Application:

Horizontal Wiring in LAN

Multi-Construction

: 4 Pair

Cable Construction

Conductor : Solid Bare Copper
Conductor Area CSA : 0.32mm²
Wire Size AWG : 22
Construction : 0.62 ±0.01
Standard Dia.(mm) : 0.62

Insulation

Average Thickness : 0.4
Insulation Dia.(mm) : 1.45 ±0.1 × 2C Twist
Al-Pet shield(on each pair, Al outward) : ≥115%
Braiding Shield : Tin-Plated Copper Wire
Construction : 0.12 ±0.003 × 8 × 6

Jacket

Jacket Material : Low Smoke Zero Halogen (LSZH)
Flame Retardant Polyethylene
Thickness(mm) : 0.7
Dia.(mm) : 8.2 ±0.3
Jacket Colour : Violet

Colour

Insulation colour are : Blue, White/Blue
Orange, White/Orange
Green, White/Green
Brown, White/Brown

Characteristics

Max. Conductor DC Resistance at 20°C (Ω/Km) : <66.6
Rated Temperature(°C) : 70
Velocity ratio : 78%
Impedance(Ω) : 1-100MHz 100 ±15
100-250MHz 100 ±20
250-500MHz 100 ±25
500-1,000MHz 100 ±30
1,000-1,200MHz 100 ±32


Screened FTP Cat 7A LSZH Cable 1,200MHz

pro-POWER

Performance:

Frequency (MHz)	Attenuation (dB)	NEXT (dB)	PS NEXT (dB)	Return loss (dB)	ELFEXT (dB)	PSELFEXT (dB)
1	2.1	78	75	20	78	75
4	3.7	78	75	23	78	75
10	5.8	78	75	25	75.3	72.3
16	7.3	78	75	25	71.2	68.2
31.25	10.3	78	75	23.6	65.4	62.4
62.5	14.6	78	75	21.5	59.4	56.4
100	18.5	75.4	72.4	20.1	55.3	52.3
250	29.7	69.4	66.4	17.3	47.3	44.3
500	42.8	64.9	61.9	17.3	41.3	38.3
600	47.1	63.7	60.7	17.3	39.7	36.7
900	58.5	61.1	58.1	15.5	36.2	33.2
1,000	61.9	60.4	57.4	15.1	35.3	32.3
1,200	68.4	59.2	56.2	14.3	33.7	30.7

Design:



Part Number Table

Description	Part Number
Cable, MULTIPR, 4PR, CAT 7A, LSZH, VLT, 100m	PP000430
Cable, MULTIPR, 4PR,, CAT 7A, LSZH, VLT, 500m	PP000431

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com
www.farnell.com
www.newark.com
www.cpc.co.uk

pro-POWER