

REGAL WEALTH ENGINEERING LIMITED

ADD: SUZHOU REPRESENTATIVE OFFICE, 0203A1 1A SINGA PLAZA JINJIHU ROAD SUZHOU INDUSTRIAL PARK, P.R. CHINA

TEL: 86-512-62532393 FAX:86-512-62532690

Type:	2X2.5mm ² PRO SPEAKER CABLE(XLPE)	Part No. : SPC151	
Spec. :	(7*46/0.10BC+XLPE3.3)*2C+COTTON YARN+NONWOVEN FABRIC+PVC8.7		
Construction:			
Conductor	Construction:	7*46/0.10mm (BC OFC)	
	DC Resistance(Max. at 20℃):	7.521 Ω /km	
Insulation	Material:	XLPE	
	Color:	BLACK, RED	
	Diameter/Thickness:	3.3±0.10mm / 0.61 0.475mm	
Filler	Material:	COTTON YARN	
Drain Wire	Construction:	/	
Wrap	Material:	NONWOVEN FABRIC	
Shield	Construction:	/	
	Coverage:	/	
Covering	Material:	/	
	Diameter:	/	
Jacket	Material:	PVC	
	Color:	BLUE	
	Diameter/Thickness:	8.7±0.20mm / 0.93 0.69mm	
Marking:	2X2.5mm ² PROFESSIONAL SPEAKER CABLE		
Performance:			
Physical Properties	Jacket	Swing Test:	≥2000
		Tensile Strength(Mpa):	≥10.5
		Elongation	≥150%
	INSULATION	Swing Test:	/
		Tensile Strength(Mpa):	/
		Elongation	/
Electrical Performance	Capacitance pF/m	/	
	Characteristic Impedance(Ω):	/	
	RTED TEMPERATURE °C		
	VOITAGE V/DC	300	
	Withstand Voltage(KV AC/Min):	2	
	Frequency(MHZ)	/	
	Attenuation(DB/M)	/	
Drawing:			
			