

UL1015 - 10AWG PVC Hook-Up Wire

152.5m reel

pro-POWER



Specifications:

Description	: 10AWG (105/0.254mm) tinned copper, heat resisting PVC insulated
	: UL style 1015 (105°C in air, 600V)
Conductors	: 10AWG (105/0.254mm-105×30AWG) tinned annealed copper
	: Minimum cross-sectional area : 5.103mm ²
	: Maximum lay of bunch : 63.5mm
Jacket	: PVC
	: Minimum thickness at any one point : 0.69mm
	: Minimum average thickness : 0.76mm
	: Nominal overall diameter : 5mm
Service Data	: For use as the internal wiring of apparatus
	: Maximum voltage rating : 600V AC, 750V DC
	: Maximum temperature rating : 105°C
	: Maximum current rating : at 20°C : 76A
	: : at 30°C : 70A
	: : at 40°C : 64A
	: Approximate mass/unit length : 65.7kg/km

Part Number Table

Description	Colour	Reel Length (m)	Part Number
10AWG 105/30 UL1015	Black	152.5	PP000196

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com
www.farnell.com
www.newark.com
www.cpc.co.uk

pro-POWER