

# Type MPX Polypropylene Film Capacitors

## Metallized Box Style, Vac Rated



## Interference Suppression and Across-the-Line VAC Applications

The Type MPX metallized, polypropylene class X2 film capacitors are ideal for across-the-line and interference suppression circuit applications. This series features the self-healing capabilities associated with metallized polypropylene, compact design, and flame retardant construction. Tape and reel packaging are available for ratings with a pitch of 10 mm to 32.5 mm.



Complies with the EU Directive 2002/95/EC requirement restricting the use of Lead (Pb), Mercury (Hg), Cadmium (Cd), Hexavalent chromium (Cr(VI)), PolyBrominated Biphenyls (PBB) and PolyBrominated Diphenyl Ethers (PBDE).

## Specifications

**Voltage Range:** 250 Vac, 60 Hz 275 Vac, 60 Hz

**Capacitance Range:** .0047– 2.2  $\mu$ F  
(.0047 – 1.0  $\mu$ F)


**Capacitance Tolerance:**  $\pm$ 10% (K) standard  
 $\pm$ 5% (J)

**Operating Temperature Range:** –40 °C to +100 °C

**Dielectric Strength:** 2100 Vdc (1 minute)

**Dissipation Factor:** .10% Max. (25°C, 1kHz)

**Insulation Resistance:** 10,000 mOhms x  $\mu$ F min.,  
not to exceed 30,000 mOhms min.



## Ratings

Cap. ( $\mu$ F)	Catalog Part Number	T $\pm$ .020 (0.5) Inches (mm)	H $\pm$ .020 (0.5) Inches (mm)	L $\pm$ .020 (0.5) Inches (mm)	S $\pm$ .040 (1.0) Inches (mm)	d Inches (mm)	dV/dt V/ $\mu$ s
<b>275 Vac</b>							
0.0047	MPXQD47K	.197 (5.0)	.433 (11.0)	.512 (13.0)	.394 (10.0)	.024 (.6)	100
0.0068	MPXQD68K	.197 (5.0)	.433 (11.0)	.512 (13.0)	.394 (10.0)	.024 (.6)	100
0.010	MPXQS1K	.197 (5.0)	.433 (11.0)	.512 (13.0)	.394 (10.0)	.024 (.6)	100
0.015	MPXQS15K	.197 (5.0)	.433 (11.0)	.512 (13.0)	.394 (10.0)	.024 (.6)	100
0.022	MPXQS22K	.197 (5.0)	.433 (11.0)	.512 (13.0)	.394 (10.0)	.024 (.6)	100
0.033	MPXQS33K	.236 (6.0)	.472 (12.0)	.512 (13.0)	.394 (10.0)	.024 (.6)	100
0.047	MPXQS47K	.197 (5.0)	.433 (11.0)	.709 (18.0)	.591 (15.0)	.032 (.8)	45
0.068	MPXQS68K	.236 (6.0)	.472 (12.0)	.709 (18.0)	.591 (15.0)	.032 (.8)	45
0.100	MPXQP1K	.236 (6.0)	.531 (13.5)	.709 (18.0)	.591 (15.0)	.032 (.8)	45
0.150	MPXQP15K	.335 (8.5)	.571 (14.5)	.709 (18.0)	.591 (15.0)	.032 (.8)	45
0.220	MPXQP22K	.276 (7.0)	.650 (16.5)	1.043 (26.5)	.886 (22.5)	.032 (.8)	25
0.330	MPXQP33K	.335 (8.5)	.669 (17.0)	1.043 (26.5)	.886 (22.5)	.032 (.8)	25
0.47	MPXQP47K	.394 (10.0)	.748 (19.0)	1.043 (26.5)	.886 (22.5)	.032 (.8)	25
0.560	MPXQP56K	.433 (11.0)	.787 (20.0)	1.260 (32.0)	1.083 (27.5)	.032 (.8)	20
0.680	MPXQP68K	.433 (11.0)	.787 (20.0)	1.260 (32.0)	1.083 (27.5)	.032 (.8)	20
1.000	MPXQW1K	.551 (14.0)	.984 (25.0)	1.260 (32.0)	1.083 (27.5)	.032 (.8)	20
1.200	MPXQW1P2K	.590 (15.0)	1.181 (30.0)	1.260 (32.0)	1.083 (27.5)	.032 (.8)	20
1.500	MPXQW1P5K	.590 (15.0)	1.181 (30.0)	1.260 (32.0)	1.083 (27.5)	.032 (.8)	20
1.800	MPXQW1P8K	.748 (19.0)	1.42 (29.0)	1.457 (37.0)	1.280 (32.5)	.032 (.8)	16
2.200	MPXQW2P2K	.748 (19.0)	1.42 (29.0)	1.457 (37.0)	1.280 (32.5)	.032 (.8)	16

## Type MPX Polypropylene Film Capacitors

---

**Notice and Disclaimer:** All product drawings, descriptions, specifications, statements, information and data (collectively, the "Information") in this datasheet or other publication are subject to change. The customer is responsible for checking, confirming and verifying the extent to which the Information contained in this datasheet or other publication is applicable to an order at the time the order is placed. All Information given herein is believed to be accurate and reliable, but it is presented without any guarantee, warranty, representation or responsibility of any kind, expressed or implied. Statements of suitability for certain applications are based on the knowledge that the Cornell Dubilier company providing such statements ("Cornell Dubilier") has of operating conditions that such Cornell Dubilier company regards as typical for such applications, but are not intended to constitute any guarantee, warranty or representation regarding any such matter – and Cornell Dubilier specifically and expressly disclaims any guarantee, warranty or representation concerning the suitability for a specific customer application, use, storage, transportation, or operating environment. The Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by Cornell Dubilier with reference to the use of any Cornell Dubilier products is given gratis (unless otherwise specified by Cornell Dubilier), and Cornell Dubilier assumes no obligation or liability for the advice given or results obtained. Although Cornell Dubilier strives to apply the most stringent quality and safety standards regarding the design and manufacturing of its products, in light of the current state of the art, isolated component failures may still occur. Accordingly, customer applications which require a high degree of reliability or safety should employ suitable designs or other safeguards (such as installation of protective circuitry or redundancies or other appropriate protective measures) in order to ensure that the failure of an electrical component does not result in a risk of personal injury or property damage. Although all product-related warnings, cautions and notes must be observed, the customer should not assume that all safety measures are indicated in such warnings, cautions and notes, or that other safety measures may not be required.