

# MULL6060-300

**UNCONTROLLED DOCUMENT**



PHYSICAL DIMENSIONS:

A	60.0[2.362]	+	1.50[.059]
B	60.0[2.362]	+	1.50[.059]
C	0.05[.002]	+	0.01[.0004]
D	0.09[.004]		MAX



ELECTRICAL CHARACTERISTICS:	
Initial Permeability ( $\mu'$ ) (13.56MHz)	150±20%
Initial Permeability ( $\mu''$ ) (13.56MHz)	5 Max

**PRODUCTS SHAPE AND DIMENSIONS**



MEASURED BY ANGILENT E4991A , 1Ts .

NOTES: UNLESS OTHERWISE SPECIFIED

1. OPERATING TEMPERATURE RANGE -40°C TO 85°C.
2. FLEXIBLE FERRITE SHEET.
3. D IS MEASURED AFTER REMOVING PAPER LINER OF ADHESIVE

DIMENSIONS ARE IN mm [INCHES].				This print is the property of Laird Tech. and is loaned in confidence subject to return upon request and with the understanding that no copies shall be made without the written consent of Laird Tech. All rights to design or invention are reserved.			
				<b>Laird</b>			
				PROJECT/PART NUMBER:	REV	PART TYPE:	DRAWN BY:
				MULL6060-300		A	CO-FIRE QU
				DATE:	SCALE:	SHEET:	
				10/08/14	NTS	1 of 1	
A	ORIGINAL DRAFT	10/08/14	QU	CAD #			
REV	DESCRIPTION	DATE	INT	MULL6060-300-A	TOOL #		