



# BRD.0B.200.PCSG

## MECHANICAL DETAILS

**Shell Style Model** BRD\* : Cap for free receptacle  
**Keying** No keying  
**Housing Material** POM (Polyoxymethylene) shell without treatment, silicone gasket  
**Cable Fixing** 0 - 0 mm  
**Variant 2** :

	Col	Col	Col	Col	Col	Col	Col	Col
Mm.								
In.								

## PERFORMANCE DETAIL

**Insert** :  
**Insulator**  
**Insulator**

## OTHER CHARACTERISTICS

**Endurance (Shell)** Endurance (Shell):  
**Temp (min)** -55°C  
**Temp (max)** +250°C  
**Humidity (max):** <=95% [at 60 deg C /140 F]  
**Vibration:** 15 g [10 Hz - 2000 Hz]  
**Shock Resistance:** 100 g [ 6 ms]  
**Salt Spray** >144 hr  
**Climatical** 50/175/21  
**Shielding (min):** 75 dB (10 MHz)  
**Shielding (min):** 40 dB (1 GHz)  
**IP Rating** 50

## Available Download

unipole\_multipole.pdf

## Related links

- [Contact](#)
- [Quote Request](#)
- [Catalogs Downloads](#)
- [Catalogs Requests](#)
- [Sample Request](#)
- [3D drawings](#)