



FVN.1S.304.CLYC37Z

(Not Recommended for New Design)

MECHANICAL DETAILS

Shell Style Model * :

Keying

Housing Material Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces

Cable Fixing 3.2 - 4.2 mm

Variant 2 Z : Nut for fitting a bend relief

	Col	Col	Col	Col	Col	Col	Col	Col
Mm.								
In.								

PERFORMANCE DETAIL

Insert 1S.304 : 4 Low Voltage

Insulator L: PEEK

Specifications

Contact Type: Special

OTHER CHARACTERISTICS

Endurance (Shell) Endurance (Shell):

Temp (min) -55°C

Temp (max) +250°C

Humidity (max): <=95% [at 60 deg C /140 F]

Vibration: 15 g [10 Hz - 2000 Hz]

Shock Resistance: 100 g [6 ms]

Salt Spray >144 hr

Climatical 50/175/21

Shielding (min): 75 dB (10 MHz)

Shielding (min): 40 dB (1 GHz)

IP Rating 50

Available Download

unipole_multipole.pdf

Related links

- [Contact](#)
- [Quote Request](#)
- [Catalogs Downloads](#)
- [Catalogs Requests](#)
- [Sample Request](#)
- [3D drawings](#)