

Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 12

sds no.: 173363

V002.5 Revision: 21.11.2013

printing date: 15.12.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE 4105 INST ADH 1LB.

Contains:

Ethyl 2-cyanoacrylate

LOCTITE 4105 INST ADH 1LB.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Adhesive

1.3. Details of the supplier of the safety data sheet

Henkel Limited

2 Bishop Square Business Park AL109EY Herfordshire Hatfield

Great Britain

Phone: +44 1606 593933 Fax-no.: +44 1606 863762

ua-products a fety.uk@uk.henkel.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Skin irritation Category 2

H315 Causes skin irritation.

Serious eye irritation Category 2

H319 Causes serious eye irritation.

Specific target organ toxicity - single exposure Category 3

H335 May cause respiratory irritation. Target organ: Respiratory tract irritation

Classification (DPD):

Xi - Irritant

R36/37/38 Irritating to eyes, respiratory system and skin.

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Signal word: Warning

Hazard statement: H315 Causes skin irritation.

H319 Causes serious eye irritation. H335 May cause respiratory irritation.

Supplemental information EUH202 Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of

children.

Contains Hydroquinone; Phthalic anhydride. May produce an allergic reaction.

Precautionary statement: P261 Avoid breathing vapors.

Prevention P280 Wear protective gloves/eye protection.

Precautionary statement: P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

Precautionary statement: P501 Dispose of waste and residues in accordance with local authority requirements.

Disposal

Response

Label elements (DPD):

Xi - Irritant



Risk phrases:

R36/37/38 Irritating to eyes, respiratory system and skin.

Safety phrases:

S23 Do not breathe vapour.

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Additional labeling:

Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.

Contains Phthalic anhydride, Hydroquinone. May produce an allergic reaction.

2.3. Other hazards

None if used properly.

SECTION 3: Composition/information on ingredients

General chemical description:

Cyanoacrylate Adhesive

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Ethyl 2-cyanoacrylate 7085-85-0	230-391-5 01-2119527766-29	>= 80- < 100 %	Serious eye irritation 2 H319 Specific target organ toxicity - single exposure 3 H335 Skin irritation 2 H315
Hydroquinone 123-31-9	204-617-8	>= 0,1-< 0,5 %	Carcinogenicity 2 H351 Germ cell mutagenicity 2 H341 Acute toxicity 4; Oral H302 Serious eye damage 1 H318 Skin sensitizer 1 H317 Acute hazards to the aquatic environment 1 H400 M factor: 10 M factor (Chron Aquat Tox): 10
Phthalic anhydride 85-44-9	201-607-5	>= 0,1-< 0,5 %	Acute toxicity 4; Oral H302 Specific target organ toxicity - single exposure 3 H335 Skin irritation 2 H315 Serious eye damage 1 H318 Respiratory sensitizer 1 H334 Skin sensitizer 1 H317

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

Declaration of ingredients according to DPD (EC) No 1999/45:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Ethyl 2-cyanoacrylate 7085-85-0	230-391-5 01-2119527766-29	>= 80 - < 100 %	Xi - Irritant; R36/37/38
Hydroquinone 123-31-9	204-617-8	>= 0,1 -< 0,5 %	Xi - Irritant; R41 Mutagen category 3.; R68 N - Dangerous for the environment; R50 carcinogenic, category 3; R40 Xn - Harmful; R22 R43
Phthalic anhydride 85-44-9	201-607-5	>= 0,1 - < 0,5 %	Xi - Irritant; R37/38, R41 Xn - Harmful; R22 R42/43

For full text of the R-Phrases indicated by codes see section 16 'Other Information'. Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Do not pull bonded skin apart. It may be gently peeled apart using a blunt object such as a spoon, preferably after soaking in warm soapy water.

Cyanoacrylates give off heat on solidification. In rare cases a large drop will generate enough heat to cause a burn.

Burns should be treated normally after the adhesive has been removed from the skin.

If lips are accidentally stuck together apply warm water to the lips and encourage maximum wetting and pressure from saliva inside the mouth.

Peel or roll lips apart. Do not try to pull the lips apart with direct opposing action.

Eye contact:

If the eye is bonded closed, release eyelashes with warm water by covering with wet pad.

Cyanoacrylate will bond to eye protein and will cause periods of weeping which will help to debond the adhesive.

Keep eye covered until debonding is complete, usually within 1-3 days.

Do not force eye open. Medical advice should be sought in case solid particles of cyanoacrylate trapped behind the eyelid cause any abrasive damage.

Ingestion:

Ensure that breathing passages are not obstructed. The product will polymerise immediately in the mouth making it almost impossible to swallow. Saliva will slowly separate the solidified product from the mouth (several hours).

4.2. Most important symptoms and effects, both acute and delayed

EYE: Irritation, conjunctivitis.

SKIN: Redness, inflammation.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Foam, extinguishing powder, carbon dioxide.

Fine water spray

Extinguishing media which must not be used for safety reasons:

None known

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.

5.3. Advice for firefighters

Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA).

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Avoid skin and eye contact.

6.2. Environmental precautions

Do not let product enter drains.

6.3. Methods and material for containment and cleaning up

Do not use cloths for mopping up. Flood with water to complete polymerization and scrape off the floor. Cured material can be disposed of as non-hazardous waste.

6.4. Reference to other sections

See advice in chapter 8

V002.5

MSDS-No.: 173363

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Ventilation (low level) is recommended when using large volumes

Use of dispensing equipment is recommended to minimise the risk of skin or eye contact

Hygiene measures:

Good industrial hygiene practices should be observed.

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.

For optimum shelf life store in original containers under refrigerated conditions at 2 - 8°C (35.6 - 46.4 °F)

7.3. Specific end use(s)

Adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for

Great Britain

Ingredient	ppm	mg/m ³	Type	Category	Remarks
ETHYL CYANOACRYLATE	0,3	1,5	Short Term Exposure		EH40 WEL
7085-85-0			Limit (STEL):		
HYDROQUINONE		0,5	Time Weighted Average		EH40 WEL
123-31-9			(TWA):		
PHTHALIC ANHYDRIDE		12	Short Term Exposure		EH40 WEL
85-44-9			Limit (STEL):		
PHTHALIC ANHYDRIDE		4	Time Weighted Average	_	EH40 WEL
85-44-9			(TWA):		

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Ethyl 2-cyanoacrylate 7085-85-0	worker	inhalation	Long term exposure - local effects		9,25 mg/m3	
Ethyl 2-cyanoacrylate 7085-85-0	worker	inhalation	Long term exposure - systemic effects		9,25 mg/m3	
Ethyl 2-cyanoacrylate 7085-85-0	general population	inhalation	Long term exposure - local effects		9,25 mg/m3	
Ethyl 2-cyanoacrylate 7085-85-0	general population	inhalation	Long term exposure - systemic effects		9,25 mg/m3	

Biological Exposure Indices:

None

8.2. Exposure controls:

V002.5

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A

Hand protection:

The use of chemical resistant gloves such as Nitrile is recommended.

Polyethylene or polypropylene gloves are recommended when using large volumes.

Do not use PVC, rubber or nylon gloves.

Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Wear protective glasses.

Skin protection:

Wear suitable protective clothing.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Liquid

black

Odor Irritating

Odour threshold No data available / Not applicable

pH No data available / Not applicable

Initial boiling point $> 149 \,^{\circ}\text{C} (> 300.2 \,^{\circ}\text{F})$

Flash point 80 - 93,3 °C (176 - 199.94 °F); Tagliabue closed cup

Decomposition temperature No data available / Not applicable

Vapour pressure < 0,6 mbar

(25 °C (77 °F))

Density 1,1 g/cm³

(20 °C (68 °F))

Bulk density

No data available / Not applicable
Viscosity

No data available / Not applicable
Viscosity (kinematic)

No data available / Not applicable
Explosive properties

No data available / Not applicable
No data available / Not applicable
Polymerises in presence of water.

(Solvent: Water)

Solidification temperature No data available / Not applicable Melting point No data available / Not applicable Flammability No data available / Not applicable No data available / Not applicable Auto-ignition temperature Explosive limits No data available / Not applicable No data available / Not applicable Partition coefficient: n-octanol/water Evaporation rate No data available / Not applicable Vapor density No data available / Not applicable No data available / Not applicable Oxidising properties

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

Rapid exothermic polymerization will occur in the presence of water, amines, alkalis and alcohols.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

No decomposition if used according to specifications.

10.5. Incompatible materials

See section reactivity

10.6. Hazardous decomposition products

carbon oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

General toxicological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Oral toxicity:

Cyanoacrylates are considered to have relatively low toxicity. Acute oral LD50 is >5000mg/kg (rat). It is almost impossible to swallow as it rapidly polymerises in the mouth.

Inhalative toxicity:

May cause respiratory irritation.

Prolonged exposure to high concentrations of vapours may lead to chronic effects in sensitive individuals In dry atmosphere with < 50% humidity, vapours may irritate the eyes and respiratory system

Skin irritation:

Causes skin irritation.

Bonds skin in seconds. Considered to be of low toxicity: acute dermal LD50 (rabbit)>2000mg/kg Due to polymerisation at the skin surface allergic reaction is unlikely to occur

Eye irritation:

Causes serious eye irritation.

Liquid product will bond eyelids. In a dry atmosphere (RH<50%) vapours may cause irritation and lachrymatory effect

Sensitizing:

May cause allergic reaction.

Acute oral toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Ethyl 2-cyanoacrylate 7085-85-0	LD50	> 5.000 mg/kg	oral		rat	OECD Guideline 401 (Acute Oral Toxicity)
Hydroquinone 123-31-9	LD50	367 mg/kg	oral		rat	OECD Guideline 401 (Acute Oral Toxicity)
Phthalic anhydride 85-44-9	LD50	2.500 - 5.000 mg/kg	oral		rat	
Phthalic anhydride 85-44-9	LD50	1.530 mg/kg			rat	

Acute dermal toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Ethyl 2-cyanoacrylate 7085-85-0	LD50	> 2.000 mg/kg	dermal		rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Phthalic anhydride 85-44-9	LD50	> 10.000 mg/kg	dermal		rabbit	

MSDS-No.: 173363

Skin corrosion/irritation:

Hazardous components	Result	Exposure	Species	Method
CAS-No.		time		
Ethyl 2-cyanoacrylate	slightly irritating	24 h	rabbit	OECD Guideline 404 (Acute
7085-85-0				Dermal Irritation / Corrosion)

Serious eye damage/irritation:

Hazardous components	Result	Exposure	Species	Method
CAS-No.		time		
Ethyl 2-cyanoacrylate	irritating	72 h	rabbit	OECD Guideline 405 (Acute
7085-85-0				Eye Irritation / Corrosion)
Phthalic anhydride	highly irritating		rabbit	
85-44-9				

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
Ethyl 2-cyanoacrylate 7085-85-0	not sensitising		guinea pig	
Hydroquinone 123-31-9	sensitising	Guinea pig maximisat ion test	guinea pig	
Phthalic anhydride 85-44-9	sensitising	Mouse local lymphnod e assay (LLNA)	mouse	
Phthalic anhydride 85-44-9	sensitising		guinea pig	

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Ethyl 2-cyanoacrylate 7085-85-0	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
	negative	bacterial reverse mutation assay (e.g Ames test)			OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Hydroquinone 123-31-9	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		EU Method B.13/14 (Mutagenicity)
Phthalic anhydride 85-44-9	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		

Repeated dose toxicity

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Hydroquinone		oral: gavage		rat	OECD Guideline 407
123-31-9	mg/kg		12 doses		(Repeated Dose 28-Day Oral
					Toxicity in Rodents)

SECTION 12: Ecological information

General ecological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

12.1. Toxicity

Ecotoxicity:

Do not empty into drains / surface water / ground water.

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Hydroquinone 123-31-9	LC50	0,17 mg/l	Fish	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
Hydroquinone 123-31-9	EC50	0,29 mg/l	Daphnia	48 h	Daphnia magna	
Hydroquinone 123-31-9	EC50	0,335 mg/l	Algae	3 d	Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Phthalic anhydride 85-44-9	LC50	313 mg/l	Fish	48 h	Leuciscus idus	

12.2. Persistence and degradability

Persistence and Biodegradability:

The product is not biodegradable.

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
Ethyl 2-cyanoacrylate 7085-85-0		aerobic	57 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Hydroquinone 123-31-9	readily biodegradable	aerobic	75 - 81 %	EU Method C.4-E (Determination of the "Ready" BiodegradabilityClosed Bottle Test)
Phthalic anhydride 85-44-9		aerobic	90 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)

12.3. Bioaccumulative potential / 12.4. Mobility in soil

Mobility:

Cured adhesives are immobile.

Bioaccumulative potential:

No data available.

Hazardous components	LogKow	Bioconcentration	Exposure	Species	Temperature	Method
CAS-No.		factor (BCF)	time			
Ethyl 2-cyanoacrylate	0,776				22 °C	EU Method A.8 (Partition
7085-85-0						Coefficient)
Hydroquinone	1,03					
123-31-9						
Phthalic anhydride	1,6					
85-44-9						

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Cured adhesive: Dispose of as water insoluble non-toxic solid chemical in authorised landfill or incinerate under controlled conditions.

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

14.1. UN number

ADR	Not dangerous goods
RID	Not dangerous goods
ADNR	Not dangerous goods
IMDG	Not dangerous goods
IATA	3334

14.2. UN proper shipping name

ADR	Not dangerous goods
RID	Not dangerous goods
ADNR	Not dangerous goods
IMDG	Not dangerous goods

IATA Aviation regulated liquid, n.o.s. (Cyanoacrylate ester)

14.3. Transport hazard class(es)

ADR	Not dangerous goods
RID	Not dangerous goods
ADNR	Not dangerous goods
IMDG	Not dangerous goods

IATA 9

14.4. Packaging group

ADR	Not dangerous goods
RID	Not dangerous goods
ADNR	Not dangerous goods
IMDG	Not dangerous goods

IATA III

14.5. Environmental hazards

not applicable
not applicable
not applicable
not applicable
not applicable

14.6. Special precautions for user

ADR not applicable

MSDS-No.: 173363 LOCTITE 4105 INST ADH 1LB. Page 11 of 12

V002.5

RID not applicable ADNR not applicable IMDG not applicable

IATA Primary packs containing less than 500ml are unregulated by this mode of transport

and may be shipped unrestricted.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content < 3 % (1999/13/EC)

15.2. Chemical safety assessment

A chemical safety assessment has been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

R22 Harmful if swallowed.

R36/37/38 Irritating to eyes, respiratory system and skin.

R37/38 Irritating to respiratory system and skin.

R40 Limited evidence of a carcinogenic effect.

R41 Risk of serious damage to eyes.

R42/43 May cause sensitization by inhalation and skin contact.

R43 May cause sensitisation by skin contact.

R50 Very toxic to aquatic organisms.

R68 Possible risk of irreversible effects.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H341 Suspected of causing genetic defects.

H351 Suspected of causing cancer.

H400 Very toxic to aquatic life.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Annex - Exposure Scenarios:

Exposure Scenarios for ethyl 2-cyanoacrylate can be downloaded under the following link:

http://mymsds.henkel.com/mymsds/.470833..en.ANNEX_DE.15743123.0.DE.pdf

Alternatively they can be accessed on the internet site www.mymsds.henkel.com by entering number 470833.

MSDS-No.: 173363 LOCTITE 4105 INST ADH 1LB.

V002.5

Page 12 of 12