

Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 11

Loctite 406

sds no. : 422581 V002.1 Revision: 18.11.2013 printing date: 17.12.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier Loctite 406

Contains:

Ethyl 2-cyanoacrylate

1.2. Relevant identified uses of the substance or mixture and uses advised against Intended use:

Adhesive

1.3. Details of the supplier of the safety data sheet

Henkel Limited 2 Bishop Square Business Park AL109EY Herfordshire Hatfield

Great Britain

Phone: +44 1606 593933 Fax-no.: +44 1606 863762

ua-productsafety.uk@uk.henkel.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Skin irritation	Category 2
H315 Causes skin irritation.	
Serious eye irritation	Category 2
H319 Causes serious eye irritation.	
Specific target organ toxicity - single exposure	Category 3
H335 May cause respiratory irritation.	
Target organ: Respiratory tract irritation	

Classification (DPD):

Xi - Irritant R36/37/38 Irritating to eyes, respiratory system and skin.

2.2. Label elements

Label elements (CLP):

Hazard pictogram:	
Signal word:	Warning
Hazard statement:	H315 Causes skin irritation. H319 Causes serious eye irritation. H335 May cause respiratory irritation.
Supplemental information	EUH202 Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.
Precautionary statement: Prevention	P261 Avoid breathing vapors. P280 Wear protective gloves/eye protection.
Precautionary statement: Response	P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 If eye irritation persists: Get medical advice/attention.
Precautionary statement: Disposal	P501 Dispose of waste and residues in accordance with local authority requirements.

Label elements (DPD):

Xi - Irritant



Risk phrases:

R36/37/38 Irritating to eyes, respiratory system and skin.

Safety phrases:

S23 Do not breathe vapour.

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Additional labeling:

Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.

2.3. Other hazards

None if used properly.

SECTION 3: Composition/information on ingredients

General chemical description: Cyanoacrylate Adhesive

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components	EC Number	content	Classification
CAS-No.	REACH-Reg No.		
Ethyl 2-cyanoacrylate 7085-85-0	230-391-5 01-2119527766-29	> 80-<100 %	Serious eye irritation 2 H319
	01 211/02//00 2/		Specific target organ toxicity - single
			exposure 3
			H335
			Skin irritation 2
			H315
Hydroquinone	204-617-8	> 0,01-< 0,1 %	Carcinogenicity 2
123-31-9			H351
			Germ cell mutagenicity 2
			H341
			Acute toxicity 4; Oral
			H302
			Serious eye damage 1
			H318
			Skin sensitizer 1
			H317
			Acute hazards to the aquatic environment 1
			H400
			M factor: 10 M factor (Chron Aquat Tox): 10

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

Declaration of ingredients according to DPD (EC) No 1999/45:

Hazardous components	EC Number	content	Classification
CAS-No.	REACH-Reg No.		
Ethyl 2-cyanoacrylate	230-391-5	> 80 - < 100 %	Xi - Irritant; R36/37/38
7085-85-0	01-2119527766-29		
Hydroquinone	204-617-8	> 0,01 - < 0,1 %	Xi - Irritant; R41
123-31-9			Mutagen category 3.; R68
			N - Dangerous for the environment; R50
			carcinogenic, category 3; R40
			Xn - Harmful; R22
			R43

For full text of the R-Phrases indicated by codes see section 16 'Other Information'. Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Do not pull bonded skin apart. It may be gently peeled apart using a blunt object such as a spoon, preferably after soaking in warm soapy water.

Cyanoacrylates give off heat on solidification. In rare cases a large drop will generate enough heat to cause a burn.

Burns should be treated normally after the adhesive has been removed from the skin.

If lips are accidentally stuck together apply warm water to the lips and encourage maximum wetting and pressure from saliva inside the mouth.

Peel or roll lips apart. Do not try to pull the lips apart with direct opposing action.

Eye contact:

If the eye is bonded closed, release eyelashes with warm water by covering with wet pad.

Cyanoacrylate will bond to eye protein and will cause periods of weeping which will help to debond the adhesive.

Keep eye covered until debonding is complete, usually within 1-3 days.

Do not force eye open. Medical advice should be sought in case solid particles of cyanoacrylate trapped behind the eyelid cause any abrasive damage.

Ingestion:

Ensure that breathing passages are not obstructed. The product will polymerise immediately in the mouth making it almost impossible to swallow. Saliva will slowly separate the solidified product from the mouth (several hours).

4.2. Most important symptoms and effects, both acute and delayed

EYE: Irritation, conjunctivitis.

SKIN: Redness, inflammation.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

4.3. Indication of any immediate medical attention and special treatment needed See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Foam, extinguishing powder, carbon dioxide.

Fine water spray

5.2. Special hazards arising from the substance or mixture

Oxides of carbon, oxides of nitrogen, irritating organic vapors.

5.3. Advice for firefighters

Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA).

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation.

6.2. Environmental precautions

Do not let product enter drains.

6.3. Methods and material for containment and cleaning up

Do not use cloths for mopping up. Flood with water to complete polymerization and scrape off the floor. Cured material can be disposed of as non-hazardous waste.

6.4. Reference to other sections

See advice in chapter 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Ventilation (low level) is recommended when using large volumes Use of dispensing equipment is recommended to minimise the risk of skin or eye contact

Hygiene measures:

Good industrial hygiene practices should be observed. Do not eat, drink or smoke while working.

Wash hands before work breaks and after finishing work.

7.2. Conditions for safe storage, including any incompatibilities

For optimum shelf life store in original containers under refrigerated conditions at 2 - 8°C (35.6 - 46.4 °F)

7.3. Specific end use(s)

Adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for

Great Britain

Ingredient	ppm	mg/m ³	Туре	Category	Remarks
ETHYL CYANOACRYLATE	0,3	1,5	Short Term Exposure		EH40 WEL
7085-85-0			Limit (STEL):		
HYDROQUINONE		0,5	Time Weighted Average		EH40 WEL
123-31-9			(TWA):		

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Ethyl 2-cyanoacrylate 7085-85-0	worker	inhalation	Long term exposure - local effects		9,25 mg/m3	
Ethyl 2-cyanoacrylate 7085-85-0	worker	inhalation	Long term exposure - systemic effects		9,25 mg/m3	
Ethyl 2-cyanoacrylate 7085-85-0	general population	inhalation	Long term exposure - local effects		9,25 mg/m3	
Ethyl 2-cyanoacrylate 7085-85-0	general population	inhalation	Long term exposure - systemic effects		9,25 mg/m3	

Biological Exposure Indices: None

8.2. Exposure controls:

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A

Hand protection:

The use of chemical resistant gloves such as Nitrile is recommended.

Polyethylene or polypropylene gloves are recommended when using large volumes.

Do not use PVC, rubber or nylon gloves.

Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Wear protective glasses.

Skin protection:

Wear suitable protective clothing.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

liquid colourless to yellowish irritating

Odour threshold

Initial boiling point

Vapour pressure

Viscosity (kinematic)

Explosive properties

Solubility (qualitative)

(Solvent: Water) Solidification temperature

Auto-ignition temperature

Decomposition temperature

Flash point

Bulk density Viscosity

Melting point

Flammability

Explosive limits

Evaporation rate

Vapor density

Density

pН

No	data	availa	ble /	No	ot appl	licab	le
----	------	--------	-------	----	---------	-------	----

No data available / Not applicable No data available / Not applicable 80 - 93,4 °C (176 - 200.12 °F) No data available / Not applicable Polymerises in presence of water.

No data available / Not applicable No data available / Not applicable

9.2. Other information

Oxidising properties

No data available / Not applicable

Partition coefficient: n-octanol/water

SECTION 10: Stability and reactivity

10.1. Reactivity

Rapid exothermic polymerization will occur in the presence of water, amines, alkalis and alcohols.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use.

10.5. Incompatible materials

None if used properly.

10.6. Hazardous decomposition products

None if used for intended purpose.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

General toxicological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Oral toxicity:

Cyanoacrylates are considered to have relatively low toxicity. Acute oral LD50 is >5000mg/kg (rat). It is almost impossible to swallow as it rapidly polymerises in the mouth.

Inhalative toxicity:

May cause respiratory irritation.

Prolonged exposure to high concentrations of vapours may lead to chronic effects in sensitive individuals In dry atmosphere with < 50% humidity, vapours may irritate the eyes and respiratory system

Skin irritation:

Causes skin irritation.

Bonds skin in seconds. Considered to be of low toxicity: acute dermal LD50 (rabbit)>2000mg/kg Due to polymerisation at the skin surface allergic reaction is unlikely to occur

Eye irritation:

Causes serious eye irritation.

Liquid product will bond eyelids. In a dry atmosphere (RH<50%) vapours may cause irritation and lachrymatory effect

Acute oral toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Ethyl 2-cyanoacrylate 7085-85-0	LD50	> 5.000 mg/kg	oral		rat	OECD Guideline 401 (Acute Oral Toxicity)
Hydroquinone 123-31-9	LD50	367 mg/kg	oral		rat	OECD Guideline 401 (Acute Oral Toxicity)

Acute dermal toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Ethyl 2-cyanoacrylate 7085-85-0	LD50	> 2.000 mg/kg	dermal		rabbit	OECD Guideline 402 (Acute Dermal Toxicity)

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Ethyl 2-cyanoacrylate 7085-85-0	slightly irritating	24 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Ethyl 2-cyanoacrylate 7085-85-0	irritating	72 h	rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
Ethyl 2-cyanoacrylate 7085-85-0	not sensitising		guinea pig	
Hydroquinone 123-31-9	sensitising	Guinea pig maximisat ion test	guinea pig	

Germ cell mutagenicity:

Hazardous components	Result	Type of study /	Metabolic	Species	Method
CAS-No.		Route of	activation /		
		administration	Exposure time		
Ethyl 2-cyanoacrylate	negative	mammalian cell	with and without		OECD Guideline 476 (In vitro
7085-85-0		gene mutation assay			Mammalian Cell Gene
					Mutation Test)
	negative	in vitro mammalian	with and without		OECD Guideline 473 (In vitro
		chromosome			Mammalian Chromosome
		aberration test			Aberration Test)
	negative	bacterial reverse			OECD Guideline 471
		mutation assay (e.g			(Bacterial Reverse Mutation
		Ames test)			Assay)
Hydroquinone	negative	bacterial reverse	with and without		EU Method B.13/14
123-31-9		mutation assay (e.g			(Mutagenicity)
		Ames test)			

Repeated dose toxicity

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Hydroquinone 123-31-9	NOAEL=>= 250 mg/kg	oral: gavage	14 days 5 days/week. 12 doses	rat	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)

SECTION 12: Ecological information

General ecological information:

Biological and Chemical Oxygen Demands (BOD and COD) are insignificant.

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

12.1. Toxicity

Ecotoxicity:

Do not empty into drains / surface water / ground water.

Hazardous components CAS-No.	Value type	Value	Acute Toxicity	Exposure time	Species	Method
	.,		Study			
Hydroquinone	LC50	0,17 mg/l	Fish	96 h	Brachydanio rerio (new name:	OECD Guideline
123-31-9		-			Danio rerio)	203 (Fish, Acute
						Toxicity Test)
Hydroquinone 123-31-9	EC50	0,29 mg/l	Daphnia	48 h	Daphnia magna	
Hydroquinone	EC50	0,335 mg/l	Algae	3 d	Selenastrum capricornutum	OECD Guideline
123-31-9		-	_		(new name: Pseudokirchnerella	201 (Alga, Growth
					subcapitata)	Inhibition Test)

12.2. Persistence and degradability

Persistence and Biodegradability:

No data available.

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
Ethyl 2-cyanoacrylate 7085-85-0		aerobic	57 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Hydroquinone 123-31-9	readily biodegradable	aerobic	75 - 81 %	EU Method C.4-E (Determination of the "Ready" BiodegradabilityClosed Bottle Test)

12.3. Bioaccumulative potential / 12.4. Mobility in soil

Mobility:

Cured adhesives are immobile.

Bioaccumulative potential:

No data available.

Hazardous components CAS-No.	LogKow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
Ethyl 2-cyanoacrylate 7085-85-0	0,776				22 °C	EU Method A.8 (Partition Coefficient)
Hydroquinone 123-31-9	1,03					

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Cured adhesive: Dispose of as water insoluble non-toxic solid chemical in authorised landfill or incinerate under controlled conditions.

Dispose of in accordance with local and national regulations.

Contribution of this product to waste is very insignificant in comparison to article in which it is used

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

14.1.	UN number				
	ADR	Not dangerous goods			
	RID	Not dangerous goods			
	ADNR	Not dangerous goods			
	IMDG	Not dangerous goods			
	IATA	3334			
14.2.	UN proper shipping name				
	ADR	Not dangerous goods			
	RID	Not dangerous goods			
	ADNR	Not dangerous goods			
	IMDG	Not dangerous goods			
	IATA	Aviation regulated liquid, n.o.s. (Cyanoacrylate ester)			
14.3.	Transport hazard class(es)				
	ADR	Not dangerous goods			
	RID	Not dangerous goods			
	ADNR	Not dangerous goods			
	IMDG	Not dangerous goods			
	IATA	9			
14.4.	Packaging group				
	ADR	Not dangerous goods			
	RID	Not dangerous goods			
	ADNR	Not dangerous goods			
	IMDG	Not dangerous goods			
	IATA	III			
14.5.	Environment	tal hazards			
	ADR	not applicable			
	RID	not applicable			
	ADNR	not applicable			
	IMDG	not applicable			
	IATA	not applicable			
14.6.	Special precautions for user				
	ADR	not applicable			
	RID	not applicable			
	ADNR	not applicable			
	IMDG	not applicable			
	IATA	Primary packs containing less than 500ml are unregulated by this mode of transport			
		and may be shipped unrestricted.			
14.7.	Transport in	bulk according to Annex II of MARPOL 73/78 and the IBC Code			

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content (1999/13/EC) < 3 %

15.2. Chemical safety assessment

A chemical safety assessment has been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

R22 Harmful if swallowed.

- R36/37/38 Irritating to eyes, respiratory system and skin.
- R40 Limited evidence of a carcinogenic effect.

R41 Risk of serious damage to eyes.

- R43 May cause sensitisation by skin contact.
- R50 Very toxic to aquatic organisms.
- R68 Possible risk of irreversible effects.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation. H335 May cause respiratory irritation.

H341 Suspected of causing genetic defects.

H351 Suspected of causing cancer.

H400 Very toxic to aquatic life.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Annex - Exposure Scenarios:

Exposure Scenarios for ethyl 2-cyanoacrylate can be downloaded under the following link: http://mymsds.henkel.com/mymsds/.470833..en.ANNEX_DE.15743123.0.DE.pdf Alternatively they can be accessed on the internet site www.mymsds.henkel.com by entering number 470833.